

Photometric test report

Family
Apollon® 21

Order number: 51MQ11WD2W55
EAN: 4069025336293

LP number
59879_6

serial
documentation
30.10.2025

siteco

Version recessed luminaire for lay-in mounting, square M625, wide distribution, UGR≤19 (L65≤3000cd/m²), tunable white

Lamps LED 2700 K ... 6500 K | CRI ≥ 90

Controlgear ECG-DALI

Setting factory setting: DIP-Step=8, colour temperature 4000K


Rated values at 4000 K
Net luminous flux = 4900 lm
Power consumption = 30.1 W
Luminous efficacy = 162.8 lm/W

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 442 cd/klm



Classifications

DIN 5040 A 5 0
CIE N1=59 N2=87 N3=97
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Apollon® 21	Order number: 51MQ11WD2W55 EAN: 4069025336293	LP number 59879_6
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	442.3	442.3	442.3	442.3	442.3	442.3	442.3	2.6	2.6
5°	439.1	439.5	440.0	440.2	440.5	440.5	440.7	21.0	23.7
10°	432.8	433.3	433.7	434.2	434.3	434.4	434.5	41.3	65.0
15°	423.3	423.6	424.0	424.3	424.5	424.7	424.9	60.2	125.2
20°	410.6	411.0	411.4	411.7	412.0	412.2	412.5	77.2	202.3
25°	394.7	395.1	395.4	395.8	396.1	396.5	396.9	91.7	294.0
30°	373.5	374.2	375.0	375.6	376.0	376.4	376.8	102.9	396.9
35°	345.9	347.0	348.2	349.1	350.1	350.8	351.6	109.7	506.6
40°	308.5	310.2	312.0	313.6	315.1	316.3	317.7	110.4	617.0
45°	246.9	250.2	253.9	256.8	259.4	261.1	263.2	99.3	716.3
50°	174.7	176.6	178.6	180.5	182.3	184.0	185.7	75.7	792.0
55°	106.6	116.0	127.0	134.7	140.6	143.2	147.5	59.0	851.0
60°	85.1	89.8	94.5	99.3	104.1	109.0	113.8	47.2	898.2
65°	70.6	72.1	73.5	74.9	74.3	73.7	73.1	36.5	934.7
70°	52.4	53.4	54.3	55.3	50.3	45.2	40.1	26.2	960.8
75°	31.6	34.9	38.1	41.4	38.4	35.4	32.4	19.4	980.2
80°	24.2	24.2	24.3	24.3	26.2	28.0	29.8	13.9	994.1
85°	10.7	10.3	9.9	9.6	10.4	11.2	12.1	5.7	999.8
90°	0.3	0.3	0.4	0.4	0.4	0.4	0.4	0.2	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0


Photometric test report

Family Apollon® 21			Order number: 51MQ11WD2W55 EAN: 4069025336293							LP number 59879_6	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	16.0	17.6	16.4	17.9	18.2	16.6	18.2	17.0	18.5	18.8
	3H	16.9	18.3	17.3	18.7	19.0	17.3	18.7	17.7	19.0	19.4
	4H	17.3	18.6	17.7	18.9	19.3	17.5	18.9	17.9	19.2	19.6
	6H	17.6	18.8	18.0	19.2	19.6	18.0	19.2	18.4	19.5	19.9
	8H	17.8	18.9	18.2	19.3	19.7	18.2	19.3	18.7	19.7	20.1
	12H	17.9	18.9	18.3	19.3	19.7	18.3	19.4	18.8	19.8	20.2
4H	2H	16.5	17.8	16.9	18.2	18.5	17.0	18.3	17.4	18.7	19.0
	3H	17.6	18.7	18.0	19.1	19.5	17.8	18.9	18.3	19.3	19.7
	4H	18.1	19.1	18.5	19.5	19.9	18.3	19.2	18.7	19.6	20.1
	6H	18.5	19.4	19.0	19.8	20.3	18.8	19.7	19.3	20.1	20.6
	8H	18.8	19.5	19.2	20.0	20.4	19.1	19.9	19.6	20.3	20.8
	12H	18.9	19.6	19.4	20.0	20.5	19.3	20.0	19.8	20.4	20.9
8H	4H	18.4	19.1	18.8	19.6	20.1	18.5	19.3	19.0	19.7	20.2
	6H	18.9	19.6	19.4	20.1	20.6	19.2	19.9	19.7	20.3	20.8
	8H	19.2	19.8	19.7	20.3	20.8	19.6	20.1	20.1	20.6	21.1
	12H	19.4	19.9	19.9	20.4	20.9	19.8	20.3	20.3	20.8	21.3
12H	4H	18.4	19.1	18.9	19.5	20.0	18.6	19.2	19.0	19.7	20.2
	6H	19.0	19.6	19.5	20.1	20.6	19.3	19.8	19.8	20.3	20.9
	8H	19.3	19.8	19.8	20.3	20.8	19.7	20.1	20.2	20.6	21.2

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 577 B = 577	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	5138.6	5207.7	5285.0	5345.8	5398.4	5434.6	5479.0
50°	3999.5	4043.7	4089.2	4132.1	4173.7	4212.7	4253.0
55°	2736.2	2975.9	3259.1	3455.4	3608.3	3674.3	3783.8
60°	2503.9	2643.6	2782.3	2923.0	3064.7	3208.4	3351.1
65°	2459.8	2509.9	2560.0	2610.1	2588.4	2566.7	2545.0
70°	2255.0	2296.7	2338.3	2380.0	2162.5	1945.0	1727.5
75°	1797.8	1982.4	2167.0	2351.6	2181.4	2011.3	1841.1
80°	2048.6	2052.6	2056.6	2060.6	2217.1	2373.4	2529.8
85°	1804.0	1741.7	1679.4	1617.3	1756.6	1896.1	2035.5

Photometric test report

Family Apollon® 21	Order number: 51MQ11WD2W55 EAN: 4069025336293	LP number 59879_6
Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85°		siteco



Photometric test report

Family Apollon® 21	Order number: 51MQ11WD2W55 EAN: 4069025336293	LP number 59879_6
Multilumen Table	environmental temperature: 25°C	siteco

DIP-Step	Switch Setting				Luminous flux [lm]	Power consumption [W]
	1	2	3	4		
0	OFF	OFF	OFF	OFF	6240	39.0
1	ON	OFF	OFF	OFF	5960	37.0
2	OFF	ON	OFF	OFF	5650	35.0
4	OFF	OFF	ON	OFF	5340	33.0
7	ON	ON	ON	OFF	5220	32.1
8	OFF	OFF	OFF	ON	4900	30.1
10	OFF	ON	OFF	ON	4590	28.1
12	OFF	OFF	ON	ON	4270	26.1
13	ON	OFF	ON	ON	3950	24.1
14	OFF	ON	ON	ON	3630	22.1