

Photometric test report

Family
Apollon® 41

Order number: 51MH11WD2N43
EAN: 4058352967201

LP number
59525_39

serial
documentation
22.12.2025

siteco

Version

recessed luminaire for lay-in mounting, square
M625, wide distribution, adjustable color
temperature: 4000 K | 6500 K, UGR≤19
($L_{65} \leq 3000 \text{ cd/m}^2$)

Lamps

LED 4000 K | CRI ≥ 80

Controlgear

ECG-DALI

Setting

DC mode (central or group accumulator) initial
emergency light level

Rated values


Net luminous flux = 530 lm
Power consumption = 4.8 W
Luminous efficacy = 110.4 lm/W

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 460 cd/klm



Classifications

DIN 5040 A 5 0
CIE N1=61 N2=87 N3=97
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Apollon® 41	Order number: 51MH11WD2N43 EAN: 4058352967201	LP number 59525_39
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	459.5	459.5	459.5	459.5	459.5	459.5	459.5	2.7	2.7
5°	458.5	458.6	458.6	458.5	458.4	458.4	458.3	21.9	24.7
10°	454.8	454.7	454.7	454.6	454.5	454.6	454.8	43.3	67.9
15°	447.3	447.2	447.2	447.1	447.1	447.4	447.7	63.4	131.4
20°	435.5	435.6	435.6	435.5	435.4	435.9	436.3	81.7	213.1
25°	418.3	418.2	418.1	417.9	417.9	418.8	419.8	96.9	310.0
30°	393.9	392.9	392.0	391.8	391.7	394.0	396.2	107.7	417.6
35°	359.0	358.1	357.3	357.0	356.7	359.8	362.9	112.7	530.3
40°	307.0	305.1	303.5	302.7	302.0	308.1	314.2	107.6	637.9
45°	209.9	219.5	229.2	228.5	227.9	223.6	219.4	86.8	724.7
50°	121.1	152.8	184.6	184.6	184.5	154.4	124.3	68.8	793.5
55°	85.1	114.1	143.1	142.6	142.1	114.1	86.2	55.5	849.0
60°	67.2	85.5	103.9	103.9	103.9	85.2	66.6	43.5	892.4
65°	60.3	67.1	74.0	73.7	73.5	66.6	59.7	34.4	926.8
70°	49.9	54.2	58.5	57.8	57.2	53.7	50.2	28.4	955.2
75°	35.1	40.7	46.3	45.7	45.1	40.2	35.4	22.4	977.6
80°	24.2	25.1	26.1	25.6	25.0	24.9	24.7	13.6	991.2
85°	13.0	14.1	15.3	15.2	15.1	14.0	12.9	7.9	999.1
90°	1.4	1.6	1.9	1.8	1.8	1.5	1.2	0.9	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Apollon® 41		Order number: 51MH11WD2N43 EAN: 4058352967201							LP number 59525_39	
UGR-Table		Standard room							siteco	
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)			
x	y									
2H	2H	8.3	9.8	8.6	10.1	10.4	8.3	9.8	8.6	10.1
	3H	9.2	10.6	9.6	10.9	11.3	9.2	10.6	9.6	10.9
	4H	9.6	10.9	10.0	11.3	11.7	9.6	10.9	10.0	11.3
	6H	10.0	11.2	10.4	11.6	12.0	10.0	11.2	10.5	11.6
	8H	10.2	11.3	10.7	11.7	12.1	10.3	11.4	10.7	11.7
	12H	10.4	11.4	10.8	11.8	12.2	10.4	11.4	10.8	11.8
4H	2H	8.8	10.1	9.2	10.5	10.8	8.8	10.1	9.2	10.5
	3H	10.0	11.1	10.4	11.5	11.9	10.0	11.1	10.4	11.5
	4H	10.7	11.6	11.1	12.0	12.5	10.6	11.6	11.1	12.0
	6H	11.2	12.0	11.6	12.5	12.9	11.1	12.0	11.6	12.4
	8H	11.4	12.2	11.9	12.6	13.1	11.4	12.2	11.8	12.6
	12H	11.6	12.3	12.1	12.7	13.2	11.6	12.3	12.1	12.7
8H	4H	11.0	11.8	11.5	12.2	12.7	11.0	11.8	11.4	12.2
	6H	11.7	12.3	12.1	12.8	13.3	11.6	12.3	12.1	12.7
	8H	12.0	12.5	12.5	13.0	13.5	11.9	12.5	12.4	13.0
	12H	12.3	12.7	12.8	13.2	13.8	12.2	12.7	12.7	13.2
12H	4H	11.1	11.7	11.5	12.2	12.7	11.0	11.7	11.5	12.2
	6H	11.7	12.3	12.2	12.8	13.3	11.7	12.3	12.2	12.7
	8H	12.1	12.6	12.6	13.1	13.6	12.1	12.5	12.6	13.0

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 555 B = 555	
C-planes	γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°
			Luminance in cd/m²				
45° 50° 55° 60°	γ	510.8	534.2	557.6	556.1	554.5	544.2
		324.0	409.1	494.2	494.1	494.0	413.4
		255.1	342.2	429.2	427.7	426.2	342.3
		231.2	294.3	357.4	357.4	357.4	293.3
65° 70° 75° 80°	γ	245.5	273.3	301.1	300.2	299.4	271.2
		250.8	272.5	294.2	290.9	287.6	270.0
		233.5	270.8	308.1	303.9	299.7	267.5
		239.3	248.8	258.3	253.2	248.1	246.6
85°	γ	256.1	279.1	302.1	300.4	298.6	277.0

Photometric test report

Family
Apollon® 41

Order number: 51MH11WD2N43
EAN: 4058352967201

LP number
59525_39

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

