

Photometric test report

Family
Round 21 M

Order number: 51MR36ND0321B
EAN: 4058352829936

LP number
59653_14

serial
documentation
22.01.2026



Version Suspended luminaire, micro prismatic cover, PMMA, wide distribution, direct-/ indirect distribution, aluminium housing, black, UGR≤19

Lamps LED 3000 K | CRI ≥ 80

Controlgear ECG-DALI

Rated values Net luminous flux = 7170 lm
Power consumption = 54.6 W
Luminous efficacy = 131.3 lm/W


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 459 cd/klm



Classifications

DIN 5040 B 5 3
CIE N1=66 N2=90 N3=98
N4=84 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 84.0%
 ϕ_o 16.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Round 21 M	Order number: 51MR36ND0321B EAN: 4058352829936	LP number 59653_14
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	459.1	459.1	459.1	459.1	459.1	459.1	459.1	0.1	0.1
1°	458.3	458.6	458.2	459.2	458.5	459.2	458.6	0.9	1.0
2°	458.4	458.7	458.0	458.1	458.4	458.6	459.0	1.8	2.7
3°	458.2	457.6	457.3	457.8	457.5	457.7	458.0	2.6	5.4
4°	456.3	456.8	456.8	457.2	456.0	457.0	456.1	3.5	8.9
5°	455.2	455.6	455.6	455.4	454.9	455.3	455.2	4.4	13.2
6°	453.9	454.5	454.0	454.2	453.3	454.1	454.1	5.2	18.4
7°	451.8	452.6	452.0	452.1	452.0	452.3	451.3	6.0	24.5
8°	450.4	450.9	450.4	450.6	450.1	450.9	449.2	6.9	31.3
9°	447.6	448.4	447.6	448.2	446.8	448.4	447.7	7.7	39.0
10°	445.2	446.0	445.3	445.8	444.5	445.7	444.6	8.5	47.5
11°	441.5	443.4	442.4	442.5	441.3	443.1	441.0	9.3	56.8
12°	438.9	440.2	439.2	440.1	438.0	439.8	438.0	10.0	66.8
13°	435.1	437.2	435.7	437.0	434.8	436.6	435.5	10.8	77.5
14°	431.4	434.0	432.4	433.6	431.6	433.2	431.9	11.5	89.0
15°	428.4	430.4	428.4	429.8	427.3	429.7	427.3	12.2	101.2
16°	424.0	426.2	424.9	426.4	423.8	425.9	423.6	12.9	114.0
17°	419.4	422.6	421.1	422.4	419.3	421.8	419.3	13.5	127.5
18°	415.4	418.3	416.6	418.3	414.7	417.9	415.7	14.1	141.7
19°	411.0	414.2	412.3	413.4	410.2	413.1	411.1	14.7	156.4
20°	406.3	409.4	407.5	408.9	405.8	408.8	406.7	15.3	171.7
21°	401.5	404.8	402.9	404.3	400.3	403.5	401.1	15.8	187.5
22°	396.7	399.3	397.7	399.2	395.1	397.8	396.4	16.3	203.8
23°	391.7	394.3	392.2	393.5	390.0	392.7	389.9	16.8	220.7
24°	385.3	388.8	386.1	387.8	384.1	387.0	384.1	17.2	237.9
25°	379.5	382.8	379.6	381.4	378.2	381.1	378.0	17.6	255.5
26°	373.8	376.5	373.2	375.2	371.7	374.0	371.1	18.0	273.5
27°	366.3	369.7	366.2	368.0	364.8	367.8	363.9	18.3	291.7
28°	359.8	362.2	358.8	361.2	358.0	360.2	356.5	18.5	310.3
29°	352.0	355.0	350.9	354.0	350.7	352.8	347.8	18.7	329.0
30°	344.7	347.1	342.9	346.4	342.8	345.3	339.9	18.9	347.9
31°	336.9	339.2	333.9	338.1	336.3	336.6	331.3	19.0	366.9
32°	329.0	330.7	326.0	329.7	328.4	328.6	322.6	19.1	386.0
33°	320.7	322.4	316.9	321.1	320.7	319.7	314.1	19.1	405.0
34°	311.5	313.5	308.1	312.3	312.2	311.4	304.9	19.1	424.1
35°	302.3	304.8	299.5	303.3	303.6	302.2	295.6	19.0	443.1
36°	292.9	295.6	290.2	293.8	294.5	292.6	286.5	18.9	462.0
37°	283.8	286.0	280.7	284.2	285.5	282.8	276.9	18.7	480.7
38°	274.4	275.8	271.2	274.0	276.2	272.6	267.7	18.5	499.1
39°	263.9	264.9	261.3	263.2	266.2	261.4	257.7	18.1	517.3
40°	252.7	253.5	250.1	251.9	256.2	249.6	248.3	17.8	535.0
41°	240.9	240.9	237.7	240.1	245.7	237.1	240.7	17.3	552.3
42°	228.3	228.0	225.7	227.9	233.8	224.4	229.3	16.7	569.1
43°	215.3	215.0	215.4	215.5	222.1	211.6	214.2	16.1	585.2
44°	202.5	201.9	200.4	203.2	209.7	199.8	197.9	15.4	600.6

Photometric test report

Family Round 21 M	Order number: 51MR36ND0321B EAN: 4058352829936	LP number 59653_14
Table of values for luminous intensities		Maximum luminous intensity



C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
45°	189.7	189.3	186.2	190.9	197.2	187.7	182.5	14.7	615.3
46°	177.4	177.1	173.6	177.8	188.9	175.9	169.9	14.0	629.4
47°	165.4	165.5	159.2	165.5	176.4	164.8	156.7	13.3	642.6
48°	153.8	154.8	148.9	153.7	165.0	154.2	147.7	12.6	655.2
49°	142.7	144.6	140.1	142.4	151.9	144.2	139.0	11.9	667.1
50°	131.1	135.0	132.4	132.1	139.8	134.6	132.6	11.3	678.4
51°	120.2	125.5	126.2	122.6	127.6	125.4	127.3	10.7	689.1
52°	109.1	116.5	119.8	113.6	115.5	116.5	122.2	10.0	699.1
53°	99.0	108.0	113.7	105.3	104.2	108.0	116.1	9.4	708.6
54°	89.9	99.7	107.2	96.9	93.7	99.6	109.3	8.8	717.4
55°	82.2	92.0	100.2	89.5	84.5	91.9	101.5	8.2	725.6
56°	77.9	84.9	92.7	82.4	76.9	84.9	92.5	7.7	733.3
57°	72.6	78.3	85.2	76.3	70.6	78.3	83.7	7.2	740.5
58°	67.4	72.2	77.7	71.1	65.6	72.5	75.4	6.7	747.1
59°	63.6	66.4	70.5	66.5	61.9	67.2	68.1	6.2	753.4
60°	61.0	61.2	63.9	62.3	59.2	62.2	61.8	5.9	759.2
61°	58.8	56.8	58.3	58.6	57.1	58.0	57.0	5.5	764.8
62°	56.4	53.2	53.7	55.3	55.3	54.6	53.0	5.3	770.1
63°	53.3	50.3	50.4	52.3	53.1	51.4	49.9	5.0	775.1
64°	49.8	47.5	48.1	49.0	50.2	48.0	47.7	4.8	779.9
65°	46.0	45.1	46.6	45.6	46.6	44.7	46.0	4.5	784.4
66°	42.4	42.6	45.5	42.3	42.9	41.5	45.4	4.3	788.8
67°	38.8	40.2	44.2	39.1	39.5	38.5	45.0	4.1	792.8
68°	35.5	38.0	42.3	36.4	36.6	36.0	43.6	3.9	796.7
69°	32.8	35.8	39.8	34.2	34.1	34.1	41.0	3.7	800.4
70°	30.8	33.8	37.1	32.9	32.0	32.6	37.9	3.5	803.9
71°	29.4	32.0	34.3	32.1	30.2	31.5	34.9	3.3	807.2
72°	28.5	30.3	31.9	31.0	28.7	30.4	32.2	3.2	810.4
73°	28.0	28.6	30.0	29.4	27.6	29.0	30.0	3.0	813.4
74°	27.7	27.2	28.6	27.5	27.0	27.4	28.4	2.9	816.3
75°	27.2	25.8	27.3	25.6	26.7	25.6	27.0	2.8	819.1
76°	26.4	24.3	25.9	23.9	26.0	24.0	25.8	2.7	821.8
77°	24.7	22.9	24.4	22.4	24.4	22.3	24.3	2.5	824.3
78°	22.4	21.3	22.5	20.9	22.4	20.7	22.7	2.3	826.6
79°	19.9	19.5	20.4	19.1	20.2	19.1	20.8	2.1	828.7
80°	17.5	17.7	18.4	17.3	18.2	17.5	18.7	1.9	830.7
81°	16.1	15.9	16.4	15.6	16.4	15.6	16.6	1.7	832.4
82°	14.7	14.1	14.7	14.0	14.8	13.9	14.5	1.6	834.0
83°	13.4	12.5	13.0	12.4	13.2	12.4	12.6	1.4	835.3
84°	11.9	10.9	11.3	10.8	11.6	10.8	11.0	1.2	836.6
85°	10.4	9.2	9.8	9.2	9.9	9.1	9.5	1.0	837.6
86°	8.8	7.4	8.2	7.5	8.3	7.4	7.9	0.9	838.5
87°	7.3	5.7	6.5	5.7	6.6	5.6	6.3	0.7	839.1
88°	5.0	4.1	4.8	4.2	4.7	4.1	4.7	0.5	839.6
89°	3.1	3.0	3.1	3.2	3.0	3.2	3.0	0.3	840.0

Photometric test report

Family Round 21 M	Order number: 51MR36ND0321B EAN: 4058352829936	LP number 59653_14
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	840.0
91°	5.3	4.7	4.9	4.5	4.6	4.4	4.5	0.5	840.5
92°	6.2	5.5	5.9	5.2	5.6	5.0	5.4	0.6	841.1
93°	6.8	6.2	6.5	6.0	6.3	6.0	6.1	0.7	841.8
94°	7.4	6.9	7.0	6.8	7.0	6.7	6.8	0.8	842.5
95°	7.8	7.4	7.6	7.2	7.6	7.3	7.3	0.8	843.3
96°	8.5	8.2	8.3	7.9	8.3	7.9	7.8	0.9	844.2
97°	9.0	8.7	8.8	8.6	8.8	8.6	8.3	0.9	845.2
98°	9.3	9.2	9.1	9.0	9.2	9.0	8.8	1.0	846.1
99°	9.8	9.7	9.7	9.5	9.6	9.4	9.3	1.0	847.2
100°	10.1	10.2	10.0	9.9	10.0	10.0	9.8	1.1	848.3
101°	10.6	10.5	10.6	10.4	10.5	10.5	10.4	1.1	849.4
102°	11.0	10.9	10.9	10.7	10.9	10.9	10.6	1.2	850.6
103°	11.4	11.3	11.3	11.1	11.4	11.3	11.1	1.2	851.8
104°	11.7	11.7	11.8	11.6	11.7	11.7	11.4	1.2	853.0
105°	12.2	12.1	12.1	12.0	12.2	12.0	11.8	1.3	854.3
106°	12.6	12.4	12.5	12.5	12.6	12.5	12.2	1.3	855.6
107°	12.9	12.8	13.0	12.9	13.0	13.0	12.7	1.4	857.0
108°	13.5	13.3	13.4	13.4	13.4	13.5	13.1	1.4	858.3
109°	14.0	13.8	13.8	13.8	14.0	13.9	13.5	1.4	859.8
110°	14.6	14.3	14.4	14.2	14.5	14.5	14.2	1.5	861.3
111°	15.2	14.8	15.0	14.8	15.0	15.0	14.6	1.5	862.8
112°	15.8	15.5	15.5	15.2	15.4	15.5	15.1	1.6	864.4
113°	16.3	16.0	16.0	15.7	16.0	16.0	15.6	1.6	866.0
114°	17.0	16.5	16.5	16.3	16.6	16.5	16.2	1.7	867.6
115°	17.5	17.1	17.1	17.0	17.2	17.1	16.8	1.7	869.3
116°	18.1	17.5	17.7	17.5	17.8	17.7	17.3	1.7	871.1
117°	18.5	18.1	18.3	18.2	18.3	18.2	18.1	1.8	872.8
118°	19.3	18.7	18.9	18.7	19.0	18.9	18.7	1.8	874.7
119°	20.0	19.3	19.6	19.5	19.7	19.4	19.2	1.9	876.5
120°	20.6	20.0	20.2	20.0	20.1	20.2	20.0	1.9	878.5
121°	21.2	20.7	20.9	20.8	20.9	20.8	20.6	2.0	880.4
122°	22.0	21.3	21.6	21.3	21.6	21.4	21.3	2.0	882.4
123°	22.7	22.1	22.3	22.1	22.3	22.0	21.9	2.0	884.5
124°	23.4	22.8	23.0	22.7	23.2	22.7	22.9	2.1	886.5
125°	24.1	23.5	23.7	23.5	24.0	23.5	23.5	2.1	888.7
126°	25.0	24.3	24.4	24.2	24.8	24.2	24.2	2.2	890.8
127°	25.7	24.9	25.2	25.0	25.6	25.0	25.0	2.2	893.0
128°	26.1	25.8	25.8	25.9	26.5	25.8	26.0	2.2	895.3
129°	26.5	26.6	26.6	26.6	27.3	26.6	26.8	2.3	897.5
130°	27.2	27.4	27.3	27.6	28.1	27.4	27.6	2.3	899.9
131°	28.1	28.4	28.0	28.3	28.8	28.3	28.3	2.3	902.2
132°	28.9	29.2	28.9	29.3	29.5	29.2	29.1	2.4	904.6
133°	29.8	30.2	29.9	30.3	30.3	30.1	30.0	2.4	907.0
134°	30.7	31.1	30.8	31.1	31.2	31.0	30.8	2.4	909.4

Photometric test report

Family Round 21 M	Order number: 51MR36ND0321B EAN: 4058352829936	LP number 59653_14
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm						Luminous flux in lm/klm		
135°	31.6	32.1	31.6	32.1	32.0	32.0	32.0	2.5	911.9
136°	32.6	32.9	32.5	33.0	32.8	32.9	32.9	2.5	914.4
137°	33.6	33.9	33.4	34.0	33.6	33.8	33.7	2.5	916.9
138°	34.7	34.9	34.5	35.0	34.4	34.9	34.6	2.5	919.5
139°	35.7	35.9	35.4	36.0	35.4	35.8	35.7	2.6	922.1
140°	36.6	36.9	36.4	37.1	36.5	36.9	36.7	2.6	924.6
141°	37.5	37.9	37.4	37.9	37.5	38.0	37.7	2.6	927.3
142°	38.5	39.0	38.4	39.1	38.4	39.0	38.8	2.6	929.9
143°	39.4	40.0	39.4	40.3	39.5	40.1	39.6	2.6	932.5
144°	40.5	41.1	40.5	41.3	40.5	41.2	40.6	2.6	935.1
145°	41.4	42.2	41.5	42.5	41.8	42.4	41.7	2.6	937.8
146°	42.5	43.3	42.7	43.5	42.9	43.6	42.9	2.6	940.4
147°	43.7	44.6	43.8	44.9	44.1	44.9	44.0	2.6	943.1
148°	45.0	45.8	45.0	46.1	45.4	46.1	45.3	2.7	945.7
149°	46.2	47.1	46.3	47.4	46.6	47.5	46.5	2.6	948.4
150°	47.6	48.5	47.7	48.8	47.9	48.8	47.9	2.6	951.0
151°	48.8	50.0	49.3	50.4	49.5	50.3	49.5	2.6	953.7
152°	50.3	51.3	50.7	51.9	51.1	51.8	51.0	2.6	956.3
153°	51.9	52.9	52.3	53.5	52.7	53.3	52.7	2.6	958.9
154°	53.6	54.6	53.9	55.0	54.2	54.9	54.2	2.6	961.5
155°	55.4	56.1	55.7	56.6	55.9	56.3	55.5	2.6	964.1
156°	57.3	57.5	57.2	57.8	57.3	57.8	57.1	2.6	966.7
157°	58.8	59.0	58.5	59.1	58.8	59.1	58.7	2.5	969.2
158°	60.1	60.2	59.9	60.3	60.0	60.1	60.1	2.5	971.7
159°	61.1	61.3	60.9	61.3	61.0	61.1	61.1	2.4	974.1
160°	62.1	62.2	61.9	62.0	61.9	61.9	62.0	2.3	976.4
161°	62.8	63.0	62.9	63.0	62.7	62.7	62.7	2.2	978.7
162°	63.5	63.8	63.4	63.7	63.3	63.4	63.3	2.2	980.8
163°	64.1	64.3	64.1	64.1	64.0	64.0	63.7	2.1	982.9
164°	64.7	64.8	64.6	64.7	64.5	64.4	64.1	2.0	984.8
165°	65.2	65.3	65.2	65.2	64.9	65.0	64.7	1.8	986.7
166°	65.7	65.8	65.6	65.7	65.4	65.3	65.1	1.7	988.4
167°	66.1	66.1	66.1	66.0	65.9	65.7	65.5	1.6	990.0
168°	66.6	66.5	66.4	66.4	66.2	66.0	65.8	1.5	991.5
169°	66.8	66.9	66.7	66.7	66.5	66.3	66.1	1.4	992.9
170°	67.1	67.0	66.8	66.9	66.7	66.6	66.4	1.3	994.2
171°	67.3	67.2	67.1	67.2	67.0	66.8	66.6	1.1	995.4
172°	67.5	67.4	67.2	67.3	67.1	66.9	67.0	1.0	996.4
173°	67.5	67.5	67.3	67.4	67.3	66.9	67.0	0.9	997.3
174°	67.7	67.5	67.4	67.6	67.4	67.1	67.3	0.8	998.1
175°	67.6	67.6	67.5	67.5	67.5	67.1	67.4	0.6	998.7
176°	67.5	67.6	67.5	67.5	67.5	67.1	67.4	0.5	999.2
177°	67.5	67.4	67.5	67.3	67.5	67.0	67.4	0.4	999.6
178°	67.4	67.3	67.5	67.4	67.4	67.1	67.5	0.3	999.9
179°	67.4	67.3	67.4	67.4	67.4	67.0	67.4	0.1	1000.0
180°	67.4	67.4	67.4	67.4	67.4	67.4	67.4	0.0	1000.0

Photometric test report

Family Round 21 M		Order number: 51MR36ND0321B EAN: 4058352829936							LP number 59653_14	
UGR-Table		Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)			
x	y									
2H	2H	15.8	17.0	16.3	17.6	18.2	15.8	17.0	16.4	17.6
	3H	16.3	17.4	16.9	18.0	18.7	16.3	17.4	16.9	18.0
	4H	16.7	17.7	17.3	18.3	19.0	16.7	17.8	17.3	18.4
	6H	17.1	18.0	17.7	18.6	19.3	17.1	18.1	17.8	18.7
	8H	17.2	18.1	17.9	18.7	19.4	17.3	18.1	17.9	18.7
	12H	17.4	18.2	18.0	18.8	19.6	17.4	18.2	18.1	18.8
4H	2H	16.0	17.0	16.6	17.6	18.3	16.0	17.0	16.6	17.6
	3H	16.8	17.6	17.4	18.3	19.0	16.8	17.6	17.4	18.3
	4H	17.3	18.0	17.9	18.7	19.4	17.3	18.0	17.9	18.7
	6H	17.8	18.5	18.5	19.1	19.9	17.8	18.5	18.5	19.1
	8H	18.0	18.5	18.6	19.2	20.0	17.9	18.5	18.6	19.2
	12H	18.2	18.7	18.9	19.4	20.2	18.2	18.7	18.9	19.4
8H	4H	17.4	18.0	18.1	18.7	19.5	17.4	18.0	18.1	18.7
	6H	18.0	18.5	18.8	19.2	20.1	18.0	18.5	18.8	19.2
	8H	18.4	18.8	19.1	19.5	20.4	18.4	18.8	19.1	19.5
	12H	18.7	19.1	19.5	19.8	20.7	18.7	19.0	19.4	19.8
12H	4H	17.5	18.0	18.2	18.7	19.5	17.5	18.0	18.2	18.7
	6H	18.2	18.6	18.9	19.3	20.2	18.2	18.6	18.9	19.3
	8H	18.5	18.9	19.3	19.6	20.5	18.5	18.9	19.3	19.6

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		D = 590	
C-planes	γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°
			Luminance in cd/m²				
45° 50° 55° 60°	γ	7034.5	7019.3	6907.6	7078.7	7314.6	6961.8
		5350.7	5507.8	5402.5	5389.4	5705.4	5492.7
		3757.2	4207.8	4582.4	4093.0	3862.0	4202.3
		3201.9	3211.9	3353.0	3267.0	3103.8	3261.2
65° 70° 75° 80°	γ	2853.8	2796.1	2893.0	2832.1	2891.8	2776.3
		2364.2	2590.5	2841.4	2523.8	2450.9	2498.5
		2754.2	2618.4	2770.4	2597.1	2706.6	2598.1
		2647.1	2677.3	2772.6	2613.8	2742.4	2636.5
85°	γ	3124.6	2778.6	2956.1	2769.5	2977.2	2742.4

Photometric test report

Family Round 21 M	Order number: 51MR36ND0321B EAN: 4058352829936	LP number 59653_14
Luminance values in cd/m²		serial
γ 65° γ 70° γ 75° γ 80° γ 85°		

