

Photometric test report

Family
Monsun® 21

Order number: 51FB107P437C3G
EAN: 4069025177766

LP number
58939_278



Version prismatic diffuser, opal, PMMA, wide distribution
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG
Setting emergency light operation: 3 h
Rated values Net luminous flux = 910 lm
 Power consumption = 4.5 W
 Luminous efficacy = 202.2 lm/W

serial
documentation
06.02.2026


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 340 cd/klm



Classifications

DIN 5040 A 4 1
 CIE N1=47 N2=77 N3=93
 N4=94 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 94.2%
 ϕ_o 5.8%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Monsun® 21	Order number: 51FB107P437C3G EAN: 4069025177766	LP number 58939_278
Table of values for luminous intensities		Maximum luminous intensity

sitEco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	340.1	340.1	340.1	340.1	340.1	340.1	340.1	2.0	2.0
5°	339.4	338.3	336.5	337.9	339.5	339.4	339.8	16.2	18.2
10°	333.5	333.0	331.2	332.8	334.6	334.7	335.0	31.7	49.9
15°	324.2	324.2	322.5	324.2	326.1	326.4	326.9	46.1	96.0
20°	311.0	311.6	310.1	311.9	314.1	314.7	315.3	58.6	154.6
25°	294.4	295.4	294.1	296.0	298.4	299.4	300.2	68.7	223.4
30°	275.2	276.6	275.1	276.8	279.4	280.7	281.6	76.1	299.5
35°	253.9	255.2	253.8	254.9	257.1	258.4	259.7	80.5	380.0
40°	231.8	232.9	231.3	231.1	232.5	233.8	235.1	81.9	461.9
45°	209.4	209.9	207.8	205.9	206.1	206.6	208.2	80.4	542.4
50°	187.2	187.1	184.8	181.3	179.3	178.3	179.7	76.6	619.0
55°	165.5	164.8	162.1	157.0	153.1	150.2	150.9	70.7	689.7
60°	143.9	142.9	139.5	133.7	127.9	123.2	122.7	63.3	753.0
65°	123.6	122.5	117.8	111.0	104.2	97.9	96.0	54.9	808.0
70°	104.7	103.3	97.1	89.4	81.7	74.3	71.0	45.8	853.8
75°	86.1	84.4	77.8	69.2	60.2	52.2	47.8	36.3	890.0
80°	68.0	66.1	60.2	50.5	40.7	32.1	26.9	26.7	916.7
85°	51.8	50.0	44.6	35.3	24.7	15.7	10.1	18.3	935.0
90°	40.8	39.2	34.4	26.0	15.9	6.9	1.8	13.1	948.2
95°	34.8	33.5	29.7	22.7	13.6	5.1	1.6	11.2	959.3
100°	29.9	28.8	25.4	19.2	11.3	3.7	1.4	9.4	968.7
105°	25.7	24.7	21.4	16.1	8.8	2.4	1.2	7.7	976.4
110°	22.1	20.9	18.0	13.0	6.6	1.4	1.1	6.1	982.5
115°	19.0	17.8	15.0	10.4	4.7	1.2	1.1	4.9	987.4
120°	16.0	14.8	12.2	7.9	3.1	1.2	1.0	3.8	991.2
125°	13.0	11.9	9.4	5.6	1.7	1.1	0.9	2.7	993.9
130°	10.1	9.1	6.9	3.7	1.4	1.1	1.0	1.9	995.9
135°	7.3	6.5	4.6	2.1	1.4	1.1	1.1	1.3	997.1
140°	4.8	4.1	2.7	1.7	1.4	1.1	1.1	0.8	998.0
145°	2.6	2.3	1.9	1.7	1.4	1.2	1.2	0.5	998.5
150°	2.0	2.0	1.9	1.6	1.3	1.3	1.3	0.4	998.9
155°	1.9	1.9	1.7	1.6	1.4	1.4	1.4	0.4	999.3
160°	1.7	1.7	1.6	1.4	1.4	1.4	1.4	0.3	999.6
165°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.2	999.8
170°	1.3	1.4	1.4	1.4	1.4	1.4	1.4	0.1	999.9
175°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.1	1000.0
180°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.0	1000.0

Photometric test report

Family Monsun® 21	Order number: 51FB107P437C3G EAN: 4069025177766	LP number 58939_278
----------------------	--	------------------------

UGR-Table		Standard room							siteco		
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	13.5	15.2	13.8	15.5	15.8	13.5	15.2	13.8	15.5	15.8
	3H	15.2	16.8	15.6	17.1	17.5	14.9	16.4	15.2	16.7	17.1
	4H	16.1	17.5	16.4	17.9	18.2	15.4	16.8	15.8	17.2	17.6
	6H	16.8	18.1	17.2	18.5	18.9	15.7	17.1	16.1	17.5	17.9
	8H	17.2	18.4	17.6	18.8	19.2	15.9	17.1	16.3	17.5	17.9
	12H	17.5	18.7	17.9	19.1	19.5	15.9	17.1	16.4	17.5	17.9
4H	2H	14.2	15.6	14.6	16.0	16.4	14.2	15.6	14.6	16.0	16.3
	3H	16.1	17.4	16.5	17.8	18.2	15.7	17.0	16.2	17.4	17.8
	4H	17.1	18.2	17.5	18.6	19.1	16.4	17.5	16.8	17.9	18.4
	6H	18.0	19.0	18.5	19.4	19.9	16.9	17.9	17.3	18.3	18.7
	8H	18.4	19.3	18.9	19.8	20.2	17.0	17.9	17.5	18.4	18.9
	12H	18.8	19.6	19.3	20.1	20.6	17.1	17.9	17.6	18.4	18.9
8H	4H	17.4	18.3	17.9	18.8	19.2	16.8	17.7	17.3	18.2	18.6
	6H	18.5	19.3	19.0	19.7	20.2	17.4	18.2	17.9	18.7	19.1
	8H	19.0	19.7	19.5	20.2	20.7	17.6	18.3	18.1	18.8	19.3
	12H	19.6	20.2	20.1	20.7	21.2	17.8	18.4	18.3	18.9	19.4
12H	4H	17.5	18.3	17.9	18.7	19.2	16.9	17.7	17.4	18.2	18.7
	6H	18.6	19.3	19.1	19.7	20.3	17.6	18.2	18.1	18.7	19.2
	8H	19.2	19.8	19.7	20.3	20.8	17.8	18.4	18.4	18.9	19.5

Luminance table		Max. for $\gamma \geq 65^\circ$			Photometric dimensions in mm:	L = 1590 B = 87	H(C0) = 21 H(C90) = 21	H(C180) = 21 H(C270) = 21
C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
γ	Luminance in cd/m²							
45°	1569.1	1578.8	1590.4	1623.6	1693.7	1787.5	1911.5	
50°	1488.2	1493.7	1504.9	1527.8	1585.6	1674.7	1810.6	
55°	1411.2	1412.8	1421.5	1432.7	1477.3	1555.2	1698.3	
60°	1335.0	1333.9	1336.2	1340.5	1369.9	1434.2	1578.6	
65°	1268.1	1265.1	1254.4	1246.4	1263.9	1312.3	1453.2	
70°	1210.6	1203.8	1172.6	1150.4	1152.5	1183.9	1318.5	
75°	1150.7	1139.9	1096.1	1051.7	1025.6	1036.2	1158.4	
80°	1087.2	1069.2	1025.4	946.3	880.4	851.1	947.3	
85°	1040.9	1018.9	971.2	872.1	741.3	635.2	661.6	

Photometric test report

Family
Monsun® 21

Order number: 51FB107P437C3G
EAN: 4069025177766

LP number
58939_278

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

