

Photometric test report

Family
Monsun® 21

Order number: 51FB10DP437C3H
EAN: 4069025177988

LP number
58939_269



Version prismatic diffuser, opal, PMMA, wide distribution
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG-DALI
Setting AC-mode
Rated values Net luminous flux = 3860 lm
 Power consumption = 25.5 W
 Luminous efficacy = 151.4 lm/W

serial
documentation
06.02.2026


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 340 cd/klm



Classifications

DIN 5040 A 4 1
 CIE N1=47 N2=77 N3=93
 N4=94 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 94.2%
 ϕ_o 5.8%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Monsun® 21	Order number: 51FB10DP437C3H EAN: 4069025177988	LP number 58939_269
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	340.1	340.1	340.1	340.1	340.1	340.1	340.1	2.0	2.0
5°	339.4	338.3	336.5	337.9	339.5	339.4	339.8	16.2	18.2
10°	333.5	333.0	331.2	332.8	334.6	334.7	335.0	31.7	49.9
15°	324.2	324.2	322.5	324.2	326.1	326.4	326.9	46.1	96.0
20°	311.0	311.6	310.1	311.9	314.1	314.7	315.3	58.6	154.6
25°	294.4	295.4	294.1	296.0	298.4	299.4	300.2	68.7	223.4
30°	275.2	276.6	275.1	276.8	279.4	280.7	281.6	76.1	299.5
35°	253.9	255.2	253.8	254.9	257.1	258.4	259.7	80.5	380.0
40°	231.8	232.9	231.3	231.1	232.5	233.8	235.1	81.9	461.9
45°	209.4	209.9	207.8	205.9	206.1	206.6	208.2	80.4	542.4
50°	187.2	187.1	184.8	181.3	179.3	178.3	179.7	76.6	619.0
55°	165.5	164.8	162.1	157.0	153.1	150.2	150.9	70.7	689.7
60°	143.9	142.9	139.5	133.7	127.9	123.2	122.7	63.3	753.0
65°	123.6	122.5	117.8	111.0	104.2	97.9	96.0	54.9	808.0
70°	104.7	103.3	97.1	89.4	81.7	74.3	71.0	45.8	853.8
75°	86.1	84.4	77.8	69.2	60.2	52.2	47.8	36.3	890.0
80°	68.0	66.1	60.2	50.5	40.7	32.1	26.9	26.7	916.7
85°	51.8	50.0	44.6	35.3	24.7	15.7	10.1	18.3	935.0
90°	40.8	39.2	34.4	26.0	15.9	6.9	1.8	13.1	948.2
95°	34.8	33.5	29.7	22.7	13.6	5.1	1.6	11.2	959.3
100°	29.9	28.8	25.4	19.2	11.3	3.7	1.4	9.4	968.7
105°	25.7	24.7	21.4	16.1	8.8	2.4	1.2	7.7	976.4
110°	22.1	20.9	18.0	13.0	6.6	1.4	1.1	6.1	982.5
115°	19.0	17.8	15.0	10.4	4.7	1.2	1.1	4.9	987.4
120°	16.0	14.8	12.2	7.9	3.1	1.2	1.0	3.8	991.2
125°	13.0	11.9	9.4	5.6	1.7	1.1	0.9	2.7	993.9
130°	10.1	9.1	6.9	3.7	1.4	1.1	1.0	1.9	995.9
135°	7.3	6.5	4.6	2.1	1.4	1.1	1.1	1.3	997.1
140°	4.8	4.1	2.7	1.7	1.4	1.1	1.1	0.8	998.0
145°	2.6	2.3	1.9	1.7	1.4	1.2	1.2	0.5	998.5
150°	2.0	2.0	1.9	1.6	1.3	1.3	1.3	0.4	998.9
155°	1.9	1.9	1.7	1.6	1.4	1.4	1.4	0.4	999.3
160°	1.7	1.7	1.6	1.4	1.4	1.4	1.4	0.3	999.6
165°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.2	999.8
170°	1.3	1.4	1.4	1.4	1.4	1.4	1.4	0.1	999.9
175°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.1	1000.0
180°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.0	1000.0

Photometric test report

Family Monsun® 21	Order number: 51FB10DP437C3H EAN: 4069025177988	LP number 58939_269
----------------------	--	------------------------

UGR-Table		Standard room							siTeco		
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	18.5	20.2	18.9	20.5	20.8	18.5	20.2	18.9	20.5	20.8
	3H	20.3	21.8	20.6	22.1	22.5	19.9	21.4	20.3	21.8	22.1
	4H	21.1	22.5	21.5	22.9	23.2	20.4	21.9	20.8	22.2	22.6
	6H	21.8	23.2	22.2	23.5	23.9	20.8	22.1	21.2	22.5	22.9
	8H	22.2	23.4	22.6	23.8	24.2	20.9	22.2	21.3	22.5	22.9
	12H	22.5	23.7	22.9	24.1	24.5	20.9	22.2	21.4	22.5	23.0
4H	2H	19.2	20.7	19.6	21.0	21.4	19.2	20.6	19.6	21.0	21.4
	3H	21.1	22.4	21.6	22.8	23.2	20.8	22.0	21.2	22.4	22.8
	4H	22.1	23.2	22.5	23.6	24.1	21.4	22.5	21.9	23.0	23.4
	6H	23.0	24.0	23.5	24.4	24.9	21.9	22.9	22.3	23.3	23.8
	8H	23.4	24.4	23.9	24.8	25.3	22.0	23.0	22.5	23.4	23.9
	12H	23.9	24.7	24.3	25.1	25.6	22.1	23.0	22.6	23.4	23.9
8H	4H	22.4	23.4	22.9	23.8	24.3	21.8	22.7	22.3	23.2	23.6
	6H	23.5	24.3	24.0	24.7	25.2	22.4	23.2	22.9	23.7	24.2
	8H	24.1	24.7	24.5	25.2	25.7	22.7	23.3	23.2	23.8	24.3
	12H	24.6	25.2	25.1	25.7	26.2	22.8	23.4	23.3	23.9	24.4
12H	4H	22.5	23.3	23.0	23.8	24.2	21.9	22.7	22.4	23.2	23.7
	6H	23.6	24.3	24.1	24.8	25.3	22.6	23.3	23.1	23.7	24.3
	8H	24.2	24.8	24.7	25.3	25.8	22.9	23.5	23.4	23.9	24.5

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1590 B = 87		H(C0) = 21 H(C90) = 21		H(C180) = 21 H(C270) = 21	
C-planes	γ	0°	15°	30°	45°	60°	75°	90°			
		180°	165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°	270°			
		Luminance in cd/m²									
45°		6655.8	6697.0	6746.0	6887.0	7184.3	7582.2	8108.2			
50°		6312.5	6335.9	6383.3	6480.7	6725.8	7103.6	7680.0			
55°		5985.8	5992.8	6029.5	6077.0	6266.4	6596.6	7204.0			
60°		5662.9	5658.1	5668.0	5686.0	5810.8	6083.5	6696.1			
65°		5379.0	5366.1	5320.7	5286.9	5361.2	5566.4	6164.3			
70°		5135.3	5106.3	4973.8	4879.8	4888.5	5021.7	5592.9			
75°		4881.1	4835.0	4649.5	4461.0	4350.3	4395.2	4913.6			
80°		4611.8	4535.2	4349.3	4014.1	3734.5	3610.2	4018.2			
85°		4415.2	4321.8	4119.7	3699.3	3144.5	2694.4	2806.2			

Photometric test report

Family
Monsun® 21

Order number: 51FB10DP437C3H
EAN: 4069025177988

LP number
58939_269

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Monsun® 21	Order number: 51FB10DP437C3H EAN: 4069025177988	LP number 58939_269
Dimming levels table		environmental temperature: 25°C

siteco

Luminous flux [%]	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	3860	25.5
95	241	252	3666	24.5
90	228	250	3472	23.4
85	215	248	3277	22.5
80	202	246	3082	21.4
75	190	243	2901	20.5
70	177	241	2705	19.4
65	164	238	2508	18.3
60	151	235	2310	17.3
55	139	232	2127	16.2
50	126	228	1932	15.1
45	113	224	1733	14.2
40	101	220	1550	13.2
35	88	215	1349	12.1
30	76	210	1164	11.2
25	63	203	964	10.2
20	51	195	778	9.3
15	38	184	577	8.3
10	26	171	390	7.5
5	13	145	188	6.9
4	12	142	172	6.8