

Photometric test report

Family
Monsun® 21

Order number: 51FB10DP467C3H
EAN: 4069025178060

LP number
58939_276



Version prismatic diffuser, opal, PMMA, wide distribution
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG-DALI
Setting emergency light operation: 3 h
Rated values Net luminous flux = 920 lm
 Power consumption = 4.5 W
 Luminous efficacy = 204.4 lm/W

serial
documentation
06.02.2026


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 340 cd/klm



Classifications

DIN 5040 A 4 1
 CIE N1=47 N2=77 N3=93
 N4=94 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 94.2%
 ϕ_o 5.8%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Monsun® 21	Order number: 51FB10DP467C3H EAN: 4069025178060	LP number 58939_276
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	340.1	340.1	340.1	340.1	340.1	340.1	340.1	2.0	2.0
5°	339.4	338.3	336.5	337.9	339.5	339.4	339.8	16.2	18.2
10°	333.5	333.0	331.2	332.8	334.6	334.7	335.0	31.7	49.9
15°	324.2	324.2	322.5	324.2	326.1	326.4	326.9	46.1	96.0
20°	311.0	311.6	310.1	311.9	314.1	314.7	315.3	58.6	154.6
25°	294.4	295.4	294.1	296.0	298.4	299.4	300.2	68.7	223.4
30°	275.2	276.6	275.1	276.8	279.4	280.7	281.6	76.1	299.5
35°	253.9	255.2	253.8	254.9	257.1	258.4	259.7	80.5	380.0
40°	231.8	232.9	231.3	231.1	232.5	233.8	235.1	81.9	461.9
45°	209.4	209.9	207.8	205.9	206.1	206.6	208.2	80.4	542.4
50°	187.2	187.1	184.8	181.3	179.3	178.3	179.7	76.6	619.0
55°	165.5	164.8	162.1	157.0	153.1	150.2	150.9	70.7	689.7
60°	143.9	142.9	139.5	133.7	127.9	123.2	122.7	63.3	753.0
65°	123.6	122.5	117.8	111.0	104.2	97.9	96.0	54.9	808.0
70°	104.7	103.3	97.1	89.4	81.7	74.3	71.0	45.8	853.8
75°	86.1	84.4	77.8	69.2	60.2	52.2	47.8	36.3	890.0
80°	68.0	66.1	60.2	50.5	40.7	32.1	26.9	26.7	916.7
85°	51.8	50.0	44.6	35.3	24.7	15.7	10.1	18.3	935.0
90°	40.8	39.2	34.4	26.0	15.9	6.9	1.8	13.1	948.2
95°	34.8	33.5	29.7	22.7	13.6	5.1	1.6	11.2	959.3
100°	29.9	28.8	25.4	19.2	11.3	3.7	1.4	9.4	968.7
105°	25.7	24.7	21.4	16.1	8.8	2.4	1.2	7.7	976.4
110°	22.1	20.9	18.0	13.0	6.6	1.4	1.1	6.1	982.5
115°	19.0	17.8	15.0	10.4	4.7	1.2	1.1	4.9	987.4
120°	16.0	14.8	12.2	7.9	3.1	1.2	1.0	3.8	991.2
125°	13.0	11.9	9.4	5.6	1.7	1.1	0.9	2.7	993.9
130°	10.1	9.1	6.9	3.7	1.4	1.1	1.0	1.9	995.9
135°	7.3	6.5	4.6	2.1	1.4	1.1	1.1	1.3	997.1
140°	4.8	4.1	2.7	1.7	1.4	1.1	1.1	0.8	998.0
145°	2.6	2.3	1.9	1.7	1.4	1.2	1.2	0.5	998.5
150°	2.0	2.0	1.9	1.6	1.3	1.3	1.3	0.4	998.9
155°	1.9	1.9	1.7	1.6	1.4	1.4	1.4	0.4	999.3
160°	1.7	1.7	1.6	1.4	1.4	1.4	1.4	0.3	999.6
165°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.2	999.8
170°	1.3	1.4	1.4	1.4	1.4	1.4	1.4	0.1	999.9
175°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.1	1000.0
180°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.0	1000.0

Photometric test report

Family Monsun® 21			Order number: 51FB10DP467C3H EAN: 4069025178060							LP number 58939_276		
UGR-Table									Standard room		siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5		0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3		0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2		0.2
Room dimensions		View crosswise (C0)					View endwise (C90)					
x	y											
2H	2H	13.5	15.2	13.9	15.5	15.9	13.5	15.2	13.9	15.5	15.8	
	3H	15.3	16.8	15.6	17.1	17.5	14.9	16.4	15.3	16.8	17.1	
	4H	16.1	17.5	16.5	17.9	18.3	15.4	16.9	15.8	17.2	17.6	
	6H	16.8	18.2	17.3	18.6	18.9	15.8	17.1	16.2	17.5	17.9	
	8H	17.2	18.5	17.6	18.8	19.2	15.9	17.2	16.3	17.6	18.0	
	12H	17.5	18.7	18.0	19.1	19.5	16.0	17.2	16.4	17.6	18.0	
4H	2H	14.2	15.7	14.6	16.0	16.4	14.2	15.7	14.6	16.0	16.4	
	3H	16.2	17.4	16.6	17.8	18.2	15.8	17.0	16.2	17.4	17.8	
	4H	17.1	18.3	17.6	18.7	19.1	16.4	17.6	16.9	18.0	18.4	
	6H	18.0	19.0	18.5	19.5	19.9	16.9	17.9	17.4	18.3	18.8	
	8H	18.5	19.4	18.9	19.8	20.3	17.1	18.0	17.5	18.4	18.9	
	12H	18.9	19.7	19.4	20.1	20.6	17.2	18.0	17.6	18.4	18.9	
8H	4H	17.4	18.4	17.9	18.8	19.3	16.8	17.8	17.3	18.2	18.7	
	6H	18.5	19.3	19.0	19.8	20.3	17.5	18.2	17.9	18.7	19.2	
	8H	19.1	19.8	19.6	20.2	20.7	17.7	18.4	18.2	18.8	19.4	
	12H	19.6	20.2	20.1	20.7	21.2	17.8	18.4	18.3	18.9	19.4	
12H	4H	17.5	18.3	18.0	18.8	19.3	16.9	17.7	17.4	18.2	18.7	
	6H	18.6	19.3	19.1	19.8	20.3	17.6	18.3	18.1	18.8	19.3	
	8H	19.2	19.8	19.7	20.3	20.8	17.9	18.5	18.4	19.0	19.5	

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1590 B = 87	H(C0) = 21 H(C90) = 21	H(C180) = 21 H(C270) = 21
C-planes	γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
			Luminance in cd/m²					
45° 50° 55° 60°		1586.3	1596.2	1607.9	1641.5	1712.3	1807.2	1932.5
		1504.5	1510.1	1521.4	1544.6	1603.0	1693.1	1830.5
		1426.7	1428.3	1437.1	1448.4	1493.6	1572.3	1717.0
		1349.7	1348.6	1350.9	1355.2	1385.0	1450.0	1596.0
65° 70° 75° 80°		1282.0	1279.0	1268.1	1260.1	1277.8	1326.7	1469.2
		1224.0	1217.0	1185.5	1163.1	1165.1	1196.9	1333.0
		1163.4	1152.4	1108.2	1063.2	1036.9	1047.6	1171.1
		1099.2	1080.9	1036.6	956.7	890.1	860.5	957.7
85°		1052.3	1030.1	981.9	881.7	749.5	642.2	668.8

Photometric test report

Family Monsun® 21	Order number: 51FB10DP467C3H EAN: 4069025178060	LP number 58939_276
------------------------------------	--	--------------------------------------

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

