




Photometric test report

Family Spot 21 Performance	Order number: 51SD33MB11D3B EAN: 4069025538833	LP number 59945_9
	Version housing, black, reflector, cover glass, transparent, medium distribution Lamps LED 4000 K CRI ≥ 90 Controlgear ECG Multilumen	serial documentation 11.05.2026
	Setting factory setting: DIP-Step=4 Rated values Net luminous flux = 3050 lm Power consumption = 19.1 W Luminous efficacy = 159.7 lm/W	

Luminous intensity in cd/klm C180-0 **Imax: 2875 cd/klm**



Classifications	
DIN 5040	A 8 0
CIE	N1=99 N2=100 N3=100 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Spot 21 Performance	Order number: 51SD33MB11D3B EAN: 4069025538833	LP number 59945_9
---	---	------------------------------------



Table of values for luminous intensities	Maximum luminous intensity
---	-----------------------------------

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm	Luminous flux in lm/klm	
0,0°	2875.4	4.3	4.3
2,5°	2846.8	34.0	38.3
5,0°	2749.2	65.7	104.0
7,5°	2546.8	91.1	195.2
10,0°	2270.6	108.1	303.2
12,5°	1962.1	116.4	419.7
15,0°	1613.1	114.4	534.1
17,5°	1309.8	108.0	642.1
20,0°	1010.8	94.8	736.9
22,5°	749.1	78.6	815.4
25,0°	553.8	64.2	879.6
27,5°	382.5	48.4	928.0
30,0°	247.7	34.0	962.0
32,5°	136.4	20.1	982.0
35,0°	55.9	8.8	990.8
37,5°	13.7	2.3	993.1
40,0°	8.1	1.4	994.5
42,5°	5.6	1.0	995.6
45,0°	4.1	0.8	996.4
47,5°	3.1	0.6	997.0
50,0°	2.4	0.5	997.5
52,5°	2.0	0.4	998.0
55,0°	1.8	0.4	998.4
57,5°	1.7	0.4	998.8
60,0°	1.4	0.3	999.1
62,5°	1.1	0.3	999.4
65,0°	0.9	0.2	999.6
67,5°	0.7	0.2	999.8
70,0°	0.5	0.1	999.9
72,5°	0.3	0.1	1000.0
75,0°	0.1	0.0	1000.0
77,5°	0.0	0.0	1000.0
80,0°	0.0	0.0	1000.0
82,5°	0.0	0.0	1000.0
85,0°	0.0	0.0	1000.0
87,5°	0.0	0.0	1000.0
90,0°	0.0	0.0	1000.0

Photometric test report

Family Spot 21 Performance	Order number: 51SD33MB11D3B EAN: 4069025538833	LP number 59945_9
--------------------------------------	---	-----------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	12.7	13.7	13.1	14.0	14.3	12.7	13.7	13.1	14.0	14.3
	3H	12.5	13.4	12.9	13.7	14.1	12.5	13.4	12.9	13.7	14.1
	4H	12.5	13.2	12.9	13.6	13.9	12.5	13.2	12.9	13.6	13.9
	6H	12.4	13.0	12.8	13.4	13.8	12.4	13.0	12.8	13.4	13.8
	8H	12.5	13.0	12.9	13.3	13.8	12.5	13.0	12.9	13.3	13.8
	12H	12.4	12.9	12.9	13.3	13.7	12.4	12.9	12.9	13.3	13.7
4H	2H	12.5	13.2	12.9	13.6	13.9	12.5	13.2	12.9	13.6	13.9
	3H	12.3	12.9	12.7	13.3	13.7	12.3	12.9	12.7	13.3	13.7
	4H	12.1	12.7	12.6	13.1	13.5	12.1	12.7	12.6	13.1	13.5
	6H	12.0	12.5	12.5	12.9	13.4	12.0	12.5	12.5	12.9	13.4
	8H	12.0	12.4	12.5	12.8	13.3	12.0	12.4	12.5	12.8	13.3
	12H	12.0	12.3	12.5	12.7	13.2	12.0	12.3	12.5	12.7	13.2
8H	4H	12.0	12.4	12.5	12.8	13.3	12.0	12.4	12.5	12.8	13.3
	6H	11.9	12.2	12.4	12.6	13.2	11.9	12.2	12.4	12.6	13.2
	8H	11.8	12.1	12.3	12.5	13.1	11.8	12.1	12.3	12.5	13.1
	12H	11.7	11.9	12.3	12.4	13.0	11.7	11.9	12.3	12.4	13.0
12H	4H	12.0	12.3	12.5	12.7	13.2	12.0	12.3	12.5	12.7	13.2
	6H	11.8	12.0	12.3	12.5	13.1	11.8	12.0	12.3	12.5	13.1
	8H	11.7	11.9	12.3	12.4	13.0	11.7	11.9	12.3	12.4	13.0


Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 82
------------------------	---	---

C-planes	0°
γ	Luminance in cd/m²
45,0°	3362.6
50,0°	2165.4
55,0°	1819.5
60,0°	1624.0
65,0°	1235.4
70,0°	847.7
75,0°	223.1
80,0°	0.0
85,0°	0.0

Photometric test report

Family Spot 21 Performance	Order number: 51SD33MB11D3B EAN: 4069025538833	LP number 59945_9
--------------------------------------	---	-----------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**



Photometric test report

Family Spot 21 Performance	Order number: 51SD33MB11D3B EAN: 4069025538833	LP number 59945_9
--------------------------------------	---	------------------------------------

Multilumen Table	environmental temperature: 25°C	sITeco
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]
	1	2	3		
0	OFF	OFF	OFF	4190	27.0
1	ON	OFF	OFF	3910	25.0
2	OFF	ON	OFF	3630	23.0
3	ON	ON	OFF	3340	21.0
4	OFF	OFF	ON	3050	19.1
5	ON	OFF	ON	2760	17.1
6	OFF	ON	ON	2470	15.2
7	ON	ON	ON	2170	13.4