




Photometric test report

Family Spot 21 Performance	Order number: 51SD34DB11B3B EAN: 4069025538857	LP number 59946_10										
	<table border="0"> <tr> <td>Version</td> <td>housing, black, reflector, cover glass, transparent, wide distribution</td> </tr> <tr> <td>Lamps</td> <td>LED 3000 K CRI ≥ 90</td> </tr> <tr> <td>Controlgear</td> <td>ECG-DALI-Multilumen</td> </tr> <tr> <td>Setting</td> <td>factory setting: DIP-Step=7</td> </tr> <tr> <td>Rated values</td> <td> Net luminous flux = 2980 lm Power consumption = 20.4 W Luminous efficacy = 146.1 lm/W </td> </tr> </table>	Version	housing, black, reflector, cover glass, transparent, wide distribution	Lamps	LED 3000 K CRI ≥ 90	Controlgear	ECG-DALI-Multilumen	Setting	factory setting: DIP-Step=7	Rated values	Net luminous flux = 2980 lm Power consumption = 20.4 W Luminous efficacy = 146.1 lm/W	serial documentation 11.05.2026 
Version	housing, black, reflector, cover glass, transparent, wide distribution											
Lamps	LED 3000 K CRI ≥ 90											
Controlgear	ECG-DALI-Multilumen											
Setting	factory setting: DIP-Step=7											
Rated values	Net luminous flux = 2980 lm Power consumption = 20.4 W Luminous efficacy = 146.1 lm/W											

Luminous intensity in cd/klm C180-0 **Imax: 1937 cd/klm**



Classifications	
DIN 5040	A 8 0
CIE	N1=99 N2=100 N3=100 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Spot 21 Performance	Order number: 51SD34DB11B3B EAN: 4069025538857	LP number 59946_10
--------------------------------------	---	------------------------------



Table of values for luminous intensities	Maximum luminous intensity
---	-----------------------------------

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm	Luminous flux in lm/klm	
0,0°	1937.4	2.9	2.9
2,5°	1918.5	22.9	25.8
5,0°	1874.2	44.8	70.6
7,5°	1803.7	64.5	135.2
10,0°	1708.3	81.3	216.5
12,5°	1592.6	94.5	311.0
15,0°	1453.4	103.1	414.1
17,5°	1289.1	106.3	520.4
20,0°	1113.4	104.4	624.7
22,5°	938.6	98.5	723.2
25,0°	755.5	87.5	810.7
27,5°	560.7	71.0	881.7
30,0°	388.9	53.3	935.0
32,5°	229.8	33.8	968.9
35,0°	101.6	16.0	984.8
37,5°	29.4	4.9	989.7
40,0°	14.2	2.5	992.2
42,5°	9.4	1.7	994.0
45,0°	6.8	1.3	995.3
47,5°	5.0	1.0	996.3
50,0°	3.8	0.8	997.1
52,5°	2.9	0.6	997.8
55,0°	2.3	0.5	998.3
57,5°	1.9	0.4	998.7
60,0°	1.5	0.4	999.1
62,5°	1.2	0.3	999.4
65,0°	0.9	0.2	999.6
67,5°	0.7	0.2	999.8
70,0°	0.5	0.1	999.9
72,5°	0.3	0.1	1000.0
75,0°	0.1	0.0	1000.0
77,5°	0.0	0.0	1000.0
80,0°	0.0	0.0	1000.0
82,5°	0.0	0.0	1000.0
85,0°	0.0	0.0	1000.0
87,5°	0.0	0.0	1000.0
90,0°	0.0	0.0	1000.0

Photometric test report

Family Spot 21 Performance	Order number: 51SD34DB11B3B EAN: 4069025538857	LP number 59946_10
--------------------------------------	---	------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	16.2	17.2	16.6	17.6	17.9	16.2	17.2	16.6	17.6	17.9
	3H	16.1	16.9	16.4	17.3	17.6	16.1	16.9	16.4	17.3	17.6
	4H	16.0	16.8	16.4	17.1	17.5	16.0	16.8	16.4	17.1	17.5
	6H	15.9	16.6	16.3	17.0	17.4	15.9	16.6	16.3	17.0	17.4
	8H	16.0	16.5	16.4	16.9	17.3	16.0	16.5	16.4	16.9	17.3
	12H	16.0	16.4	16.4	16.8	17.2	16.0	16.4	16.4	16.8	17.2
4H	2H	16.0	16.8	16.4	17.1	17.5	16.0	16.8	16.4	17.1	17.5
	3H	15.8	16.4	16.2	16.8	17.2	15.8	16.4	16.2	16.8	17.2
	4H	15.6	16.2	16.1	16.7	17.1	15.6	16.2	16.1	16.7	17.1
	6H	15.5	16.0	16.0	16.5	17.0	15.5	16.0	16.0	16.5	17.0
	8H	15.5	15.9	16.0	16.4	16.9	15.5	15.9	16.0	16.4	16.9
	12H	15.5	15.8	16.0	16.3	16.8	15.5	15.8	16.0	16.3	16.8
8H	4H	15.5	15.9	16.0	16.4	16.9	15.5	15.9	16.0	16.4	16.9
	6H	15.4	15.7	15.9	16.2	16.7	15.4	15.7	15.9	16.2	16.7
	8H	15.3	15.6	15.8	16.1	16.6	15.3	15.6	15.8	16.1	16.6
	12H	15.3	15.5	15.8	16.0	16.6	15.3	15.5	15.8	16.0	16.6
12H	4H	15.5	15.8	16.0	16.3	16.8	15.5	15.8	16.0	16.3	16.8
	6H	15.4	15.6	15.9	16.1	16.6	15.4	15.6	15.9	16.1	16.6
	8H	15.3	15.5	15.8	16.0	16.6	15.3	15.5	15.8	16.0	16.6


Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 82
------------------------	---	---

C-planes	0°
γ	Luminance in cd/m²
45,0°	5440.9
50,0°	3344.7
55,0°	2268.6
60,0°	1697.4
65,0°	1204.4
70,0°	826.6
75,0°	218.0
80,0°	0.0
85,0°	0.0

Photometric test report

Family Spot 21 Performance	Order number: 51SD34DB11B3B EAN: 4069025538857	LP number 59946_10
--------------------------------------	---	------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**



Photometric test report

Family Spot 21 Performance	Order number: 51SD34DB11B3B EAN: 4069025538857	LP number 59946_10
--------------------------------------	---	------------------------------

Multilumen Table	environmental temperature: 25°C	sITeco
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting				Luminous flux [lm]	Power consumption [W]
	1	2	3	4		
11	ON	OFF	ON	ON	4080	28.6
10	ON	OFF	ON	OFF	3810	26.4
9	ON	OFF	OFF	ON	3540	24.4
8	ON	OFF	OFF	OFF	3260	22.3
7	OFF	ON	ON	ON	2980	20.4
6	OFF	ON	ON	OFF	2690	18.3
5	OFF	ON	OFF	ON	2400	16.2
4	OFF	ON	OFF	OFF	2110	14.3
3	OFF	OFF	ON	ON	1810	12.2
2	OFF	OFF	ON	OFF	1510	10.4
1	OFF	OFF	OFF	ON	1210	8.5
0	OFF	OFF	OFF	OFF	900	6.6