




Photometric test report

Family Spot 21 Standard	Order number: 51SE12DA2CA2C EAN: 4069025446763	LP number 59930_13
	Version housing, white, reflector, lens PMMA, medium distribution Lamps LED 2700 K CRI ≥ 90 Controlgear ECG-DALI-Multilumen Setting factory setting: DIP-Step=6	serial documentation 11.05.2026
	Rated values Net luminous flux = 2250 lm Power consumption = 17.7 W Luminous efficacy = 127.1 lm/W	

Luminous intensity in cd/klm C180-0 **Imax: 2926 cd/klm**



Classifications	
DIN 5040	A 8 0
CIE	N1=94 N2=98 N3=100 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Spot 21 Standard	Order number: 51SE12DA2CA2C EAN: 4069025446763	LP number 59930_13
-----------------------------------	---	------------------------------

sITeco

Table of values for luminous intensities	Maximum luminous intensity
---	-----------------------------------

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm	Luminous flux in lm/klm	
0,0°	2925.8	4.4	4.4
2,5°	2880.2	34.4	38.8
5,0°	2743.4	65.5	104.4
7,5°	2469.4	88.4	192.7
10,0°	2066.4	98.4	291.1
12,5°	1641.6	97.4	388.5
15,0°	1288.9	91.5	479.9
17,5°	1036.1	85.4	565.3
20,0°	838.8	78.6	644.0
22,5°	662.8	69.5	713.5
25,0°	519.2	60.2	773.7
27,5°	397.3	50.3	824.0
30,0°	287.9	39.5	863.4
32,5°	189.6	27.9	891.4
35,0°	126.2	19.8	911.2
37,5°	88.2	14.7	925.9
40,0°	65.4	11.5	937.4
42,5°	51.6	9.6	947.0
45,0°	39.6	7.7	954.7
47,5°	31.5	6.4	961.0
50,0°	25.2	5.3	966.3
52,5°	21.1	4.6	970.9
55,0°	19.1	4.3	975.2
57,5°	17.3	4.0	979.2
60,0°	15.4	3.6	982.8
62,5°	13.7	3.3	986.2
65,0°	11.8	2.9	989.1
67,5°	9.9	2.5	991.6
70,0°	8.2	2.1	993.7
72,5°	6.8	1.8	995.5
75,0°	5.5	1.5	997.0
77,5°	4.3	1.2	998.1
80,0°	3.2	0.9	999.0
82,5°	2.1	0.6	999.6
85,0°	1.2	0.3	999.9
87,5°	0.3	0.1	1000.0
90,0°	0.0	0.0	1000.0

Photometric test report

Family Spot 21 Standard	Order number: 51SE12DA2CA2C EAN: 4069025446763	LP number 59930_13
----------------------------	---	-----------------------

UGR-Table	Standard room	siteco								
-----------	---------------	--------	--	--	--	--	--	--	--	--

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	19.4	20.4	19.7	20.7	21.1	19.4	20.4	19.7	20.7	21.1
	3H	19.8	20.8	20.2	21.1	21.5	19.8	20.8	20.2	21.1	21.5
	4H	20.1	20.9	20.5	21.2	21.6	20.1	20.9	20.5	21.2	21.6
	6H	20.2	20.9	20.6	21.3	21.7	20.2	20.9	20.6	21.3	21.7
	8H	20.4	20.9	20.8	21.3	21.7	20.4	20.9	20.8	21.3	21.7
	12H	20.4	20.9	20.8	21.3	21.7	20.4	20.9	20.8	21.3	21.7
4H	2H	19.5	20.3	19.9	20.7	21.1	19.5	20.3	19.9	20.7	21.1
	3H	20.1	20.8	20.6	21.2	21.6	20.1	20.8	20.6	21.2	21.6
	4H	20.4	21.0	20.8	21.4	21.9	20.4	21.0	20.8	21.4	21.9
	6H	20.6	21.1	21.1	21.6	22.0	20.6	21.1	21.1	21.6	22.0
	8H	20.7	21.1	21.2	21.6	22.1	20.7	21.1	21.2	21.6	22.1
	12H	20.8	21.1	21.3	21.6	22.1	20.8	21.1	21.3	21.6	22.1
8H	4H	20.5	20.9	20.9	21.4	21.8	20.5	20.9	20.9	21.4	21.8
	6H	20.7	21.1	21.2	21.6	22.1	20.7	21.1	21.2	21.6	22.1
	8H	20.8	21.1	21.3	21.6	22.2	20.8	21.1	21.3	21.6	22.2
	12H	20.9	21.1	21.5	21.7	22.2	20.9	21.1	21.5	21.7	22.2
12H	4H	20.5	20.8	21.0	21.3	21.8	20.5	20.8	21.0	21.3	21.8
	6H	20.8	21.0	21.3	21.5	22.1	20.8	21.0	21.3	21.5	22.1
	8H	20.9	21.1	21.4	21.6	22.2	20.9	21.1	21.4	21.6	22.2


Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 62
-----------------	---------------------------------	--------------------------------------

C-planes	0°
γ	Luminance in cd/m ²
45,0°	41697.8
50,0°	29222.1
55,0°	24788.5
60,0°	22898.9
65,0°	20895.0
70,0°	17941.9
75,0°	15903.3
80,0°	13789.5
85,0°	10303.9

Photometric test report

Family Spot 21 Standard	Order number: 51SE12DA2CA2C EAN: 4069025446763	LP number 59930_13
-----------------------------------	---	------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85°



Photometric test report

Family Spot 21 Standard	Order number: 51SE12DA2CA2C EAN: 4069025446763	LP number 59930_13
-----------------------------------	---	------------------------------

Multilumen Table	environmental temperature: 25°C	sITeco
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting				Luminous flux [lm]	Power consumption [W]
	1	2	3	4		
11	ON	OFF	ON	ON	3330	28.0
10	ON	OFF	ON	OFF	3120	25.9
9	ON	OFF	OFF	ON	2910	23.7
8	ON	OFF	OFF	OFF	2700	21.6
7	OFF	ON	ON	ON	2480	19.8
6	OFF	ON	ON	OFF	2250	17.7
5	OFF	ON	OFF	ON	2020	15.6
4	OFF	ON	OFF	OFF	1780	13.8
3	OFF	OFF	ON	ON	1540	11.7
2	OFF	OFF	ON	OFF	1290	9.9
1	OFF	OFF	OFF	ON	1040	8.1
0	OFF	OFF	OFF	OFF	780	6.2