




# Photometric test report

<b>Family</b> <b>Spot 21 Standard</b>	<b>Order number: 51SE14DB11C2C</b> <b>EAN: 4069025447111</b>	<b>LP number</b> <b>59931_33</b>
	<b>Version</b> housing, white, reflector, cover glass, transparent, wide distribution	<b>serial documentation</b> <b>11.05.2026</b>
	<b>Lamps</b> LED 3500 K   CRI ≥ 90	
<b>Controlgear</b> ECG-DALI-Multilumen		
<b>Setting</b> factory setting: DIP-Step=7		
<b>Rated values</b> Net luminous flux = 2940 lm Power consumption = 19.8 W Luminous efficacy = 148.5 lm/W		

**Luminous intensity in cd/klm** C180-0 **Imax: 1454 cd/klm**



Classifications	
DIN 5040	A 7 0
CIE	N1=94 N2=98 N3=100 N4=100 N5=100

Luminaire light output ratios	
$\eta_{LB}$	100.0%
$\phi_u$	100.0%
$\phi_o$	0.0%

**Measurement conditions**  
 DIN EN 13032 and DIN 5032

## Photometric test report

<b>Family</b> Spot 21 Standard	<b>Order number: 51SE14DB11C2C</b> <b>EAN: 4069025447111</b>	<b>LP number</b> 59931_33
-----------------------------------	---	------------------------------

**sITeco**

<b>Table of values for luminous intensities</b>	<b>Maximum luminous intensity</b>
---	-----------------------------------

C-planes	0°	Phi-zone	Total Phi-zone
$\gamma$	Luminous intensity in cd/klm	Luminous flux in lm/klm	
0,0°	1453.7	2.2	2.2
2,5°	1438.9	17.2	19.4
5,0°	1404.1	33.5	52.9
7,5°	1351.1	48.3	101.3
10,0°	1289.5	61.4	162.7
12,5°	1223.4	72.6	235.2
15,0°	1148.5	81.5	316.7
17,5°	1063.6	87.7	404.4
20,0°	985.2	92.4	496.8
22,5°	896.4	94.0	590.8
25,0°	801.5	92.9	683.7
27,5°	663.4	84.0	767.6
30,0°	489.2	67.1	834.7
32,5°	307.3	45.3	880.0
35,0°	173.2	27.2	907.2
37,5°	114.5	19.1	926.3
40,0°	77.4	13.6	940.0
42,5°	52.8	9.8	949.7
45,0°	37.7	7.3	957.0
47,5°	28.4	5.7	962.8
50,0°	22.7	4.8	967.6
52,5°	19.1	4.2	971.7
55,0°	16.7	3.8	975.5
57,5°	15.0	3.5	978.9
60,0°	13.6	3.2	982.2
62,5°	12.4	3.0	985.2
65,0°	11.2	2.8	988.0
67,5°	10.1	2.6	990.6
70,0°	9.0	2.3	992.9
72,5°	7.7	2.0	994.9
75,0°	6.2	1.6	996.5
77,5°	4.7	1.3	997.8
80,0°	3.6	1.0	998.8
82,5°	2.5	0.7	999.5
85,0°	1.5	0.4	999.9
87,5°	0.5	0.1	1000.0
90,0°	0.0	0.0	1000.0

## Photometric test report

<b>Family</b> Spot 21 Standard	<b>Order number: 51SE14DB11C2C</b> <b>EAN: 4069025447111</b>	<b>LP number</b> 59931_33
-----------------------------------	---	------------------------------

<b>UGR-Table</b>	<b>Standard room</b>	<b>siteco</b>
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	19.8	20.9	20.1	21.2	21.5	19.8	20.9	20.1	21.2	21.5
	3H	20.1	21.1	20.5	21.4	21.8	20.1	21.1	20.5	21.4	21.8
	4H	20.2	21.1	20.6	21.5	21.9	20.2	21.1	20.6	21.5	21.9
	6H	20.3	21.2	20.7	21.5	21.9	20.3	21.2	20.7	21.5	21.9
	8H	20.5	21.2	21.0	21.5	22.0	20.5	21.2	21.0	21.5	22.0
	12H	20.5	21.1	21.0	21.5	21.9	20.5	21.1	21.0	21.5	21.9
4H	2H	19.7	20.7	20.1	21.0	21.4	19.7	20.7	20.1	21.0	21.4
	3H	20.2	20.9	20.6	21.3	21.8	20.2	20.9	20.6	21.3	21.8
	4H	20.4	21.1	20.9	21.5	22.0	20.4	21.1	20.9	21.5	22.0
	6H	20.6	21.2	21.1	21.6	22.1	20.6	21.2	21.1	21.6	22.1
	8H	20.7	21.2	21.2	21.6	22.1	20.7	21.2	21.2	21.6	22.1
	12H	20.8	21.2	21.3	21.6	22.1	20.8	21.2	21.3	21.6	22.1
8H	4H	20.5	21.0	21.0	21.4	21.9	20.5	21.0	21.0	21.4	21.9
	6H	20.8	21.1	21.3	21.6	22.1	20.8	21.1	21.3	21.6	22.1
	8H	20.8	21.2	21.3	21.7	22.2	20.8	21.2	21.3	21.7	22.2
	12H	20.9	21.2	21.5	21.7	22.3	20.9	21.2	21.5	21.7	22.3
12H	4H	20.5	20.9	21.0	21.4	21.9	20.5	20.9	21.0	21.4	21.9
	6H	20.8	21.1	21.3	21.6	22.1	20.8	21.1	21.3	21.6	22.1
	8H	20.9	21.1	21.4	21.7	22.2	20.9	21.1	21.4	21.7	22.2

<b>Luminance table</b>	<b>Max. for <math>\gamma \geq 65^\circ</math></b>	<b>Photometric dimensions in mm: D = 82</b>
------------------------	---	---


<b>C-planes</b>	<b>0°</b>
$\gamma$	<b>Luminance in cd/m<sup>2</sup></b>
45,0°	29659.5
50,0°	19697.4
55,0°	16240.0
60,0°	15171.5
65,0°	14781.3
70,0°	14677.1
75,0°	13361.8
80,0°	11563.9
85,0°	9600.5

**Photometric test report**

<b>Family</b> Spot 21 Standard	<b>Order number: 51SE14DB11C2C</b> <b>EAN: 4069025447111</b>	<b>LP number</b> 59931_33
-----------------------------------	---	------------------------------


**Luminance values in cd/m<sup>2</sup>**

$\gamma$  65°   
   $\gamma$  70°   
   $\gamma$  75°   
   $\gamma$  80°   
   $\gamma$  85°



### Photometric test report

<b>Family</b> <b>Spot 21 Standard</b>	<b>Order number: 51SE14DB11C2C</b> <b>EAN: 4069025447111</b>	<b>LP number</b> <b>59931_33</b>
--	---	-------------------------------------

<b>Multilumen Table</b>	environmental temperature: 25°C	
-------------------------	---------------------------------	---

DIP-Step	Switch Setting				Luminous flux [lm]	Power consumption [W]
	1	2	3	4		
11	ON	OFF	ON	ON	3960	28.1
10	ON	OFF	ON	OFF	3710	25.9
9	ON	OFF	OFF	ON	3460	23.8
8	ON	OFF	OFF	OFF	3200	21.7
7	OFF	ON	ON	ON	2940	19.8
6	OFF	ON	ON	OFF	2670	17.7
5	OFF	ON	OFF	ON	2390	15.7
4	OFF	ON	OFF	OFF	2110	13.8
3	OFF	OFF	ON	ON	1820	11.7
2	OFF	OFF	ON	OFF	1530	9.9
1	OFF	OFF	OFF	ON	1230	8.1
0	OFF	OFF	OFF	OFF	920	6.2