



Photometric test report

Family Spot 21 Standard	Order number: 51SE32DB11C2C EAN: 4069025447319	LP number 59932_32
	Version housing, black, reflector, cover glass, transparent, narrow distribution Lamps LED 3500 K CRI ≥ 90 Controlgear ECG-DALI-Multilumen Setting factory setting: DIP-Step=7 Rated values Net luminous flux = 2880 lm Power consumption = 19.8 W Luminous efficacy = 145.5 lm/W	serial documentation 11.05.2026



Luminous intensity in cd/klm C180-0 **Imax: 4689 cd/klm**



Classifications	
DIN 5040	A 8 0
CIE	N1=100 N2=100 N3=100 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Spot 21 Standard	Order number: 51SE32DB11C2C EAN: 4069025447319	LP number 59932_32
-----------------------------------	---	------------------------------



Table of values for luminous intensities	Maximum luminous intensity
---	-----------------------------------

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
0°	4689.0	1.1	1.1
1°	4662.7	8.9	10.0
2°	4570.2	17.5	27.5
3°	4419.7	25.4	52.9
4°	4221.2	32.3	85.2
5°	4002.2	38.3	123.4
6°	3748.8	43.0	166.4
7°	3484.3	46.6	213.0
8°	3214.3	49.1	262.0
9°	2959.0	50.8	312.8
10°	2688.0	51.2	364.0
11°	2425.9	50.8	414.7
12°	2119.1	48.3	463.1
13°	1876.2	46.3	509.3
14°	1687.1	44.8	554.1
15°	1466.8	133.0	687.1
20°	726.5	136.2	823.3
25°	445.9	103.3	926.6
30°	219.5	60.2	986.8
35°	21.0	6.6	993.4
40°	7.3	2.6	995.9
45°	3.6	1.4	997.3
50°	2.0	0.8	998.2
55°	1.5	0.7	998.9
60°	1.1	0.5	999.4
65°	0.7	0.4	999.7
70°	0.4	0.2	999.9
75°	0.1	0.1	1000.0
80°	0.0	0.0	1000.0
85°	0.0	0.0	1000.0
90°	0.0	0.0	1000.0

Photometric test report

Family Spot 21 Standard	Order number: 51SE32DB11C2C EAN: 4069025447319	LP number 59932_32
----------------------------	---	-----------------------

UGR-Table		Standard room									
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	10.0	10.9	10.4	11.2	11.6	10.0	10.9	10.4	11.2	11.6
	3H	9.9	10.7	10.3	11.0	11.4	9.9	10.7	10.3	11.0	11.4
	4H	9.8	10.5	10.2	10.8	11.2	9.8	10.5	10.2	10.8	11.2
	6H	9.6	10.3	10.1	10.7	11.1	9.6	10.3	10.1	10.7	11.1
	8H	9.7	10.2	10.1	10.6	11.0	9.7	10.2	10.1	10.6	11.0
	12H	9.6	10.1	10.1	10.5	10.9	9.6	10.1	10.1	10.5	10.9
4H	2H	9.7	10.5	10.1	10.8	11.2	9.7	10.5	10.1	10.8	11.2
	3H	9.5	10.2	10.0	10.5	11.0	9.5	10.2	10.0	10.5	11.0
	4H	9.4	10.0	9.9	10.4	10.8	9.4	10.0	9.9	10.4	10.8
	6H	9.3	9.8	9.7	10.2	10.7	9.3	9.8	9.7	10.2	10.7
	8H	9.3	9.6	9.7	10.1	10.6	9.3	9.6	9.7	10.1	10.6
	12H	9.2	9.5	9.7	10.0	10.5	9.2	9.5	9.7	10.0	10.5
8H	4H	9.3	9.7	9.7	10.1	10.6	9.3	9.7	9.7	10.1	10.6
	6H	9.1	9.4	9.6	9.9	10.4	9.1	9.4	9.6	9.9	10.4
	8H	9.0	9.3	9.5	9.8	10.3	9.0	9.3	9.5	9.8	10.3
	12H	8.9	9.2	9.4	9.7	10.3	8.9	9.2	9.4	9.7	10.3
12H	4H	9.2	9.5	9.7	10.0	10.5	9.2	9.5	9.7	10.0	10.5
	6H	9.0	9.3	9.5	9.8	10.3	9.0	9.3	9.5	9.8	10.3
	8H	8.9	9.2	9.4	9.7	10.3	8.9	9.2	9.4	9.7	10.3


Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 82
------------------------	---------------------------------	--------------------------------------

C-planes	0°
γ	Luminance in cd/m^2
45°	2801.1
50°	1712.1
55°	1438.5
60°	1210.7
65°	911.0
70°	644.2
75°	212.8
80°	0.0
85°	0.0

Photometric test report

Family Spot 21 Standard	Order number: 51SE32DB11C2C EAN: 4069025447319	LP number 59932_32
-----------------------------------	---	------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85°



Photometric test report

Family Spot 21 Standard	Order number: 51SE32DB11C2C EAN: 4069025447319	LP number 59932_32
-----------------------------------	---	------------------------------

Multilumen Table	environmental temperature: 25°C	sITeco
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting				Luminous flux [lm]	Power consumption [W]
	1	2	3	4		
11	ON	OFF	ON	ON	3880	28.1
10	ON	OFF	ON	OFF	3640	25.9
9	ON	OFF	OFF	ON	3390	23.8
8	ON	OFF	OFF	OFF	3140	21.7
7	OFF	ON	ON	ON	2880	19.8
6	OFF	ON	ON	OFF	2610	17.7
5	OFF	ON	OFF	ON	2340	15.7
4	OFF	ON	OFF	OFF	2070	13.8
3	OFF	OFF	ON	ON	1790	11.7
2	OFF	OFF	ON	OFF	1500	9.9
1	OFF	OFF	OFF	ON	1200	8.1
0	OFF	OFF	OFF	OFF	900	6.2