



Photometric test report

Family Spot 21 Standard	Order number: 51SE32DB11D2C EAN: 4069025447326	LP number 59932_33
	Version housing, black, reflector, cover glass, transparent, narrow distribution Lamps LED 4000 K CRI ≥ 90 Controlgear ECG-DALI-Multilumen Setting factory setting: DIP-Step=7 Rated values Net luminous flux = 2890 lm Power consumption = 19.8 W Luminous efficacy = 146 lm/W	serial documentation 11.05.2026



Luminous intensity in cd/klm C180-0 **Imax: 4689 cd/klm**



Classifications	
DIN 5040	A 8 0
CIE	N1=100 N2=100 N3=100 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Spot 21 Standard	Order number: 51SE32DB11D2C EAN: 4069025447326	LP number 59932_33
-----------------------------------	---	------------------------------



Table of values for luminous intensities	Maximum luminous intensity
---	-----------------------------------

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
0°	4689.0	1.1	1.1
1°	4662.7	8.9	10.0
2°	4570.2	17.5	27.5
3°	4419.7	25.4	52.9
4°	4221.2	32.3	85.2
5°	4002.2	38.3	123.4
6°	3748.8	43.0	166.4
7°	3484.3	46.6	213.0
8°	3214.3	49.1	262.0
9°	2959.0	50.8	312.8
10°	2688.0	51.2	364.0
11°	2425.9	50.8	414.7
12°	2119.1	48.3	463.1
13°	1876.2	46.3	509.3
14°	1687.1	44.8	554.1
15°	1466.8	133.0	687.1
20°	726.5	136.2	823.3
25°	445.9	103.3	926.6
30°	219.5	60.2	986.8
35°	21.0	6.6	993.4
40°	7.3	2.6	995.9
45°	3.6	1.4	997.3
50°	2.0	0.8	998.2
55°	1.5	0.7	998.9
60°	1.1	0.5	999.4
65°	0.7	0.4	999.7
70°	0.4	0.2	999.9
75°	0.1	0.1	1000.0
80°	0.0	0.0	1000.0
85°	0.0	0.0	1000.0
90°	0.0	0.0	1000.0

Photometric test report

Family Spot 21 Standard	Order number: 51SE32DB11D2C EAN: 4069025447326	LP number 59932_33
----------------------------	---	-----------------------

UGR-Table		Standard room									
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	10.0	11.0	10.4	11.3	11.6	10.0	11.0	10.4	11.3	11.6
	3H	9.9	10.7	10.3	11.0	11.4	9.9	10.7	10.3	11.0	11.4
	4H	9.8	10.5	10.2	10.9	11.2	9.8	10.5	10.2	10.9	11.2
	6H	9.7	10.3	10.1	10.7	11.1	9.7	10.3	10.1	10.7	11.1
	8H	9.7	10.2	10.2	10.6	11.0	9.7	10.2	10.2	10.6	11.0
	12H	9.6	10.1	10.1	10.5	10.9	9.6	10.1	10.1	10.5	10.9
4H	2H	9.8	10.5	10.2	10.8	11.2	9.8	10.5	10.2	10.8	11.2
	3H	9.6	10.2	10.0	10.6	11.0	9.6	10.2	10.0	10.6	11.0
	4H	9.4	10.0	9.9	10.4	10.8	9.4	10.0	9.9	10.4	10.8
	6H	9.3	9.8	9.7	10.2	10.7	9.3	9.8	9.7	10.2	10.7
	8H	9.3	9.7	9.7	10.1	10.6	9.3	9.7	9.7	10.1	10.6
	12H	9.2	9.5	9.7	10.0	10.5	9.2	9.5	9.7	10.0	10.5
8H	4H	9.3	9.7	9.7	10.1	10.6	9.3	9.7	9.7	10.1	10.6
	6H	9.1	9.5	9.6	9.9	10.5	9.1	9.5	9.6	9.9	10.5
	8H	9.0	9.3	9.5	9.8	10.4	9.0	9.3	9.5	9.8	10.4
	12H	8.9	9.2	9.5	9.7	10.3	8.9	9.2	9.5	9.7	10.3
12H	4H	9.2	9.5	9.7	10.0	10.5	9.2	9.5	9.7	10.0	10.5
	6H	9.0	9.3	9.5	9.8	10.3	9.0	9.3	9.5	9.8	10.3
	8H	8.9	9.2	9.5	9.7	10.3	8.9	9.2	9.5	9.7	10.3


Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 82
------------------------	---------------------------------	--------------------------------------

C-planes	0°
γ	Luminance in cd/m ²
45°	2810.9
50°	1718.0
55°	1443.5
60°	1214.9
65°	914.2
70°	646.4
75°	213.6
80°	0.0
85°	0.0

Photometric test report

Family Spot 21 Standard	Order number: 51SE32DB11D2C EAN: 4069025447326	LP number 59932_33
-----------------------------------	---	------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85°



Photometric test report

Family Spot 21 Standard	Order number: 51SE32DB11D2C EAN: 4069025447326	LP number 59932_33
--	---	-------------------------------------

Multilumen Table	environmental temperature: 25°C	
-------------------------	---------------------------------	---

DIP-Step	Switch Setting				Luminous flux [lm]	Power consumption [W]
	1	2	3	4		
11	ON	OFF	ON	ON	3900	28.1
10	ON	OFF	ON	OFF	3660	25.9
9	ON	OFF	OFF	ON	3410	23.8
8	ON	OFF	OFF	OFF	3150	21.7
7	OFF	ON	ON	ON	2890	19.8
6	OFF	ON	ON	OFF	2630	17.7
5	OFF	ON	OFF	ON	2360	15.7
4	OFF	ON	OFF	OFF	2080	13.8
3	OFF	OFF	ON	ON	1800	11.7
2	OFF	OFF	ON	OFF	1510	9.9
1	OFF	OFF	OFF	ON	1210	8.1
0	OFF	OFF	OFF	OFF	910	6.2