




Photometric test report

Family Spot 21 Standard	Order number: 51SE32MB11B2C EAN: 4069025447388	LP number 59932_27
	Version housing, black, reflector, cover glass, transparent, narrow distribution Lamps LED 3000 K CRI ≥ 90 Controlgear ECG Multilumen Setting factory setting: DIP-Step=4	serial documentation 11.05.2026
	Rated values Net luminous flux = 2800 lm Power consumption = 18.5 W Luminous efficacy = 151.4 lm/W	

Luminous intensity in cd/klm C180-0 **Imax: 4689 cd/klm**



Classifications	
DIN 5040	A 8 0
CIE	N1=100 N2=100 N3=100 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Spot 21 Standard	Order number: 51SE32MB11B2C EAN: 4069025447388	LP number 59932_27
-----------------------------------	---	------------------------------

sITeco

Table of values for luminous intensities	Maximum luminous intensity
---	-----------------------------------

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm	Luminous flux in lm/klm	
0°	4689.0	1.1	1.1
1°	4662.7	8.9	10.0
2°	4570.2	17.5	27.5
3°	4419.7	25.4	52.9
4°	4221.2	32.3	85.2
5°	4002.2	38.3	123.4
6°	3748.8	43.0	166.4
7°	3484.3	46.6	213.0
8°	3214.3	49.1	262.0
9°	2959.0	50.8	312.8
10°	2688.0	51.2	364.0
11°	2425.9	50.8	414.7
12°	2119.1	48.3	463.1
13°	1876.2	46.3	509.3
14°	1687.1	44.8	554.1
15°	1466.8	133.0	687.1
20°	726.5	136.2	823.3
25°	445.9	103.3	926.6
30°	219.5	60.2	986.8
35°	21.0	6.6	993.4
40°	7.3	2.6	995.9
45°	3.6	1.4	997.3
50°	2.0	0.8	998.2
55°	1.5	0.7	998.9
60°	1.1	0.5	999.4
65°	0.7	0.4	999.7
70°	0.4	0.2	999.9
75°	0.1	0.1	1000.0
80°	0.0	0.0	1000.0
85°	0.0	0.0	1000.0
90°	0.0	0.0	1000.0

Photometric test report

Family Spot 21 Standard	Order number: 51SE32MB11B2C EAN: 4069025447388	LP number 59932_27
-----------------------------------	---	------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	9.9	10.8	10.3	11.2	11.5	9.9	10.8	10.3	11.2	11.5
	3H	9.8	10.6	10.2	10.9	11.3	9.8	10.6	10.2	10.9	11.3
	4H	9.7	10.4	10.1	10.7	11.1	9.7	10.4	10.1	10.7	11.1
	6H	9.5	10.2	10.0	10.6	11.0	9.5	10.2	10.0	10.6	11.0
	8H	9.6	10.1	10.0	10.5	10.9	9.6	10.1	10.0	10.5	10.9
	12H	9.5	10.0	10.0	10.4	10.8	9.5	10.0	10.0	10.4	10.8
4H	2H	9.7	10.4	10.1	10.7	11.1	9.7	10.4	10.1	10.7	11.1
	3H	9.5	10.1	9.9	10.4	10.9	9.5	10.1	9.9	10.4	10.9
	4H	9.3	9.9	9.8	10.3	10.7	9.3	9.9	9.8	10.3	10.7
	6H	9.2	9.7	9.6	10.1	10.6	9.2	9.7	9.6	10.1	10.6
	8H	9.2	9.5	9.6	10.0	10.5	9.2	9.5	9.6	10.0	10.5
	12H	9.1	9.4	9.6	9.9	10.4	9.1	9.4	9.6	9.9	10.4
8H	4H	9.2	9.6	9.6	10.0	10.5	9.2	9.6	9.6	10.0	10.5
	6H	9.0	9.3	9.5	9.8	10.3	9.0	9.3	9.5	9.8	10.3
	8H	8.9	9.2	9.4	9.7	10.2	8.9	9.2	9.4	9.7	10.2
	12H	8.8	9.1	9.3	9.6	10.2	8.8	9.1	9.3	9.6	10.2
12H	4H	9.1	9.4	9.6	9.9	10.4	9.1	9.4	9.6	9.9	10.4
	6H	8.9	9.2	9.4	9.7	10.2	8.9	9.2	9.4	9.7	10.2
	8H	8.8	9.1	9.3	9.6	10.2	8.8	9.1	9.3	9.6	10.2


Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 82
------------------------	---	---

C-planes	0°
γ	Luminance in cd/m²
45°	2723.3
50°	1664.5
55°	1398.6
60°	1177.0
65°	885.7
70°	626.3
75°	206.9
80°	0.0
85°	0.0

Photometric test report

Family Spot 21 Standard	Order number: 51SE32MB11B2C EAN: 4069025447388	LP number 59932_27
-----------------------------------	---	------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85°



Photometric test report

Family Spot 21 Standard	Order number: 51SE32MB11B2C EAN: 4069025447388	LP number 59932_27
-----------------------------------	---	------------------------------

Multilumen Table	environmental temperature: 25°C	sITeco
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]
	1	2	3		
0	OFF	OFF	OFF	3770	26.5
1	ON	OFF	OFF	3540	24.5
2	OFF	ON	OFF	3300	22.5
3	ON	ON	OFF	3050	20.5
4	OFF	OFF	ON	2800	18.5
5	ON	OFF	ON	2540	16.6
6	OFF	ON	ON	2280	14.8
7	ON	ON	ON	2010	12.9