



Photometric test report

Family Spot 21 Standard	Order number: 51SE33DA2DA2C EAN: 4069025447418	LP number 59940_13
	Version housing, black, reflector, lens PMMA, wide distribution Lamps LED 2700 K CRI ≥ 90 Controlgear ECG-DALI-Multilumen Setting factory setting: DIP-Step=6 Rated values Net luminous flux = 2210 lm Power consumption = 17.7 W Luminous efficacy = 124.9 lm/W	serial documentation 11.05.2026



Luminous intensity in cd/klm C180-0 **Imax: 2638 cd/klm**



Classifications	
DIN 5040	A 8 0
CIE	N1=92 N2=98 N3=100 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Spot 21 Standard	Order number: 51SE33DA2DA2C EAN: 4069025447418	LP number 59940_13
-----------------------------------	---	------------------------------

siteco

Table of values for luminous intensities	Maximum luminous intensity
---	-----------------------------------

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm	Luminous flux in lm/klm	
0,0°	2638.3	3.9	3.9
2,5°	2607.2	31.2	35.1
5,0°	2509.4	60.0	95.1
7,5°	2342.7	83.8	178.9
10,0°	2101.4	100.0	278.9
12,5°	1793.5	106.4	385.4
15,0°	1462.2	103.7	489.1
17,5°	1137.7	93.8	582.9
20,0°	857.0	80.4	663.2
22,5°	616.7	64.7	727.9
25,0°	449.1	52.0	780.0
27,5°	328.3	41.6	821.5
30,0°	236.7	32.4	854.0
32,5°	154.3	22.7	876.7
35,0°	101.7	16.0	892.7
37,5°	76.7	12.8	905.5
40,0°	64.2	11.3	916.8
42,5°	57.3	10.6	927.4
45,0°	51.1	9.9	937.3
47,5°	44.6	9.0	946.3
50,0°	37.9	8.0	954.3
52,5°	31.6	6.9	961.2
55,0°	26.8	6.0	967.2
57,5°	24.1	5.6	972.7
60,0°	21.5	5.1	977.8
62,5°	18.8	4.6	982.4
65,0°	15.7	3.9	986.3
67,5°	12.6	3.2	989.5
70,0°	10.1	2.6	992.1
72,5°	8.3	2.2	994.3
75,0°	6.8	1.8	996.1
77,5°	5.4	1.5	997.5
80,0°	4.1	1.1	998.7
82,5°	2.8	0.8	999.4
85,0°	1.6	0.4	999.9
87,5°	0.5	0.1	1000.0
90,0°	0.0	0.0	1000.0

Photometric test report

Family Spot 21 Standard	Order number: 51SE33DA2DA2C EAN: 4069025447418	LP number 59940_13
----------------------------	---	-----------------------

UGR-Table		Standard room									
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	20.2	21.2	20.5	21.6	21.9	20.2	21.2	20.5	21.6	21.9
	3H	20.8	21.7	21.2	22.1	22.4	20.8	21.7	21.2	22.1	22.4
	4H	21.0	21.9	21.4	22.2	22.6	21.0	21.9	21.4	22.2	22.6
	6H	21.2	22.0	21.7	22.4	22.8	21.2	22.0	21.7	22.4	22.8
	8H	21.4	22.0	21.8	22.4	22.8	21.4	22.0	21.8	22.4	22.8
	12H	21.4	22.0	21.8	22.3	22.8	21.4	22.0	21.8	22.3	22.8
4H	2H	20.4	21.3	20.8	21.7	22.0	20.4	21.3	20.8	21.7	22.0
	3H	21.2	21.9	21.6	22.3	22.7	21.2	21.9	21.6	22.3	22.7
	4H	21.5	22.1	21.9	22.5	23.0	21.5	22.1	21.9	22.5	23.0
	6H	21.8	22.3	22.2	22.7	23.2	21.8	22.3	22.2	22.7	23.2
	8H	21.9	22.3	22.4	22.8	23.3	21.9	22.3	22.4	22.8	23.3
	12H	21.9	22.3	22.4	22.8	23.3	21.9	22.3	22.4	22.8	23.3
8H	4H	21.6	22.1	22.1	22.5	23.0	21.6	22.1	22.1	22.5	23.0
	6H	21.9	22.3	22.4	22.8	23.3	21.9	22.3	22.4	22.8	23.3
	8H	22.1	22.4	22.6	22.9	23.4	22.1	22.4	22.6	22.9	23.4
	12H	22.1	22.4	22.7	22.9	23.5	22.1	22.4	22.7	22.9	23.5
12H	4H	21.6	22.0	22.1	22.4	22.9	21.6	22.0	22.1	22.4	22.9
	6H	22.0	22.2	22.5	22.7	23.3	22.0	22.2	22.5	22.7	23.3
	8H	22.1	22.3	22.6	22.9	23.4	22.1	22.3	22.6	22.9	23.4

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 62
------------------------	---------------------------------	--------------------------------------

C-planes	0°
γ	Luminance in cd/m ²
45,0°	52890.6
50,0°	43207.6
55,0°	34202.9
60,0°	31447.3
65,0°	27122.8
70,0°	21698.0
75,0°	19303.0
80,0°	17346.8
85,0°	13488.7

Photometric test report


Family
Spot 21 Standard

Order number: 51SE33DA2DA2C
EAN: 4069025447418

LP number
59940_13

Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°



Photometric test report

Family Spot 21 Standard	Order number: 51SE33DA2DA2C EAN: 4069025447418	LP number 59940_13
-----------------------------------	---	------------------------------

Multilumen Table	environmental temperature: 25°C	sITeco
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting				Luminous flux [lm]	Power consumption [W]
	1	2	3	4		
11	ON	OFF	ON	ON	3270	28.0
10	ON	OFF	ON	OFF	3070	25.8
9	ON	OFF	OFF	ON	2860	23.7
8	ON	OFF	OFF	OFF	2650	21.6
7	OFF	ON	ON	ON	2430	19.8
6	OFF	ON	ON	OFF	2210	17.7
5	OFF	ON	OFF	ON	1980	15.6
4	OFF	ON	OFF	OFF	1750	13.8
3	OFF	OFF	ON	ON	1510	11.7
2	OFF	OFF	ON	OFF	1270	9.9
1	OFF	OFF	OFF	ON	1020	8.0
0	OFF	OFF	OFF	OFF	770	6.2