



Photometric test report

Family Spot 21 Standard	Order number: 51SE63MA2ED2C EAN: 4069025448019	LP number 59942_12
	Version housing, white aluminium, reflector, lens PMMA, wide distribution Lamps LED 4000 K CRI ≥ 90 Controlgear ECG Multilumen Setting factory setting: DIP-Step=6 Rated values Net luminous flux = 2300 lm Power consumption = 14.8 W Luminous efficacy = 155.4 lm/W	serial documentation 11.05.2026
		

Luminous intensity in cd/klm C180-0 **Imax: 2638 cd/klm**



Classifications	
DIN 5040	A 8 0
CIE	N1=92 N2=98 N3=100 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Spot 21 Standard	Order number: 51SE63MA2ED2C EAN: 4069025448019	LP number 59942_12
-----------------------------------	---	------------------------------

siteco

Table of values for luminous intensities	Maximum luminous intensity
---	-----------------------------------

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm	Luminous flux in lm/klm	
0,0°	2638.3	3.9	3.9
2,5°	2607.2	31.2	35.1
5,0°	2509.4	60.0	95.1
7,5°	2342.7	83.8	178.9
10,0°	2101.4	100.0	278.9
12,5°	1793.5	106.4	385.4
15,0°	1462.2	103.7	489.1
17,5°	1137.7	93.8	582.9
20,0°	857.0	80.4	663.2
22,5°	616.7	64.7	727.9
25,0°	449.1	52.0	780.0
27,5°	328.3	41.6	821.5
30,0°	236.7	32.4	854.0
32,5°	154.3	22.7	876.7
35,0°	101.7	16.0	892.7
37,5°	76.7	12.8	905.5
40,0°	64.2	11.3	916.8
42,5°	57.3	10.6	927.4
45,0°	51.1	9.9	937.3
47,5°	44.6	9.0	946.3
50,0°	37.9	8.0	954.3
52,5°	31.6	6.9	961.2
55,0°	26.8	6.0	967.2
57,5°	24.1	5.6	972.7
60,0°	21.5	5.1	977.8
62,5°	18.8	4.6	982.4
65,0°	15.7	3.9	986.3
67,5°	12.6	3.2	989.5
70,0°	10.1	2.6	992.1
72,5°	8.3	2.2	994.3
75,0°	6.8	1.8	996.1
77,5°	5.4	1.5	997.5
80,0°	4.1	1.1	998.7
82,5°	2.8	0.8	999.4
85,0°	1.6	0.4	999.9
87,5°	0.5	0.1	1000.0
90,0°	0.0	0.0	1000.0

Photometric test report

Family Spot 21 Standard	Order number: 51SE63MA2ED2C EAN: 4069025448019	LP number 59942_12
-----------------------------------	---	------------------------------

UGR-Table		Standard room									
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	20.3	21.4	20.7	21.7	22.0	20.3	21.4	20.7	21.7	22.0
	3H	20.9	21.9	21.3	22.2	22.6	20.9	21.9	21.3	22.2	22.6
	4H	21.2	22.0	21.6	22.4	22.8	21.2	22.0	21.6	22.4	22.8
	6H	21.4	22.1	21.8	22.5	22.9	21.4	22.1	21.8	22.5	22.9
	8H	21.5	22.1	22.0	22.5	22.9	21.5	22.1	22.0	22.5	22.9
	12H	21.5	22.1	22.0	22.5	22.9	21.5	22.1	22.0	22.5	22.9
4H	2H	20.6	21.4	21.0	21.8	22.2	20.6	21.4	21.0	21.8	22.2
	3H	21.3	22.0	21.8	22.4	22.9	21.3	22.0	21.8	22.4	22.9
	4H	21.6	22.3	22.1	22.7	23.1	21.6	22.3	22.1	22.7	23.1
	6H	21.9	22.4	22.4	22.9	23.3	21.9	22.4	22.4	22.9	23.3
	8H	22.0	22.5	22.5	22.9	23.4	22.0	22.5	22.5	22.9	23.4
	12H	22.1	22.4	22.6	22.9	23.4	22.1	22.4	22.6	22.9	23.4
8H	4H	21.7	22.2	22.2	22.6	23.1	21.7	22.2	22.2	22.6	23.1
	6H	22.1	22.4	22.6	22.9	23.4	22.1	22.4	22.6	22.9	23.4
	8H	22.2	22.5	22.7	23.0	23.5	22.2	22.5	22.7	23.0	23.5
	12H	22.3	22.5	22.8	23.0	23.6	22.3	22.5	22.8	23.0	23.6
12H	4H	21.7	22.1	22.2	22.6	23.1	21.7	22.1	22.2	22.6	23.1
	6H	22.1	22.4	22.6	22.9	23.4	22.1	22.4	22.6	22.9	23.4
	8H	22.2	22.5	22.8	23.0	23.5	22.2	22.5	22.8	23.0	23.5


Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 62
------------------------	---------------------------------	--------------------------------------

C-planes	0°
γ	Luminance in cd/m ²
45,0°	55044.5
50,0°	44967.2
55,0°	35595.7
60,0°	32728.0
65,0°	28227.4
70,0°	22581.6
75,0°	20089.1
80,0°	18053.2
85,0°	14038.0

Photometric test report

Family Spot 21 Standard	Order number: 51SE63MA2ED2C EAN: 4069025448019	LP number 59942_12
-----------------------------------	---	------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**



Photometric test report

Family Spot 21 Standard	Order number: 51SE63MA2ED2C EAN: 4069025448019	LP number 59942_12
-----------------------------------	---	------------------------------

Multilumen Table	environmental temperature: 25°C	sITeco
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]
	1	2	3		
0	OFF	OFF	OFF	3790	26.5
1	ON	OFF	OFF	3560	24.4
2	OFF	ON	OFF	3320	22.4
3	ON	ON	OFF	3070	20.4
4	OFF	OFF	ON	2820	18.5
5	ON	OFF	ON	2560	16.5
6	OFF	ON	ON	2300	14.8
7	ON	ON	ON	2030	12.8