

Photometric test report

Family
Silica® 21 round M

Order number: 51MF31DBENSA
EAN: 4069025807618

LP number
60085_7

serial
documentation
20.05.2026



Version Suspended luminaire, housing, silver, cover, opal, direct-/ indirect distribution, extremely wide distribution, UGR≤22

Lamps LED 4000 K | CRI ≥ 90

Controlgear ECG-DALI


Rated values Net luminous flux = 7390 lm
Power consumption = 46.1 W
Luminous efficacy = 160.3 lm/W

siteco

Luminous intensity in cd/klm

C180-0

Imax: 255 cd/klm



Classifications

DIN 5040 B 4 3
CIE N1=49 N2=79 N3=96
N4=68 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 68.5%
 ϕ_o 31.5%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Silica® 21 round M	Order number: 51MF31DBENSA EAN: 4069025807618	LP number 60085_7
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
0°	254.7	1.5	1.5
5°	253.4	12.1	13.6
10°	249.4	23.7	37.4
15°	242.5	34.4	71.8
20°	233.1	43.7	115.5
25°	221.5	51.3	166.8
30°	207.7	56.9	223.7
35°	192.3	60.5	284.2
40°	175.7	61.9	346.1
45°	157.8	61.2	407.2
50°	139.4	58.6	465.8
55°	120.7	54.2	520.0
60°	101.5	48.2	568.2
65°	81.9	40.7	608.8
70°	62.4	32.1	641.0
75°	43.7	23.1	664.1
80°	26.3	14.2	678.3
85°	11.3	6.2	684.5
90°	0.7	0.4	684.8
95°	2.7	1.5	686.3
100°	6.1	3.3	689.6
105°	10.8	5.7	695.4
110°	17.8	9.2	704.5
115°	27.5	13.6	718.2
120°	42.4	20.1	738.3
125°	59.8	26.9	765.2
130°	71.9	30.2	795.4
135°	81.6	31.6	827.0
140°	90.7	31.9	858.9
145°	98.0	30.8	889.7
150°	105.3	28.9	918.6
155°	110.8	25.7	944.3
160°	114.3	21.4	965.7
165°	116.6	16.5	982.3
170°	119.0	11.3	993.6
175°	119.3	5.7	999.3
180°	119.9	0.7	1000.0

Photometric test report

Family Silica® 21 round M	Order number: 51MF31DBENSA EAN: 4069025807618	LP number 60085_7
------------------------------	--	----------------------

UGR-Table		Standard room							siTeco		
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	16.4	17.5	17.1	18.3	19.2	16.4	17.5	17.1	18.3	19.2
	3H	17.8	18.8	18.6	19.6	20.6	17.8	18.8	18.6	19.6	20.6
	4H	18.5	19.4	19.2	20.2	21.2	18.5	19.4	19.2	20.2	21.2
	6H	18.9	19.8	19.7	20.6	21.6	18.9	19.8	19.7	20.6	21.6
	8H	19.0	19.8	19.8	20.6	21.6	19.0	19.8	19.8	20.6	21.6
	12H	19.1	19.9	19.9	20.7	21.7	19.1	19.9	19.9	20.7	21.7
4H	2H	17.0	17.9	17.8	18.7	19.7	17.0	17.9	17.8	18.7	19.7
	3H	18.7	19.5	19.5	20.3	21.3	18.7	19.5	19.5	20.3	21.3
	4H	19.4	20.1	20.2	20.9	22.0	19.4	20.1	20.2	20.9	22.0
	6H	20.0	20.6	20.8	21.4	22.5	20.0	20.6	20.8	21.4	22.5
	8H	20.1	20.6	20.9	21.5	22.6	20.1	20.6	20.9	21.5	22.6
	12H	20.2	20.7	21.1	21.6	22.7	20.2	20.7	21.1	21.6	22.7
8H	4H	19.6	20.2	20.5	21.0	22.1	19.6	20.2	20.5	21.0	22.1
	6H	20.2	20.7	21.1	21.6	22.7	20.2	20.7	21.1	21.6	22.7
	8H	20.5	21.0	21.4	21.8	23.0	20.5	21.0	21.4	21.8	23.0
	12H	20.8	21.1	21.7	22.0	23.1	20.8	21.1	21.7	22.0	23.1
12H	4H	19.6	20.2	20.5	21.0	22.1	19.6	20.2	20.5	21.0	22.1
	6H	20.4	20.8	21.3	21.7	22.8	20.4	20.8	21.3	21.7	22.8
	8H	20.7	21.0	21.6	21.9	23.0	20.7	21.0	21.6	21.9	23.0

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	D = 586
-----------------	---------------------------------	-------------------------------	---------

C-planes		0°
γ	Luminance in cd/m²	
45°	6115.0	
50°	5944.4	
55°	5767.8	
60°	5560.2	
65°	5308.0	
70°	4997.6	
75°	4625.1	
80°	4151.2	
85°	3546.3	

Photometric test report

Family
Silica® 21 round M

Order number: 51MF31DBENSA
EAN: 4069025807618

LP number
60085_7

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Silica® 21 round M	Order number: 51MF31DBENSA EAN: 4069025807618	LP number 60085_7
Dimming levels table		environmental temperature: 25°C

siteco

Luminous flux [%]	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	7390	46.1
95	241	252	7024	43.7
90	228	250	6657	41.3
85	215	248	6290	39.1
80	202	246	5920	36.9
75	189	243	5550	34.6
70	176	241	5177	32.3
65	163	238	4803	30.0
60	150	235	4427	27.8
55	138	232	4079	25.6
50	125	228	3700	23.2
45	112	224	3320	20.9
40	100	220	2968	18.8
35	87	215	2585	16.4
30	75	209	2230	14.4
25	62	202	1844	12.2
20	50	194	1487	10.1
15	37	183	1098	7.7
10	25	169	738	5.0
5	13	145	376	2.1
3	7	122	195	0.9