

Photometric test report

Family
Silica® 21 round S

Order number: 51MF33DADMBA
EAN: 4069025808028

LP number
60075_6

serial
documentation
20.05.2026



Version Suspended luminaire, housing, black,
microprismatic optics, direct-/ indirect
distribution, wide distribution, UGR≤19

Lamps LED 3000 K | CRI ≥ 90

Controlgear ECG-DALI

Rated values Net luminous flux = 3940 lm
Power consumption = 28.7 W
Luminous efficacy = 137.3 lm/W


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 298 cd/klm



Classifications

DIN 5040 B 5 3
CIE N1=64 N2=89 N3=97
N4=61 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 61.2%
 ϕ_o 38.8%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Silica® 21 round S	Order number: 51MF33DADMBA EAN: 4069025808028	LP number 60075_6
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	297.5	297.5	297.5	297.5	297.5	297.5	297.5	1.8	1.8
5°	297.9	296.3	294.6	295.7	297.1	296.9	296.8	14.2	15.9
10°	294.0	292.4	290.5	291.3	292.5	292.2	292.2	27.8	43.7
15°	286.8	285.2	283.1	283.6	284.4	284.1	284.0	40.3	84.1
20°	276.8	275.2	272.8	273.0	273.5	273.1	272.9	51.3	135.4
25°	264.9	263.0	260.1	260.0	260.5	259.8	259.2	60.4	195.8
30°	250.5	248.3	244.9	244.7	245.5	244.2	243.3	67.4	263.2
35°	232.4	230.3	226.1	226.3	226.9	225.6	223.7	71.4	334.6
40°	204.7	204.8	201.0	200.8	197.5	198.4	196.1	70.6	405.2
45°	144.8	154.1	156.3	153.3	139.9	153.0	153.7	58.5	463.8
50°	88.0	100.9	117.8	100.8	87.4	99.3	115.3	42.5	506.3
55°	54.2	61.9	87.8	61.7	53.7	60.3	86.3	29.6	535.9
60°	34.5	41.8	61.6	42.3	34.4	41.3	62.3	21.4	557.3
65°	30.8	35.8	38.1	36.7	31.6	36.7	36.1	17.6	574.8
70°	25.3	30.9	19.5	31.4	25.4	31.5	19.3	13.8	588.7
75°	23.9	21.5	17.1	22.0	24.3	21.8	15.7	11.2	599.8
80°	17.2	13.0	17.0	12.6	17.4	13.2	18.1	8.2	608.0
85°	8.0	7.5	6.3	7.5	8.0	7.7	6.4	4.0	612.0
90°	0.8	1.0	0.6	0.9	0.7	0.8	0.4	0.4	612.4
95°	3.4	3.3	3.2	3.2	3.3	3.3	3.2	1.8	614.2
100°	7.6	7.4	7.4	7.5	7.6	7.5	7.6	4.0	618.3
105°	13.3	13.2	13.4	13.5	13.6	13.5	13.6	7.1	625.4
110°	21.9	21.7	22.1	22.3	22.3	22.3	22.3	11.4	636.8
115°	33.8	33.7	34.0	34.1	34.4	34.5	34.4	17.0	653.7
120°	52.1	51.9	51.7	51.7	51.6	51.6	51.5	24.6	678.3
125°	73.6	73.4	73.4	73.3	73.7	73.7	73.3	33.0	711.3
130°	88.5	88.3	88.5	88.9	89.3	88.9	88.6	37.3	748.6
135°	100.4	100.4	100.8	101.4	101.3	100.9	100.6	39.1	787.6
140°	111.5	111.3	111.3	111.7	111.6	111.3	111.1	39.3	826.9
145°	120.6	120.7	120.9	120.8	120.5	120.4	120.0	37.9	864.8
150°	129.5	129.5	129.5	129.3	128.9	128.9	128.6	35.4	900.2
155°	136.3	136.0	135.6	135.3	135.2	135.2	135.2	31.4	931.6
160°	140.6	140.3	140.0	139.7	140.0	139.5	139.8	26.2	957.9
165°	143.5	143.5	143.4	143.6	143.5	143.1	143.4	20.3	978.2
170°	146.4	146.4	146.3	146.0	145.5	145.7	145.9	13.9	992.1
175°	146.7	146.7	146.8	147.0	147.0	147.1	147.2	7.0	999.1
180°	147.5	147.5	147.5	147.5	147.5	147.5	147.5	0.9	1000.0

Photometric test report

Family Silica® 21 round S	Order number: 51MF33DADMBA EAN: 4069025808028	LP number 60075_6
UGR-Table	Standard room	siteco

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	14.3	15.2	15.1	16.1	17.1	14.1	15.1	14.9	15.9	16.9
	3H	14.8	15.7	15.7	16.6	17.7	14.7	15.5	15.5	16.4	17.5
	4H	15.3	16.1	16.2	17.0	18.1	15.0	15.8	15.9	16.7	17.8
	6H	15.7	16.5	16.6	17.4	18.5	15.4	16.2	16.3	17.0	18.2
	8H	15.8	16.5	16.7	17.4	18.6	15.6	16.2	16.5	17.1	18.3
	12H	16.0	16.6	16.9	17.5	18.7	15.7	16.3	16.6	17.2	18.4
4H	2H	14.4	15.2	15.2	16.0	17.1	14.2	15.0	15.1	15.9	17.0
	3H	15.1	15.8	16.0	16.7	17.8	15.1	15.8	16.0	16.7	17.8
	4H	15.7	16.2	16.6	17.2	18.3	15.6	16.2	16.5	17.1	18.3
	6H	16.2	16.8	17.2	17.7	18.8	16.2	16.7	17.1	17.6	18.8
	8H	16.4	16.9	17.3	17.8	19.0	16.4	16.8	17.3	17.8	19.0
	12H	16.6	17.0	17.6	18.0	19.2	16.6	17.0	17.5	17.9	19.1
8H	4H	15.8	16.2	16.7	17.2	18.4	15.8	16.2	16.7	17.2	18.4
	6H	16.5	16.9	17.4	17.8	19.0	16.5	16.9	17.4	17.8	19.0
	8H	16.8	17.2	17.8	18.2	19.4	16.9	17.2	17.8	18.2	19.4
	12H	17.2	17.5	18.1	18.4	19.7	17.2	17.5	18.1	18.4	19.6
12H	4H	15.8	16.2	16.8	17.2	18.4	15.8	16.2	16.8	17.2	18.4
	6H	16.6	17.0	17.6	17.9	19.1	16.6	16.9	17.6	17.9	19.1
	8H	17.0	17.3	18.0	18.2	19.5	17.0	17.3	18.0	18.3	19.5

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		D = 386	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	6892.6	7335.9	7441.8	7298.8	6660.9	7284.5	7318.8
50°	4607.2	5285.6	6171.3	5282.5	4576.7	5201.8	6037.6
55°	3182.4	3635.7	5152.1	3619.8	3153.1	3541.2	5066.5
60°	2325.7	2817.8	4148.6	2848.7	2318.6	2780.8	4197.5
65°	2455.8	2850.8	3037.5	2920.9	2517.1	2922.1	2873.5
70°	2491.1	3036.9	1923.8	3093.6	2505.0	3099.6	1900.3
75°	3111.4	2799.1	2221.8	2860.2	3156.3	2838.8	2037.0
80°	3328.4	2520.2	3288.8	2447.5	3366.9	2568.7	3508.9
85°	3095.5	2894.6	2443.4	2904.3	3078.1	2965.3	2456.9

Photometric test report

Family Silica® 21 round S	Order number: 51MF33DADMBA EAN: 4069025808028	LP number 60075_6
--	--	------------------------------------

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Silica® 21 round S	Order number: 51MF33DADMBA EAN: 4069025808028	LP number 60075_6
Dimming levels table		environmental temperature: 25°C



Luminous flux [%]	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	3940	28.7
95	241	252	3748	27.3
90	227	250	3540	25.8
85	214	248	3346	24.3
80	201	245	3151	22.8
75	188	243	2954	21.4
70	175	240	2757	19.9
65	162	238	2559	18.5
60	149	234	2359	17.1
55	137	231	2174	15.8
50	124	228	1972	14.4
45	111	224	1769	12.9
40	99	219	1581	11.6
35	86	214	1375	10.2
30	74	209	1185	8.9
25	61	202	979	7.5
20	49	194	787	6.2
15	37	183	594	4.8
10	25	169	400	3.5
5	12	142	189	1.9
3	7	122	108	1.2