

Photometric test report

Family
Silica® 21 round S

Order number: 51MF41DA3NSA
EAN: 4069025808639

LP number
60071_94



Version Suspended luminaire, housing, silver, cover, opal, direct extremely wide distribution, UGR≤22

Lamps LED 3000 K | CRI ≥ 80

Controlgear ECG-DALI

Rated values Net luminous flux = 2190 lm
Power consumption = 15.4 W
Luminous efficacy = 142.2 lm/W


serial
documentation
20.05.2026

siteco

Luminous intensity in cd/klm

C180-0

Imax: 372 cd/klm



Classifications

DIN 5040 A 4 0
CIE N1=49 N2=79 N3=96
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Silica® 21 round S	Order number: 51MF41DA3NSA EAN: 4069025808639	LP number 60071_94
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
0°	372.1	2.2	2.2
5°	370.3	17.7	19.9
10°	364.3	34.7	54.6
15°	354.3	50.3	104.9
20°	340.6	63.8	168.7
25°	323.6	75.0	243.7
30°	303.5	83.2	326.8
35°	281.0	88.3	415.2
40°	256.7	90.4	505.6
45°	230.6	89.4	595.0
50°	203.7	85.5	680.5
55°	176.4	79.2	759.7
60°	148.2	70.4	830.1
65°	119.6	59.4	889.5
70°	91.1	46.9	936.5
75°	63.8	33.8	970.3
80°	38.4	20.7	991.0
85°	16.5	9.0	1000.0
90°	0.0	0.0	1000.0
95°	0.0	0.0	1000.0
100°	0.0	0.0	1000.0
105°	0.0	0.0	1000.0
110°	0.0	0.0	1000.0
115°	0.0	0.0	1000.0
120°	0.0	0.0	1000.0
125°	0.0	0.0	1000.0
130°	0.0	0.0	1000.0
135°	0.0	0.0	1000.0
140°	0.0	0.0	1000.0
145°	0.0	0.0	1000.0
150°	0.0	0.0	1000.0
155°	0.0	0.0	1000.0
160°	0.0	0.0	1000.0
165°	0.0	0.0	1000.0
170°	0.0	0.0	1000.0
175°	0.0	0.0	1000.0
180°	0.0	0.0	1000.0

Photometric test report

Family Silica® 21 round S		Order number: 51MF41DA3NSA EAN: 4069025808639							LP number 60071_94	
UGR-Table		Standard room							siteco	
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)			
x	y									
2H	2H	18.4	20.1	18.7	20.4	20.7	18.4	20.1	18.7	20.4
	3H	19.9	21.5	20.3	21.8	22.2	19.9	21.5	20.3	21.8
	4H	20.6	22.0	21.0	22.4	22.7	20.6	22.0	21.0	22.4
	6H	21.1	22.4	21.5	22.7	23.1	21.1	22.4	21.5	22.7
	8H	21.3	22.5	21.7	22.9	23.3	21.3	22.5	21.7	22.9
	12H	21.4	22.5	21.8	22.9	23.3	21.4	22.5	21.8	22.9
4H	2H	19.1	20.6	19.5	20.9	21.3	19.1	20.6	19.5	20.9
	3H	20.9	22.1	21.3	22.5	22.9	20.9	22.1	21.3	22.5
	4H	21.6	22.7	22.1	23.1	23.6	21.6	22.7	22.1	23.1
	6H	22.2	23.2	22.7	23.6	24.1	22.2	23.2	22.7	23.6
	8H	22.4	23.3	22.9	23.8	24.2	22.4	23.3	22.9	23.8
	12H	22.6	23.4	23.1	23.8	24.3	22.6	23.4	23.1	23.8
8H	4H	22.0	22.8	22.4	23.3	23.8	22.0	22.8	22.4	23.3
	6H	22.7	23.4	23.2	23.9	24.4	22.7	23.4	23.2	23.9
	8H	23.0	23.6	23.5	24.1	24.6	23.0	23.6	23.5	24.1
	12H	23.2	23.7	23.7	24.2	24.8	23.2	23.7	23.7	24.2
12H	4H	22.0	22.8	22.5	23.3	23.7	22.0	22.8	22.5	23.3
	6H	22.8	23.4	23.3	23.9	24.4	22.8	23.4	23.3	23.9
	8H	23.1	23.6	23.6	24.1	24.7	23.1	23.6	23.6	24.1

Luminance table		Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 386
C-planes	0°		
γ	Luminance in cd/m²		
45°	6102.0		
50°	5931.7		
55°	5755.5		
60°	5548.3		
65°	5296.6		
70°	4986.9		
75°	4615.2		
80°	4142.4		
85°	3538.5		

Photometric test report

Family
Silica® 21 round S

Order number: 51MF41DA3NSA
EAN: 4069025808639

LP number
60071_94

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Silica® 21 round S	Order number: 51MF41DA3NSA EAN: 4069025808639	LP number 60071_94
Dimming levels table		environmental temperature: 25°C

siteco

Luminous flux [%]	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	2190	15.4
95	241	252	2079	14.7
90	228	250	1968	13.9
85	216	248	1865	13.2
80	203	246	1754	12.4
75	190	243	1643	11.8
70	177	241	1530	11.0
65	165	238	1427	10.3
60	152	235	1314	9.7
55	139	232	1202	8.9
50	127	229	1098	8.2
45	114	225	984	7.4
40	102	221	880	6.7
35	89	216	766	6.0
30	77	210	661	5.3
25	64	204	547	4.5
20	52	196	440	3.8
15	39	185	326	2.9
10	27	172	219	2.2
5	15	150	112	1.4
4	13	145	94	1.2