

Photometric test report

Family
Silica® 21 round S

Order number: 51MF43DA3MBA
EAN: 4069025809346

LP number
59826_847

serial
documentation
20.05.2026

siteco



Version Suspended luminaire, housing, black, microprismatic optics, direct wide distribution, UGR≤19

Lamps LED 3000 K | CRI ≥ 80

Controlgear ECG-DALI


Rated values Net luminous flux = 2410 lm
Power consumption = 17.2 W
Luminous efficacy = 140.1 lm/W

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 487 cd/klm



Classifications

DIN 5040 A 5 0
CIE N1=64 N2=89 N3=97
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Silica® 21 round S	Order number: 51MF43DA3MBA EAN: 4069025809346	LP number 59826_847
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	486.1	486.1	486.1	486.1	486.1	486.1	486.1	2.9	2.9
5°	486.7	484.1	481.4	483.1	485.4	485.1	485.0	23.1	26.0
10°	480.4	477.8	474.6	475.9	477.9	477.5	477.5	45.4	71.5
15°	468.5	466.0	462.5	463.3	464.8	464.2	464.0	65.9	137.4
20°	452.3	449.7	445.8	446.0	446.9	446.2	446.0	83.9	221.2
25°	432.8	429.8	425.0	424.8	425.7	424.4	423.6	98.8	320.0
30°	409.4	405.7	400.1	399.8	401.2	399.1	397.5	110.0	430.0
35°	379.7	376.2	369.4	369.8	370.7	368.6	365.6	116.7	546.7
40°	334.5	334.6	328.5	328.1	322.7	324.2	320.4	115.4	662.1
45°	236.5	251.7	255.4	250.5	228.6	250.0	251.1	95.6	757.7
50°	143.7	164.9	192.5	164.8	142.8	162.3	188.3	69.5	827.3
55°	88.6	101.2	143.4	100.8	87.8	98.6	141.0	48.4	875.6
60°	56.4	68.4	100.7	69.1	56.3	67.5	101.9	34.9	910.5
65°	50.4	58.5	62.3	59.9	51.6	59.9	58.9	28.7	939.3
70°	41.3	50.4	31.9	51.3	41.6	51.4	31.5	22.6	961.8
75°	39.1	35.2	27.9	35.9	39.6	35.7	25.6	18.2	980.1
80°	28.0	21.2	27.7	20.6	28.4	21.6	29.6	13.4	993.4
85°	13.1	12.2	10.3	12.3	13.0	12.5	10.4	6.6	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Silica® 21 round S	Order number: 51MF43DA3MBA EAN: 4069025809346	LP number 59826_847
------------------------------	--	------------------------

UGR-Table		Standard room									siteco	
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3		
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3		
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2		
Room dimensions		View crosswise (C0)					View endwise (C90)					
x	y											
2H	2H	16.9	18.4	17.3	18.7	19.1	16.7	18.2	17.1	18.5	18.9	
	3H	17.6	19.0	18.0	19.3	19.7	17.5	18.8	17.9	19.2	19.5	
	4H	18.1	19.4	18.5	19.7	20.1	17.8	19.1	18.2	19.4	19.8	
	6H	18.6	19.7	19.0	20.1	20.5	18.2	19.4	18.7	19.8	20.2	
	8H	18.8	19.9	19.2	20.3	20.7	18.6	19.6	19.0	20.0	20.4	
	12H	19.0	20.0	19.4	20.4	20.8	18.7	19.7	19.1	20.1	20.5	
4H	2H	17.2	18.4	17.6	18.8	19.1	17.0	18.3	17.4	18.6	19.0	
	3H	18.0	19.1	18.4	19.5	19.9	18.0	19.1	18.4	19.5	19.9	
	4H	18.6	19.5	19.0	19.9	20.4	18.5	19.5	19.0	19.9	20.3	
	6H	19.2	20.0	19.6	20.4	20.9	19.1	19.9	19.6	20.4	20.8	
	8H	19.4	20.2	19.9	20.6	21.1	19.4	20.2	19.9	20.6	21.1	
	12H	19.7	20.3	20.2	20.8	21.3	19.6	20.3	20.1	20.7	21.2	
8H	4H	18.8	19.6	19.3	20.0	20.5	18.8	19.6	19.3	20.0	20.5	
	6H	19.6	20.2	20.1	20.7	21.2	19.6	20.2	20.1	20.7	21.2	
	8H	20.0	20.5	20.5	21.0	21.5	20.0	20.5	20.5	21.0	21.5	
	12H	20.3	20.7	20.8	21.2	21.8	20.3	20.7	20.8	21.2	21.8	
12H	4H	18.9	19.5	19.4	20.0	20.5	18.9	19.5	19.4	20.0	20.5	
	6H	19.7	20.2	20.2	20.7	21.2	19.7	20.2	20.2	20.7	21.2	
	8H	20.1	20.5	20.6	21.0	21.6	20.1	20.6	20.6	21.1	21.6	

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		D = 386	
C-planes		15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
	γ	Luminance in cd/m²					
45°		6888.8	7331.9	7437.7	7294.7	6657.3	7314.7
50°		4604.7	5282.7	6167.9	5279.6	4574.2	6034.2
55°		3180.7	3633.7	5149.3	3617.8	3151.4	5063.8
60°		2324.4	2816.2	4146.3	2847.1	2317.3	4195.2
65°		2454.4	2849.2	3035.8	2919.3	2515.7	2872.0
70°		2489.7	3035.2	1922.7	3092.0	2503.7	1899.3
75°		3109.7	2797.7	2220.6	2858.6	3154.6	2035.9
80°		3326.6	2518.8	3287.1	2446.1	3365.0	3507.1
85°		3093.6	2893.0	2442.1	2902.4	3076.3	2455.8

Photometric test report

Family
Silica® 21 round S

Order number: 51MF43DA3MBA
EAN: 4069025809346

LP number
59826_847

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Silica® 21 round S	Order number: 51MF43DA3MBA EAN: 4069025809346	LP number 59826_847
Dimming levels table		environmental temperature: 25°C
		siteco

Luminous flux [%]	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	2410	17.2
95	241	252	2289	16.4
90	228	250	2168	15.5
85	215	248	2045	14.7
80	203	246	1933	13.9
75	190	243	1810	13.0
70	177	241	1687	12.2
65	164	238	1564	11.4
60	152	235	1450	10.6
55	139	232	1326	9.9
50	126	228	1202	9.0
45	114	225	1087	8.2
40	101	220	962	7.4
35	89	216	846	6.6
30	76	210	721	5.7
25	64	204	605	5.0
20	51	195	478	4.1
15	39	185	362	3.3
10	27	172	244	2.4
5	14	148	116	1.4
4	12	142	97	1.2