Photometric test report

Family
Apollon® rectangular



Order number: 51MP26WD2M42W
EAN: 4069025343895


LP number
59344_120

serial documentation
20.05.2026

Version	surface-mounted and suspended luminaire, microprismatic optics, wide distribution, UGR≤22, adjustable color temperature: 3000 K | 3500 K | 4000K
Lamps	LED 3000 K | CRI ≥ 80
Controlgear	ECG Multilumen
Setting	individual position: DIP-Step=10, colour temperature 3000K
Rated values	Net luminous flux = 7400 lm Power consumption = 57.0 W Luminous efficacy = 129.8 lm/W

siteco

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 461 cd/klm**



Classifications

DIN 5040	A 5 1
CIE	N1=61 N2=87 N3=97 N4=97 N5=100

Luminaire light output ratios

ηLB	100.0%
ϕ_u	96.9%
ϕ_o	3.1%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family	Order number: 51MP26WD2M42W	LP number
Apollon® rectangular	EAN: 4069025343895	59344_120

siteco

Table of values for luminous intensities

Maximum luminous intensity

C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	461.4	461.4	461.4	461.4	461.4	461.4	461.4	2.8	2.8
5°	459.4	459.1	459.2	459.1	459.1	458.9	459.2	21.9	24.7
10°	452.8	452.3	452.6	452.2	452.5	452.2	452.4	43.1	67.8
15°	442.1	441.3	442.0	441.6	442.2	441.7	442.0	62.7	130.4
20°	426.8	425.8	426.8	426.4	427.3	426.7	427.3	80.0	210.4
25°	405.3	404.1	405.7	405.3	406.7	406.0	406.9	94.0	304.4
30°	373.7	372.1	374.7	374.3	376.6	375.8	377.3	102.7	407.1
35°	329.4	327.4	330.7	330.2	332.9	331.2	333.4	104.0	511.1
40°	276.6	274.1	276.8	275.9	278.9	276.1	277.7	97.4	608.5
45°	222.9	219.6	220.9	219.3	222.4	217.7	218.2	85.3	693.8
50°	174.4	171.2	171.4	169.7	171.1	166.2	166.5	71.4	765.2
55°	133.1	129.8	129.4	127.3	127.2	122.9	123.6	57.2	822.4
60°	100.8	96.8	95.6	92.8	92.4	88.6	88.7	44.4	866.8
65°	76.9	72.2	70.3	66.6	66.9	62.9	62.1	33.8	900.6
70°	59.3	54.7	52.5	48.1	48.7	44.3	43.1	25.7	926.3
75°	45.5	41.8	39.8	34.7	34.7	30.6	29.6	19.3	945.7
80°	34.6	31.6	29.4	23.8	22.7	19.7	19.2	13.9	959.5
85°	22.2	20.2	18.0	13.5	12.3	10.0	9.8	8.2	967.7
90°	13.3	11.8	8.8	5.0	3.4	2.0	1.4	3.5	971.2
95°	12.6	11.5	8.3	4.7	2.9	1.3	1.0	3.2	974.5
100°	12.4	11.4	8.1	4.6	2.9	1.5	0.9	3.2	977.6
105°	11.8	10.9	7.8	4.6	2.9	1.5	0.8	3.0	980.6
110°	11.2	10.3	7.6	4.6	2.9	1.5	0.8	2.8	983.4
115°	10.7	9.8	7.6	4.9	2.9	1.5	0.8	2.7	986.1
120°	10.1	9.4	7.4	5.0	2.9	1.5	0.7	2.5	988.6
125°	9.4	8.7	7.1	4.9	3.0	1.5	0.7	2.3	990.9
130°	8.6	8.0	6.6	4.9	3.0	1.5	0.7	2.0	992.9
135°	7.8	7.3	6.3	4.7	2.9	1.4	0.6	1.7	994.6
140°	7.1	6.7	5.8	4.4	2.8	1.4	0.7	1.5	996.1
145°	6.4	6.1	5.2	4.0	2.7	1.5	0.8	1.2	997.3
150°	5.6	5.3	4.6	3.6	2.5	1.5	1.0	1.0	998.2
155°	4.8	4.5	4.0	3.2	2.2	1.5	1.1	0.7	998.9
160°	3.9	3.7	3.3	2.6	1.9	1.5	1.2	0.5	999.4
165°	3.1	2.9	2.7	2.2	1.8	1.5	1.3	0.3	999.7
170°	2.3	2.3	2.1	1.8	1.6	1.5	1.4	0.2	999.9
175°	1.8	1.7	1.6	1.5	1.5	1.5	1.4	0.1	1000.0
180°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.0	1000.0

Photometric test report

Family	Order number: 51MP26WD2M42W	LP number
Apollon® rectangular	EAN: 4069025343895	59344_120

siteco

UGR-Table

Standard room

Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	17.5	19.1	17.9	19.4	19.7	17.4	19.0	17.8	19.3	19.6
	3H	18.5	19.9	18.9	20.2	20.6	18.1	19.5	18.5	19.9	20.2
	4H	19.0	20.3	19.4	20.6	21.0	18.4	19.7	18.8	20.1	20.5
	6H	19.5	20.7	19.9	21.0	21.4	18.7	19.9	19.1	20.3	20.7
	8H	19.8	20.9	20.2	21.2	21.7	18.9	20.0	19.3	20.3	20.7
	12H	20.0	21.0	20.4	21.4	21.8	19.0	20.0	19.4	20.4	20.8
4H	2H	17.9	19.2	18.3	19.6	19.9	17.8	19.1	18.2	19.5	19.9
	3H	19.0	20.1	19.5	20.5	20.9	18.8	19.8	19.2	20.2	20.6
	4H	19.7	20.7	20.1	21.1	21.5	19.2	20.1	19.6	20.6	21.0
	6H	20.3	21.2	20.8	21.6	22.1	19.5	20.4	20.0	20.8	21.3
	8H	20.7	21.4	21.1	21.9	22.4	19.7	20.5	20.2	20.9	21.4
	12H	21.0	21.7	21.5	22.1	22.6	19.8	20.5	20.3	21.0	21.5
8H	4H	19.9	20.6	20.3	21.1	21.6	19.4	20.2	19.9	20.6	21.1
	6H	20.7	21.3	21.2	21.8	22.3	19.9	20.5	20.4	21.0	21.5
	8H	21.1	21.7	21.6	22.2	22.7	20.1	20.7	20.6	21.2	21.7
	12H	21.5	22.0	22.0	22.5	23.0	20.3	20.8	20.8	21.3	21.8
12H	4H	19.9	20.6	20.4	21.0	21.5	19.5	20.1	19.9	20.6	21.1
	6H	20.7	21.3	21.2	21.8	22.3	20.0	20.5	20.5	21.0	21.5
	8H	21.2	21.7	21.7	22.2	22.7	20.2	20.7	20.8	21.2	21.8

Luminance table

Max. for $\gamma >= 65°$

Photometric dimensions in mm: L = 1534 B = 200 H(C0) = 13 H(C90) = 0 H(C180) = 13 H(C270) = 0

C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	7138.6	7047.7	7132.2	7153.1	7348.0	7303.7	7442.9
50°	6074.6	5977.0	6025.7	6037.0	6179.6	6115.0	6249.3
55°	5121.5	5007.4	5034.7	5022.4	5109.8	5048.6	5195.8
60°	4372.4	4213.1	4201.1	4148.3	4218.8	4154.9	4276.6
65°	3853.3	3631.9	3577.9	3462.1	3569.5	3464.1	3545.8
70°	3547.9	3287.2	3206.0	3010.7	3153.3	2988.7	3039.2
75°	3413.7	3155.7	3068.3	2757.9	2882.6	2685.4	2756.3
80°	3508.4	3240.4	3096.4	2619.6	2662.2	2498.8	2663.8
85°	3517.3	3247.5	3028.8	2453.5	2481.2	2329.7	2714.9


Photometric test report

Family	Order number: 51MP26WD2M42W	LP number
Apollon® rectangular	**EAN: 4069025343895**	**59344_120**

Luminance values in cd/m²

γ 65° γ 70° γ 75° γ 80° γ 85°

siteco



Photometric test report

Family	Order number: 51MP26WD2M42W	LP number
Apollon® rectangular	**EAN: 4069025343895**	**59344_120**

siteco

Multilumen Table

environmental temperature: 25°C

DIP-Step	Switch Setting 1	2	3	4	Luminous flux [lm]	Power consumption [W]
10	OFF	ON	OFF	ON	7400	57.0
11	ON	ON	OFF	ON	6400	48.0
12	OFF	OFF	ON	ON	5400	40.0
13	ON	OFF	ON	ON	4400	32.0