Photometric test report

Family
Apollon® rectangular



Order number: 51MP26WM2M42W
EAN: 4069025343918


LP number
59344_127

serial documentation
20.05.2026

Version	surface-mounted and suspended luminaire, microprismatic optics, wide distribution, UGR≤22, adjustable color temperature: 3000 K | 3500 K | 4000K
Lamps	LED 3500 K | CRI ≥ 80
Controlgear	ECG-DALI-Multilumen
Setting	individual position: DIP-Step=3, colour temperature 3500K
Rated values	Net luminous flux = 8000 lm Power consumption = 55.0 W Luminous efficacy = 145.5 lm/W

siteco

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 461 cd/klm**



Classifications

DIN 5040	A 5 1
CIE	N1=61 N2=87 N3=97 N4=97 N5=100

Luminaire light output ratios

ηLB	100.0%
ϕ_u	96.9%
ϕ_o	3.1%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family	Order number: 51MP26WM2M42W	LP number
Apollon® rectangular	EAN: 4069025343918	59344_127

siteco

Table of values for luminous intensities

Maximum luminous intensity

C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	461.4	461.4	461.4	461.4	461.4	461.4	461.4	2.8	2.8
5°	459.4	459.1	459.2	459.1	459.1	458.9	459.2	21.9	24.7
10°	452.8	452.3	452.6	452.2	452.5	452.2	452.4	43.1	67.8
15°	442.1	441.3	442.0	441.6	442.2	441.7	442.0	62.7	130.4
20°	426.8	425.8	426.8	426.4	427.3	426.7	427.3	80.0	210.4
25°	405.3	404.1	405.7	405.3	406.7	406.0	406.9	94.0	304.4
30°	373.7	372.1	374.7	374.3	376.6	375.8	377.3	102.7	407.1
35°	329.4	327.4	330.7	330.2	332.9	331.2	333.4	104.0	511.1
40°	276.6	274.1	276.8	275.9	278.9	276.1	277.7	97.4	608.5
45°	222.9	219.6	220.9	219.3	222.4	217.7	218.2	85.3	693.8
50°	174.4	171.2	171.4	169.7	171.1	166.2	166.5	71.4	765.2
55°	133.1	129.8	129.4	127.3	127.2	122.9	123.6	57.2	822.4
60°	100.8	96.8	95.6	92.8	92.4	88.6	88.7	44.4	866.8
65°	76.9	72.2	70.3	66.6	66.9	62.9	62.1	33.8	900.6
70°	59.3	54.7	52.5	48.1	48.7	44.3	43.1	25.7	926.3
75°	45.5	41.8	39.8	34.7	34.7	30.6	29.6	19.3	945.7
80°	34.6	31.6	29.4	23.8	22.7	19.7	19.2	13.9	959.5
85°	22.2	20.2	18.0	13.5	12.3	10.0	9.8	8.2	967.7
90°	13.3	11.8	8.8	5.0	3.4	2.0	1.4	3.5	971.2
95°	12.6	11.5	8.3	4.7	2.9	1.3	1.0	3.2	974.5
100°	12.4	11.4	8.1	4.6	2.9	1.5	0.9	3.2	977.6
105°	11.8	10.9	7.8	4.6	2.9	1.5	0.8	3.0	980.6
110°	11.2	10.3	7.6	4.6	2.9	1.5	0.8	2.8	983.4
115°	10.7	9.8	7.6	4.9	2.9	1.5	0.8	2.7	986.1
120°	10.1	9.4	7.4	5.0	2.9	1.5	0.7	2.5	988.6
125°	9.4	8.7	7.1	4.9	3.0	1.5	0.7	2.3	990.9
130°	8.6	8.0	6.6	4.9	3.0	1.5	0.7	2.0	992.9
135°	7.8	7.3	6.3	4.7	2.9	1.4	0.6	1.7	994.6
140°	7.1	6.7	5.8	4.4	2.8	1.4	0.7	1.5	996.1
145°	6.4	6.1	5.2	4.0	2.7	1.5	0.8	1.2	997.3
150°	5.6	5.3	4.6	3.6	2.5	1.5	1.0	1.0	998.2
155°	4.8	4.5	4.0	3.2	2.2	1.5	1.1	0.7	998.9
160°	3.9	3.7	3.3	2.6	1.9	1.5	1.2	0.5	999.4
165°	3.1	2.9	2.7	2.2	1.8	1.5	1.3	0.3	999.7
170°	2.3	2.3	2.1	1.8	1.6	1.5	1.4	0.2	999.9
175°	1.8	1.7	1.6	1.5	1.5	1.5	1.4	0.1	1000.0
180°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.0	1000.0

Photometric test report

Family	Order number: 51MP26WM2M42W	LP number
Apollon® rectangular	EAN: 4069025343918	59344_127

siteco

UGR-Table

Standard room

Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	17.8	19.3	18.2	19.7	20.0	17.7	19.3	18.1	19.6	19.9
	3H	18.8	20.1	19.1	20.5	20.8	18.4	19.8	18.8	20.1	20.5
	4H	19.2	20.5	19.6	20.9	21.3	18.7	20.0	19.1	20.4	20.7
	6H	19.8	20.9	20.2	21.3	21.7	19.0	20.2	19.4	20.5	20.9
	8H	20.1	21.1	20.5	21.5	21.9	19.1	20.2	19.6	20.6	21.0
	12H	20.3	21.3	20.7	21.7	22.1	19.2	20.3	19.7	20.6	21.1
4H	2H	18.2	19.5	18.6	19.8	20.2	18.1	19.4	18.5	19.8	20.1
	3H	19.3	20.4	19.7	20.8	21.2	19.0	20.1	19.4	20.5	20.9
	4H	19.9	20.9	20.4	21.3	21.8	19.4	20.4	19.9	20.8	21.3
	6H	20.6	21.5	21.1	21.9	22.3	19.8	20.7	20.3	21.1	21.6
	8H	20.9	21.7	21.4	22.2	22.6	20.0	20.7	20.4	21.2	21.7
	12H	21.3	21.9	21.7	22.4	22.9	20.1	20.8	20.6	21.3	21.7
8H	4H	20.1	20.9	20.6	21.4	21.8	19.7	20.4	20.1	20.9	21.4
	6H	20.9	21.6	21.4	22.1	22.6	20.2	20.8	20.7	21.3	21.8
	8H	21.4	21.9	21.9	22.4	22.9	20.4	21.0	20.9	21.4	22.0
	12H	21.8	22.3	22.3	22.8	23.3	20.6	21.1	21.1	21.6	22.1
12H	4H	20.2	20.8	20.6	21.3	21.8	19.7	20.4	20.2	20.9	21.4
	6H	21.0	21.6	21.5	22.0	22.6	20.3	20.8	20.8	21.3	21.8
	8H	21.5	21.9	22.0	22.4	23.0	20.5	21.0	21.0	21.5	22.0

Luminance table

Max. for $\gamma >= 65°$

Photometric dimensions in mm: L = 1534, B = 200, H(C0) = 13, H(C90) = 0, H(C180) = 13, H(C270) = 0

C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	7717.4	7619.1	7710.5	7733.1	7943.8	7895.9	8046.4
50°	6567.1	6461.6	6514.3	6526.5	6680.7	6610.8	6756.0
55°	5536.8	5413.4	5442.9	5429.6	5524.2	5457.9	5617.0
60°	4726.9	4554.7	4541.7	4484.7	4560.9	4491.7	4623.4
65°	4165.7	3926.3	3868.0	3742.8	3859.0	3745.0	3833.2
70°	3835.5	3553.7	3465.9	3254.8	3409.0	3231.0	3285.6
75°	3690.5	3411.6	3317.1	2981.5	3116.3	2903.1	2979.7
80°	3792.8	3503.2	3347.5	2832.0	2878.1	2701.4	2879.8
85°	3802.5	3510.8	3274.4	2652.4	2682.3	2518.6	2935.0


Photometric test report

Family	Order number: 51MP26WM2M42W	LP number
Apollon® rectangular	**EAN: 4069025343918**	**59344_127**

Luminance values in cd/m²

γ 65° γ 70° γ 75° γ 80° γ 85°

siteco



Photometric test report

Family	Order number: 51MP26WM2M42W	LP number
Apollon® rectangular	**EAN: 4069025343918**	**59344_127**

siteco

Multilumen Table

environmental temperature: 25°C

DIP-Step	1	Switch Setting2	Luminous flux [lm]	Power consumption [W]
3	**ON**	**ON**	8000	55.0
2	**OFF**	**ON**	6900	47.0
1	**ON**	**OFF**	5800	39.0
0	**OFF**	**OFF**	4700	32.0