




Photometric test report

Family Spot 21 Licross®	Order number: 51SL14MB11A2C EAN: 4069025502490	LP number 59931_37
	Version housing, white, reflector, cover glass, transparent, wide distribution Lamps LED 2700 K CRI ≥ 90 Controlgear ECG Multilumen Setting factory setting: DIP-Step=4	serial documentation 21.05.2026
	Rated values Net luminous flux = 2710 lm Power consumption = 18.5 W Luminous efficacy = 146.5 lm/W	

Luminous intensity in cd/klm C180-0 **Imax: 1454 cd/klm**



Classifications	
DIN 5040	A 7 0
CIE	N1=94 N2=98 N3=100 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Spot 21 Licross®	Order number: 51SL14MB11A2C EAN: 4069025502490	LP number 59931_37
-----------------------------------	---	------------------------------

sITeco

Table of values for luminous intensities	Maximum luminous intensity
---	-----------------------------------

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm	Luminous flux in lm/klm	
0,0°	1453.7	2.2	2.2
2,5°	1438.9	17.2	19.4
5,0°	1404.1	33.5	52.9
7,5°	1351.1	48.3	101.3
10,0°	1289.5	61.4	162.7
12,5°	1223.4	72.6	235.2
15,0°	1148.5	81.5	316.7
17,5°	1063.6	87.7	404.4
20,0°	985.2	92.4	496.8
22,5°	896.4	94.0	590.8
25,0°	801.5	92.9	683.7
27,5°	663.4	84.0	767.6
30,0°	489.2	67.1	834.7
32,5°	307.3	45.3	880.0
35,0°	173.2	27.2	907.2
37,5°	114.5	19.1	926.3
40,0°	77.4	13.6	940.0
42,5°	52.8	9.8	949.7
45,0°	37.7	7.3	957.0
47,5°	28.4	5.7	962.8
50,0°	22.7	4.8	967.6
52,5°	19.1	4.2	971.7
55,0°	16.7	3.8	975.5
57,5°	15.0	3.5	978.9
60,0°	13.6	3.2	982.2
62,5°	12.4	3.0	985.2
65,0°	11.2	2.8	988.0
67,5°	10.1	2.6	990.6
70,0°	9.0	2.3	992.9
72,5°	7.7	2.0	994.9
75,0°	6.2	1.6	996.5
77,5°	4.7	1.3	997.8
80,0°	3.6	1.0	998.8
82,5°	2.5	0.7	999.5
85,0°	1.5	0.4	999.9
87,5°	0.5	0.1	1000.0
90,0°	0.0	0.0	1000.0

Photometric test report

Family Spot 21 Licross®	Order number: 51SL14MB11A2C EAN: 4069025502490	LP number 59931_37
-----------------------------------	---	------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	19.5	20.6	19.8	20.9	21.2	19.5	20.6	19.8	20.9	21.2
	3H	19.8	20.8	20.2	21.1	21.5	19.8	20.8	20.2	21.1	21.5
	4H	20.0	20.9	20.3	21.2	21.6	20.0	20.9	20.3	21.2	21.6
	6H	20.0	20.9	20.5	21.2	21.6	20.0	20.9	20.5	21.2	21.6
	8H	20.2	20.9	20.7	21.3	21.7	20.2	20.9	20.7	21.3	21.7
	12H	20.2	20.8	20.7	21.2	21.6	20.2	20.8	20.7	21.2	21.6
4H	2H	19.5	20.4	19.9	20.7	21.1	19.5	20.4	19.9	20.7	21.1
	3H	19.9	20.7	20.3	21.0	21.5	19.9	20.7	20.3	21.0	21.5
	4H	20.2	20.8	20.6	21.2	21.7	20.2	20.8	20.6	21.2	21.7
	6H	20.3	20.9	20.8	21.3	21.8	20.3	20.9	20.8	21.3	21.8
	8H	20.4	20.9	20.9	21.4	21.8	20.4	20.9	20.9	21.4	21.8
	12H	20.5	20.9	21.0	21.3	21.9	20.5	20.9	21.0	21.3	21.9
8H	4H	20.2	20.7	20.7	21.2	21.6	20.2	20.7	20.7	21.2	21.6
	6H	20.5	20.9	21.0	21.3	21.9	20.5	20.9	21.0	21.3	21.9
	8H	20.5	20.9	21.1	21.4	21.9	20.5	20.9	21.1	21.4	21.9
	12H	20.6	20.9	21.2	21.4	22.0	20.6	20.9	21.2	21.4	22.0
12H	4H	20.2	20.6	20.7	21.1	21.6	20.2	20.6	20.7	21.1	21.6
	6H	20.5	20.8	21.0	21.3	21.8	20.5	20.8	21.0	21.3	21.8
	8H	20.6	20.9	21.1	21.4	21.9	20.6	20.9	21.1	21.4	21.9


Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 82
------------------------	---	---

C-planes	0°
γ	Luminance in cd/m²
45,0°	27339.2
50,0°	18156.5
55,0°	14969.5
60,0°	13984.6
65,0°	13625.0
70,0°	13528.9
75,0°	12316.5
80,0°	10659.3
85,0°	8849.4

Photometric test report

Family Spot 21 Licross®	Order number: 51SL14MB11A2C EAN: 4069025502490	LP number 59931_37
-----------------------------------	---	------------------------------

Luminance values in cd/m²
γ 65°
γ 70°
γ 75°
γ 80°
γ 85°
siteco



Photometric test report

Family Spot 21 Licross®	Order number: 51SL14MB11A2C EAN: 4069025502490	LP number 59931_37
--	---	-------------------------------------

Multilumen Table	environmental temperature: 25°C	
-------------------------	---------------------------------	---

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]
	1	2	3		
0	OFF	OFF	OFF	3650	26.5
1	ON	OFF	OFF	3420	24.5
2	OFF	ON	OFF	3190	22.5
3	ON	ON	OFF	2950	20.5
4	OFF	OFF	ON	2710	18.5
5	ON	OFF	ON	2460	16.6
6	OFF	ON	ON	2210	14.8
7	ON	ON	ON	1950	12.9