




Photometric test report

Family Spot 21 Licross®	Order number: 51SL63MB11B2C EAN: 4069025502681	LP number 59936_34
	Version housing, white aluminium, reflector, cover glass, transparent, medium distribution	serial documentation 21.05.2026
	Lamps LED 3000 K CRI ≥ 90	
Controlgear ECG Multilumen		
Setting factory setting: DIP-Step=4		
Rated values	Net luminous flux = 2810 lm Power consumption = 18.5 W Luminous efficacy = 151.9 lm/W	
		

Luminous intensity in cd/klm C180-0 **I_{max}: 2273 cd/klm**



Classifications	
DIN 5040	A 8 0
CIE	N1=98 N2=99 N3=100 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Spot 21 Licross®	Order number: 51SL63MB11B2C EAN: 4069025502681	LP number 59936_34
--	---	-------------------------------------

sITeco

Table of values for luminous intensities	Maximum luminous intensity
---	-----------------------------------

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm	Luminous flux in lm/klm	
0,0°	2272.8	3.4	3.4
2,5°	2247.7	26.9	30.3
5,0°	2167.7	51.8	82.1
7,5°	2040.8	73.0	155.1
10,0°	1880.0	89.5	244.6
12,5°	1690.1	100.3	344.9
15,0°	1482.7	105.2	450.1
17,5°	1267.9	104.5	554.6
20,0°	1065.6	99.9	654.5
22,5°	874.9	91.8	746.3
25,0°	714.3	82.8	829.0
27,5°	533.8	67.6	896.6
30,0°	335.3	46.0	942.6
32,5°	151.5	22.3	964.9
35,0°	44.0	6.9	971.8
37,5°	23.3	3.9	975.7
40,0°	17.4	3.1	978.7
42,5°	13.8	2.6	981.3
45,0°	11.3	2.2	983.5
47,5°	9.4	1.9	985.4
50,0°	8.2	1.7	987.1
52,5°	7.3	1.6	988.7
55,0°	6.6	1.5	990.2
57,5°	6.0	1.4	991.6
60,0°	5.5	1.3	992.9
62,5°	5.0	1.2	994.1
65,0°	4.6	1.1	995.3
67,5°	4.1	1.0	996.3
70,0°	3.6	0.9	997.2
72,5°	3.0	0.8	998.0
75,0°	2.3	0.6	998.6
77,5°	1.8	0.5	999.1
80,0°	1.4	0.4	999.5
82,5°	1.0	0.3	999.8
85,0°	0.6	0.2	999.9
87,5°	0.2	0.1	1000.0
90,0°	0.0	0.0	1000.0

Photometric test report

Family Spot 21 Licross®	Order number: 51SL63MB11B2C EAN: 4069025502681	LP number 59936_34
-----------------------------------	---	------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	13.7	14.7	14.1	15.0	15.4	13.7	14.7	14.1	15.0	15.4
	3H	14.0	14.9	14.4	15.2	15.6	14.0	14.9	14.4	15.2	15.6
	4H	14.1	14.9	14.5	15.3	15.6	14.1	14.9	14.5	15.3	15.6
	6H	14.2	14.9	14.6	15.3	15.7	14.2	14.9	14.6	15.3	15.7
	8H	14.4	14.9	14.8	15.3	15.7	14.4	14.9	14.8	15.3	15.7
12H	14.3	14.8	14.8	15.2	15.6	14.3	14.8	14.8	15.2	15.6	
4H	2H	13.7	14.5	14.1	14.8	15.2	13.7	14.5	14.1	14.8	15.2
	3H	14.0	14.7	14.5	15.1	15.5	14.0	14.7	14.5	15.1	15.5
	4H	14.2	14.8	14.7	15.2	15.7	14.2	14.8	14.7	15.2	15.7
	6H	14.3	14.9	14.8	15.3	15.8	14.3	14.9	14.8	15.3	15.8
	8H	14.4	14.9	14.9	15.3	15.8	14.4	14.9	14.9	15.3	15.8
12H	14.5	14.8	15.0	15.3	15.8	14.5	14.8	15.0	15.3	15.8	
8H	4H	14.2	14.7	14.7	15.1	15.6	14.2	14.7	14.7	15.1	15.6
	6H	14.5	14.8	15.0	15.3	15.8	14.5	14.8	15.0	15.3	15.8
	8H	14.5	14.8	15.0	15.3	15.8	14.5	14.8	15.0	15.3	15.8
	12H	14.6	14.8	15.1	15.3	15.9	14.6	14.8	15.1	15.3	15.9
12H	4H	14.2	14.6	14.7	15.0	15.5	14.2	14.6	14.7	15.0	15.5
	6H	14.4	14.7	15.0	15.2	15.7	14.4	14.7	15.0	15.2	15.7
	8H	14.5	14.8	15.1	15.3	15.8	14.5	14.8	15.1	15.3	15.8

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 82
------------------------	---	---

C-planes	0°
γ	Luminance in cd/m²
45,0°	8529.5
50,0°	6808.6
55,0°	6141.2
60,0°	5871.1
65,0°	5809.2
70,0°	5617.8
75,0°	4742.9
80,0°	4302.2
85,0°	3675.3


Photometric test report

Family Spot 21 Licross®	Order number: 51SL63MB11B2C EAN: 4069025502681	LP number 59936_34
-----------------------------------	---	------------------------------



Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°



Photometric test report

Family Spot 21 Licross®	Order number: 51SL63MB11B2C EAN: 4069025502681	LP number 59936_34
--	---	-------------------------------------

Multilumen Table	environmental temperature: 25°C	
-------------------------	---------------------------------	---

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]
	1	2	3		
0	OFF	OFF	OFF	3780	26.5
1	ON	OFF	OFF	3540	24.5
2	OFF	ON	OFF	3300	22.5
3	ON	ON	OFF	3060	20.5
4	OFF	OFF	ON	2810	18.5
5	ON	OFF	ON	2550	16.6
6	OFF	ON	ON	2290	14.8
7	ON	ON	ON	2020	12.9