




Photometric test report

Family Spot 21 Licross®	Order number: 51SL64MB11D2C EAN: 4069025502759	LP number 59937_36										
	<table border="0"> <tr> <td>Version</td> <td>housing, white aluminium, reflector, cover glass, transparent, wide distribution</td> </tr> <tr> <td>Lamps</td> <td>LED 4000 K CRI ≥ 90</td> </tr> <tr> <td>Controlgear</td> <td>ECG Multilumen</td> </tr> <tr> <td>Setting</td> <td>factory setting: DIP-Step=4</td> </tr> <tr> <td>Rated values</td> <td>Net luminous flux = 2830 lm Power consumption = 18.5 W Luminous efficacy = 153 lm/W</td> </tr> </table>	Version	housing, white aluminium, reflector, cover glass, transparent, wide distribution	Lamps	LED 4000 K CRI ≥ 90	Controlgear	ECG Multilumen	Setting	factory setting: DIP-Step=4	Rated values	Net luminous flux = 2830 lm Power consumption = 18.5 W Luminous efficacy = 153 lm/W	serial documentation 21.05.2026 
Version	housing, white aluminium, reflector, cover glass, transparent, wide distribution											
Lamps	LED 4000 K CRI ≥ 90											
Controlgear	ECG Multilumen											
Setting	factory setting: DIP-Step=4											
Rated values	Net luminous flux = 2830 lm Power consumption = 18.5 W Luminous efficacy = 153 lm/W											

Luminous intensity in cd/klm C180-0 **I_{max}: 1410 cd/klm**



Classifications	
DIN 5040	A 7 0
CIE	N1=96 N2=99 N3=100 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Spot 21 Licross®	Order number: 51SL64MB11D2C EAN: 4069025502759	LP number 59937_36
--	---	-------------------------------------

sITeco

Table of values for luminous intensities	Maximum luminous intensity
---	-----------------------------------

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm	Luminous flux in lm/klm	
0,0°	1409.8	2.1	2.1
2,5°	1402.5	16.8	18.9
5,0°	1383.3	33.0	51.9
7,5°	1350.1	48.3	100.2
10,0°	1305.8	62.2	162.4
12,5°	1250.9	74.2	236.6
15,0°	1183.2	84.0	320.6
17,5°	1103.1	90.9	411.5
20,0°	1024.9	96.1	507.6
22,5°	937.8	98.4	606.0
25,0°	838.9	97.2	703.2
27,5°	692.9	87.7	790.9
30,0°	508.4	69.7	860.5
32,5°	313.6	46.2	906.7
35,0°	170.0	26.7	933.5
37,5°	107.2	17.9	951.4
40,0°	69.8	12.3	963.7
42,5°	45.7	8.5	972.1
45,0°	29.8	5.8	977.9
47,5°	20.8	4.2	982.1
50,0°	15.0	3.2	985.3
52,5°	11.4	2.5	987.7
55,0°	9.1	2.0	989.8
57,5°	7.4	1.7	991.5
60,0°	6.2	1.5	993.0
62,5°	5.4	1.3	994.3
65,0°	4.6	1.1	995.4
67,5°	4.0	1.0	996.5
70,0°	3.5	0.9	997.4
72,5°	2.9	0.8	998.1
75,0°	2.3	0.6	998.7
77,5°	1.7	0.5	999.2
80,0°	1.3	0.4	999.5
82,5°	0.9	0.2	999.8
85,0°	0.6	0.2	999.9
87,5°	0.2	0.1	1000.0
90,0°	0.0	0.0	1000.0

Photometric test report

Family Spot 21 Licross®	Order number: 51SL64MB11D2C EAN: 4069025502759	LP number 59937_36
-----------------------------------	---	------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	19.1	20.2	19.4	20.5	20.8	19.1	20.2	19.4	20.5	20.8
	3H	19.0	20.0	19.4	20.3	20.7	19.0	20.0	19.4	20.3	20.7
	4H	19.0	19.8	19.4	20.2	20.6	19.0	19.8	19.4	20.2	20.6
	6H	18.9	19.7	19.3	20.1	20.5	18.9	19.7	19.3	20.1	20.5
	8H	19.0	19.6	19.5	20.0	20.4	19.0	19.6	19.5	20.0	20.4
	12H	19.0	19.6	19.4	19.9	20.4	19.0	19.6	19.4	19.9	20.4
4H	2H	18.9	19.8	19.3	20.1	20.5	18.9	19.8	19.3	20.1	20.5
	3H	18.8	19.5	19.2	19.9	20.3	18.8	19.5	19.2	19.9	20.3
	4H	18.8	19.4	19.2	19.8	20.3	18.8	19.4	19.2	19.8	20.3
	6H	18.7	19.3	19.2	19.7	20.2	18.7	19.3	19.2	19.7	20.2
	8H	18.7	19.2	19.2	19.6	20.1	18.7	19.2	19.2	19.6	20.1
	12H	18.7	19.1	19.2	19.6	20.1	18.7	19.1	19.2	19.6	20.1
8H	4H	18.7	19.2	19.2	19.6	20.1	18.7	19.2	19.2	19.6	20.1
	6H	18.7	19.0	19.2	19.5	20.0	18.7	19.0	19.2	19.5	20.0
	8H	18.6	18.9	19.1	19.4	20.0	18.6	18.9	19.1	19.4	20.0
	12H	18.6	18.9	19.1	19.4	19.9	18.6	18.9	19.1	19.4	19.9
12H	4H	18.7	19.0	19.2	19.5	20.0	18.7	19.0	19.2	19.5	20.0
	6H	18.6	18.9	19.1	19.4	19.9	18.6	18.9	19.1	19.4	19.9
	8H	18.6	18.8	19.1	19.4	19.9	18.6	18.8	19.1	19.4	19.9

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 82
------------------------	---	---

C-planes	0°
γ	Luminance in cd/m²
45,0°	22550.6
50,0°	12528.6
55,0°	8517.8
60,0°	6657.8
65,0°	5844.2
70,0°	5494.8
75,0°	4770.4
80,0°	4018.0
85,0°	3695.3


Photometric test report

Family Spot 21 Licross®	Order number: 51SL64MB11D2C EAN: 4069025502759	LP number 59937_36
--	---	-------------------------------------

Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°

sitEco



Photometric test report

Family Spot 21 Licross®	Order number: 51SL64MB11D2C EAN: 4069025502759	LP number 59937_36
-----------------------------------	---	------------------------------

Multilumen Table	environmental temperature: 25°C	sITeco
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]
	1	2	3		
0	OFF	OFF	OFF	3810	26.5
1	ON	OFF	OFF	3570	24.5
2	OFF	ON	OFF	3330	22.5
3	ON	ON	OFF	3080	20.5
4	OFF	OFF	ON	2830	18.5
5	ON	OFF	ON	2570	16.6
6	OFF	ON	ON	2300	14.8
7	ON	ON	ON	2030	12.9