

Photometric test report

Family
Silhouette® 21

Order number: **51LN12NKM40A**
EAN: **4069025398239**

LP number
59582_28



Version surface-mounted luminaire, white, diffuser, PMMA, opal, with homogeneous illumination, extremely wide distribution, adjustable color temperature: 3000K | 4000K | 5000K

Lamps LED 4000 K | CRI ≥ 80

Controlgear ECG-DALI-Multilumen

Setting factory setting: DIP-Step=2, colour temperature 4000K

Rated values Net luminous flux = 4910 lm
Power consumption = 34.0 W
Luminous efficacy = 144.4 lm/W

serial
documentation
17.06.2026


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 296 cd/klm



Classifications

DIN 5040 A 3 1
CIE N1=43 N2=73 N3=92
N4=94 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 93.9%
 ϕ_o 6.1%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Silhouette® 21	Order number: 51LN12NKM40A EAN: 4069025398239	LP number 59582_28
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	295.9	295.9	295.9	295.9	295.9	295.9	295.9	1.8	1.8
5°	294.8	294.8	294.8	294.8	294.7	294.7	294.7	14.1	15.9
10°	291.5	291.5	291.4	291.2	291.1	291.0	291.0	27.7	43.6
15°	286.0	286.0	285.8	285.5	285.1	284.9	284.9	40.5	84.1
20°	278.5	278.4	277.9	277.3	276.8	276.4	276.3	52.0	136.1
25°	269.0	268.7	268.0	267.0	266.1	265.6	265.4	61.9	197.9
30°	257.6	257.2	256.2	254.8	253.4	252.6	252.3	69.8	267.8
35°	244.0	243.7	242.4	240.6	238.6	237.4	237.0	75.6	343.4
40°	228.7	228.2	226.6	224.4	222.0	220.3	219.8	79.0	422.4
45°	211.7	211.0	209.2	206.5	203.7	201.4	200.8	80.0	502.4
50°	193.1	192.3	190.2	187.0	183.7	181.0	180.2	78.4	580.9
55°	173.2	172.4	169.9	166.3	162.4	159.2	158.1	74.5	655.4
60°	152.5	151.5	148.7	144.5	140.0	136.2	134.9	68.4	723.8
65°	131.3	130.2	126.9	122.2	117.0	112.6	110.8	60.4	784.2
70°	111.3	109.8	105.4	99.6	93.6	88.4	86.2	51.1	835.3
75°	92.9	91.2	86.0	78.5	70.7	64.7	62.0	41.3	876.7
80°	76.4	74.5	68.7	60.2	50.1	42.0	38.6	31.8	908.5
85°	61.7	59.7	53.7	44.6	33.4	22.3	17.3	23.0	931.5
90°	48.4	46.4	40.5	31.6	20.6	9.3	0.5	15.8	947.3
95°	37.0	35.0	29.6	21.4	11.8	3.6	0.6	10.9	958.2
100°	27.5	25.8	21.0	14.1	7.2	3.0	0.8	7.7	965.9
105°	20.0	18.6	14.7	9.9	5.9	2.9	1.1	5.5	971.4
110°	14.9	13.8	11.4	8.5	5.7	3.0	1.4	4.3	975.7
115°	12.5	11.8	10.3	8.2	5.5	3.0	1.6	3.8	979.5
120°	11.7	11.3	10.0	7.7	5.3	3.1	1.8	3.5	983.0
125°	11.1	10.6	9.3	7.1	5.1	3.1	2.0	3.1	986.2
130°	10.5	10.0	8.7	6.8	4.9	3.2	2.2	2.8	989.0
135°	9.8	9.4	8.0	6.3	4.7	3.2	2.4	2.4	991.4
140°	9.1	8.7	7.2	5.9	4.6	3.3	2.7	2.1	993.5
145°	8.3	8.0	6.6	5.5	4.4	3.5	3.0	1.8	995.3
150°	7.5	7.2	6.0	5.1	4.3	3.7	3.3	1.5	996.7
155°	6.8	6.3	5.5	4.8	4.2	3.9	3.6	1.1	997.9
160°	6.0	5.4	4.9	4.5	4.2	4.0	3.8	0.9	998.7
165°	5.3	4.7	4.4	4.4	4.3	4.2	4.1	0.6	999.4
170°	4.8	4.2	4.3	4.3	4.3	4.3	4.2	0.4	999.8
175°	4.4	4.0	4.2	4.3	4.4	4.4	4.4	0.2	1000.0
180°	4.3	4.3	4.3	4.3	4.3	4.3	4.3	0.0	1000.0

Photometric test report

Family Silhouette® 21			Order number: 51LN12NKM40A EAN: 4069025398239							LP number 59582_28	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	19.1	20.8	19.4	21.1	21.4	19.1	20.8	19.5	21.2	21.5
	3H	20.9	22.5	21.3	22.8	23.2	20.8	22.4	21.2	22.7	23.1
	4H	21.8	23.3	22.2	23.6	24.0	21.5	23.0	21.9	23.3	23.7
	6H	22.6	24.0	23.0	24.4	24.8	22.0	23.4	22.4	23.8	24.2
	8H	23.1	24.4	23.5	24.7	25.1	22.3	23.6	22.7	24.0	24.4
	12H	23.5	24.7	23.9	25.1	25.5	22.4	23.7	22.8	24.0	24.5
4H	2H	19.8	21.4	20.2	21.7	22.1	19.9	21.4	20.3	21.7	22.1
	3H	21.9	23.2	22.3	23.6	24.0	21.7	23.0	22.2	23.4	23.8
	4H	22.9	24.1	23.3	24.5	24.9	22.6	23.7	23.0	24.1	24.6
	6H	23.9	24.9	24.4	25.4	25.8	23.2	24.3	23.7	24.7	25.2
	8H	24.4	25.4	24.9	25.8	26.3	23.5	24.4	23.9	24.9	25.4
	12H	24.9	25.8	25.4	26.2	26.7	23.7	24.5	24.2	25.0	25.5
8H	4H	23.3	24.2	23.7	24.7	25.2	23.0	24.0	23.5	24.4	24.9
	6H	24.5	25.3	25.0	25.8	26.3	23.8	24.6	24.3	25.1	25.6
	8H	25.1	25.8	25.6	26.3	26.8	24.2	24.9	24.7	25.4	25.9
	12H	25.8	26.4	26.3	26.9	27.4	24.4	25.1	24.9	25.6	26.1
12H	4H	23.3	24.2	23.8	24.7	25.2	23.1	24.0	23.6	24.4	24.9
	6H	24.6	25.3	25.1	25.8	26.3	24.0	24.7	24.5	25.2	25.7
	8H	25.3	25.9	25.8	26.4	27.0	24.4	25.0	24.9	25.5	26.0

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1133 B = 148	H(C0) = 30 H(C90) = 0	H(C180) = 30 H(C270) = 0
C-planes	γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
			Luminance in cd/m²					
45°		7288.1	7308.5	7369.2	7478.9	7658.7	7924.8	8315.7
50°		7085.1	7103.8	7164.5	7276.8	7465.3	7758.9	8208.6
55°		6858.6	6877.5	6935.4	7045.5	7241.5	7558.6	8072.6
60°		6609.0	6627.5	6676.6	6778.9	6972.6	7311.0	7897.7
65°		6341.2	6352.4	6386.6	6473.4	6657.4	7010.5	7679.7
70°		6119.7	6114.5	6089.6	6120.4	6268.1	6616.6	7378.5
75°		5985.3	5962.2	5878.5	5784.8	5804.9	6122.7	7012.7
80°		5993.4	5949.7	5804.9	5597.3	5366.6	5462.1	6512.6
85°		6246.0	6189.6	6001.2	5677.8	5201.9	4691.5	5811.9

Photometric test report

Family
Silhouette® 21

Order number: 51LN12NKM40A
EAN: 4069025398239

LP number
59582_28

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Silhouette® 21	Order number: 51LN12NKM40A EAN: 4069025398239	LP number 59582_28
Multilumen Table	environmental temperature: 25°C	siteco

DIP-Step	Switch Setting				Luminous flux [lm]	Power consumption [W]
	1	2	3	4		
8	OFF	OFF	OFF	ON	2870	19.7
6	OFF	ON	ON	OFF	3630	24.8
4	OFF	OFF	ON	OFF	4260	29.3
2	OFF	ON	OFF	OFF	4910	34.0
0	OFF	OFF	OFF	OFF	5580	39.1