

Photometric test report

Family
Apollon® 31

Order number: 51MP11HD2443
EAN: 4069025542823

LP number
59818_206

serial
documentation
02.07.2026

siteco


Version recessed luminaire for lay-in mounting, square M625, wide distribution, UGR≤19
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG-DALI-Multilumen
Rated values Net luminous flux = 5800 lm
Power consumption = 41.8 W
Luminous efficacy = 138.8 lm/W

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 516 cd/klm



Classifications

DIN 5040 A 5 0
CIE N1=66 N2=91 N3=97
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Apollon® 31	Order number: 51MP11HD2443 EAN: 4069025542823	LP number 59818_206
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	516.0	516.0	516.0	516.0	516.0	516.0	516.0	3.1	3.1
5°	513.4	513.4	513.6	513.4	513.9	513.6	513.5	24.5	27.6
10°	505.3	505.3	505.6	505.3	505.7	505.3	505.4	48.1	75.7
15°	492.1	492.0	492.0	491.8	492.0	491.7	491.3	69.8	145.5
20°	474.4	474.2	473.9	473.5	473.9	473.8	473.7	88.8	234.4
25°	452.4	452.9	452.9	451.7	452.0	452.8	453.3	104.8	339.2
30°	426.0	426.7	426.7	424.4	424.8	426.0	427.3	116.7	455.9
35°	386.2	386.6	387.0	382.5	382.5	384.2	386.1	121.0	576.9
40°	306.7	305.0	301.7	300.2	301.5	298.7	296.8	106.2	683.1
45°	251.7	228.7	212.0	224.1	237.2	214.4	198.2	86.7	769.8
50°	202.6	172.2	139.6	166.0	189.8	152.6	126.0	68.9	838.7
55°	152.2	114.4	83.4	112.2	145.8	97.1	74.5	49.9	888.5
60°	103.3	69.1	47.6	69.2	105.6	58.8	43.1	33.5	922.0
65°	71.5	44.6	28.0	45.9	71.7	40.4	27.2	23.2	945.2
70°	46.4	39.5	24.6	40.3	46.2	37.1	25.1	19.2	964.4
75°	26.4	35.4	24.1	35.0	24.6	35.6	25.0	15.9	980.3
80°	19.1	24.0	22.5	23.8	21.7	25.4	23.2	12.5	992.8
85°	13.5	12.5	12.3	12.2	14.2	13.2	12.9	7.1	999.8
90°	0.4	0.4	0.3	0.3	0.2	0.3	0.3	0.2	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Apollon® 31			Order number: 51MP11HD2443 EAN: 4069025542823							LP number 59818_206	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	16.4	17.9	16.8	18.2	18.5	16.2	17.7	16.6	18.0	18.4
	3H	17.0	18.4	17.4	18.7	19.1	16.6	17.9	17.0	18.3	18.6
	4H	17.4	18.7	17.8	19.0	19.4	16.9	18.2	17.3	18.5	18.9
	6H	17.7	18.9	18.1	19.2	19.6	17.4	18.5	17.8	18.9	19.3
	8H	17.9	19.0	18.4	19.3	19.8	17.7	18.7	18.1	19.1	19.5
	12H	18.1	19.1	18.5	19.5	19.9	17.9	18.9	18.3	19.2	19.7
4H	2H	16.6	17.9	17.0	18.2	18.6	16.5	17.7	16.9	18.1	18.5
	3H	17.3	18.4	17.7	18.8	19.2	17.2	18.2	17.6	18.6	19.0
	4H	17.8	18.8	18.3	19.2	19.6	17.6	18.6	18.1	19.0	19.4
	6H	18.4	19.2	18.8	19.6	20.1	18.3	19.1	18.8	19.6	20.0
	8H	18.6	19.4	19.1	19.8	20.3	18.6	19.4	19.1	19.8	20.3
	12H	18.9	19.6	19.4	20.0	20.5	18.9	19.6	19.4	20.0	20.5
8H	4H	18.1	18.8	18.5	19.2	19.7	17.9	18.6	18.3	19.0	19.5
	6H	18.8	19.4	19.3	19.8	20.4	18.7	19.3	19.2	19.8	20.3
	8H	19.1	19.7	19.6	20.2	20.7	19.1	19.7	19.6	20.1	20.7
	12H	19.5	20.0	20.0	20.5	21.0	19.5	20.0	20.1	20.5	21.0
12H	4H	18.1	18.7	18.6	19.2	19.7	17.9	18.6	18.4	19.0	19.5
	6H	18.9	19.4	19.4	19.9	20.4	18.8	19.3	19.3	19.8	20.3
	8H	19.3	19.7	19.8	20.2	20.8	19.3	19.7	19.8	20.2	20.8

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 555 B = 555	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	6703.8	6089.4	5645.8	5968.7	6317.2	5709.8	5278.7
50°	5936.2	5045.5	4088.3	4861.4	5559.5	4471.0	3691.8
55°	4997.6	3755.1	2738.6	3683.8	4784.8	3188.0	2446.9
60°	3888.9	2600.7	1793.7	2606.6	3975.4	2214.9	1623.0
65°	3186.8	1986.5	1246.0	2043.8	3192.7	1801.3	1213.0
70°	2555.3	2175.3	1355.3	2216.4	2544.6	2042.3	1384.6
75°	1920.9	2574.3	1756.2	2547.5	1787.5	2592.4	1819.9
80°	2072.2	2607.1	2440.5	2585.0	2350.7	2749.7	2517.2
85°	2910.8	2694.7	2666.7	2642.5	3060.5	2849.6	2797.1

Photometric test report

Family
Apollon® 31

Order number: 51MP11HD2443
EAN: 4069025542823

LP number
59818_206

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family
Apollon® 31

Order number: 51MP11HD2443
EAN: 4069025542823

LP number
59818_206

Multilumen Table

environmental temperature: 25°C

sITeco

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]
	1	2	3		
7	ON	ON	ON	5800	41.8
6	ON	ON	OFF	5640	39.6
5	ON	OFF	ON	5380	37.5
4	ON	OFF	OFF	5110	35.3
3	OFF	ON	ON	4840	33.2
2	OFF	ON	OFF	4570	31.1
1	OFF	OFF	ON	4300	29.1
0	OFF	OFF	OFF	4000	27.1