

Order No.: 5EA40ELC01 | GTIN (EAN): 4058352641347

Product description: SConWi,SmartPlugCelMotLow



SITECO Connect WirelessSmart Plug Cellular Motion Low, sensor, communication: local mesh radio network, EGPRS, NB-IoT NB2, LTE Cat M1, 5G, 4G, 2G, 2.4GHz, D4i type A, control: remote setup and operation, local setting and operation with USB stick, local setting and operation with smartphone app, manual, by time, by timer, by weekday, by AstroDim calendar, by daylight, by movement, via API, with radio clock, optionally via radio push button, sensor technology: 1 PIR movement sensor, daylight sensor, temperature sensor, inclination sensor, GPS, GNSS, GLONASS, GALILEO, The usage fees for remote access via web application and mobile communications (LTE CAT M1 / NB IoT NB2 / EGPRS) are included in the scope of delivery with a term of 5 years. This individually extendable runtime starts when the device QR code is scanned into a system, Smart Interface below, Logarithmic DALI dimming curve preset. Can be switched to linear via software, installation type: screw fastening, installation location: to the luminaire, of plastic, voltage: 24V, voltage type: DC, PIR movement sensor, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 CE

Wt. (kg): 0.1
GTIN (EAN): 4058352641347

Order No.: 5EA40ELC01 | GTIN (EAN): 4058352641347

Detailed technical description: SConWi,SmartPlugCelMotLow



Key data

- System family: SITECO Connect 31 Wireless
- Product type: sensor
- Product name: SITECO Connect Wireless
- Order No.: 5EA40ELC01

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: D4i, Smart Interface below, The usage fees for remote access via web application and mobile communications (LTE CAT M1 / NB IoT NB2 / EGPRS) are included in the scope of delivery with a term of 5 years. This individually extendable runtime starts when the device QR code is scanned into a system, Logarithmic DALI dimming curve preset. Can be switched to linear via software

Certificates, Standards

- Protection rating: IP66
- Temperature range (operation): -40..+85°C
- Standard: according to Zhaga book 18
- Certification, designation: CE

Material, Colour

- housing: plastic, transparent, colour-backed, transparent
- Colour specification: transparent

Mounting

- Mounting method, mounting location: screw fastening, to the luminaire
- Mounting height: 0..6m

Electrical connection

- Nominal voltage: 24V, DC

Dimensions, Weight

- Weight: 0.1kg

Inputs

PIR movement sensor


- Detection range: max. ø11m

Order No.: 5EA40ELC01 | GTIN (EAN): 4058352641347


Dimensions: SConWi,SmartPlugCelMotLow

Detection zone "Smart Plug Cellular Motion Low"
5EA40ELC01

Side view



Top view



Mounting height	X axis	Y axis
5.0 m	8.5 m	8.8 m
6.0 m	10.2 m	10.6 m

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -