

**Order No.:** 56TL6M | **GTIN (EAN):** 4058352401286

**Product description:** Lic,multiadapter,sh.steel,sr



Licross®, rail insert, adapter,with plug, 5-pole, with phase selection, mains connection: 230V, AC, 50/60Hz, terminal,5-pole, max. 2.5mm<sup>2</sup>, multi adapter, of sheet steel, coil coated, metallic grey (RAL 9006), for IP20/IP40 protection rating, length: 500mm, width: 64mm, height: 68mm, multifunctional insert, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, UKCA, packaging unit: 1 piece

IP 20  

Wt. (kg): 0.4  
GTIN (EAN): 4058352401286

Order No.: 56TL6M | GTIN (EAN): 4058352401286

Detailed technical description: Lic,multiadapter,sh.steel,sr



#### Key data

- System family: Licross®
- Product type: rail insert
- Product name: Licross®
- Order No.: 56TL6M

#### Lighting technology | Lamps | Control gear

#### Component 1

#### Lamps:

- Supplement: internal wiring halogen-free, for trunking rail, 7..14-core, max. 0.5A

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE, UKCA

#### Material, Colour

- multi adapter: sheet steel, coil coated, metallic grey (RAL 9006), for IP20/IP40 protection rating
- Colour specification: metallic grey (RAL 9006)

#### Mounting

- Supplement: only suitable for use in indoor areas

#### Electrical connection

- Connection: plug, 5-pole, with phase selection
- Nominal voltage: 230V, 50/60Hz, AC

#### Dimensions, Weight

- Length: 500mm
- Width: 64mm
- Height: 68mm
- Weight: 0.4kg