

Order No.: 56TL1TA | **GTIN (EAN):** 4058352406731

Product description: Lic,el.ad,sh.steel,wh



Licross®, rail insert, adapter, with plug, 6-pole, with phase selection, mains connection: 230V, AC, 50/60Hz, terminal, 5-pole, max. 2.5mm², electrical adapter, of sheet steel, coil coated, white, for IP20/IP40 protection rating, inclusive M4 fixing screw, length: 210mm, width: 64mm, height: 68mm, multifunctional insert, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, UKCA, packaging unit: 1 piece

IP 20  

Wt. (kg): 0.3
GTIN (EAN): 4058352406731

Order No.: 56TL1TA | GTIN (EAN): 4058352406731

Detailed technical description: Lic,el.ad,sh.steel,wh



Key data

- System family: Licross®
- Product type: rail insert
- Product name: Licross®
- Order No.: 56TL1TA

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Supplement: internal wiring halogen-free, for trunking rail, 7..14-core, max. 0.5A

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE, UKCA

Material, Colour

- electrical adapter: sheet steel, coil coated, white, for IP20/IP40 protection rating, inclusive M4 fixing screw
- Colour specification: white

Mounting

- Mounting height: object related (mounting location without light from other sources)
- Supplement: only suitable for use in indoor areas

Electrical connection

- Connection: plug, 6-pole, with phase selection
- Nominal voltage: 230V, 50/60Hz, AC

Dimensions, Weight

- Length: 210mm
- Width: 64mm
- Height: 68mm
- Weight: 0.3kg