

Order No.: 56TL1M | GTIN (EAN): 4058352400609 Product description: Lic,multiadapter,sh.steel,wh



Licross®, rail insert, adapter,with plug, 5-pole, with phase selection, mains connection: 230V, AC, 50/60Hz, terminal,5-pole, max. 2.5mm², multi adapter, of sheet steel, coil coated, white, for IP20/IP40 protection rating, length: 500mm, width: 64mm, height: 68mm, multifunctional insert, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, UKCA, packaging unit: 1 piece

IP 20 ⊕ (∈

Wt. (kg): 0.4

GTIN (EAN): 4058352400609



Order No.: 56TL1M | GTIN (EAN): 4058352400609

Detailed technical description: Lic, multiadapter, sh. steel, wh



Key data

System family: Licross®
Product type: rail insert
Product name: Licross®
Order No.: 56TL1M

Lighting technology | Lamps | Control gear

Component 1

Lamps:

 Supplement: internal wiring halogenfree, for trunking rail, 7..14-core, max. 0.5A

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE, UKCA

Material, Colour

- multi adapter: sheet steel, coil coated, white, for IP20/IP40 protection rating
- Colour specification: white

Mounting

 Supplement: only suitable for use in indoor areas

Electrical connection

- Connection: plug, 5-pole, with phase selection
- Nominal voltage: 230V, 50/60Hz, AC

Dimensions, Weight

Length: 500mmWidth: 64mmHeight: 68mmWeight: 0.4kg