

Order No.: 5LZ930303 | GTIN (EAN): 4058352386033


Product description: SCon11,psh.bttm.interf,centCtrl



SITECO Connect 11 push button interface, central control, installation type: recessed, installation location: in the switch box, of plastic, protection rating (complete): IP20, insulation class (complete): insulation class III (safety extra-low voltage), certification: CE, 4 x push button input, 4 x push button input, 1 x DALI-2, 1 x LED green, packaging unit: 1 piece

IP 20  

Wt. (kg): 0.1
GTIN (EAN): 4058352386033



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 29.09.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 5LZ930303 | GTIN (EAN): 4058352386033

Detailed technical description: SCon11,psh.bttm.interf,centCtrl



Key data

- System family: Siteco Connect 11
- Product type: lighting management components
- Product name: SITECO Connect 11
- Order No.: 5LZ930303

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class III (safety extra-low voltage)
- Temperature range (operation): -20..+75°C
- Certification, designation: CE

Material, Colour

- adapter: plastic, grey
- housing: plastic, grey
- Colour specification: grey

Mounting

- Mounting method, mounting location: recessed, in the switch box
- Supplement: only suitable for indoor use

Dimensions, Weight

- Weight: 0.1kg

Inputs

4x push button input

- Feature: zero-potential, cable length max. 0.5m

Outputs

1x LED green

- Feature: for displaying initialization

Order No.: 5LZ930303 | GTIN (EAN): 4058352386033

Dimensions: SCon11,psh.btn.interf,centCtrl

