

## Order No.: 59HL94002 | GTIN (EAN): 4058352379349 Product description: HB11basemod,surf



Highbay 11Interface S, slave, local control - self-sufficient standalone sensors, central control - connection to lighting or building management, dimmable, installation type: surface-mounted, installation location: to the luminaire, of plastic, protection rating (complete): IP54, insulation class (complete): insulation class II (safety insulation), certification: CE, 1 x 1 x DALI-2, packaging unit: 1 piece

IP 54 🔲 🤆

Wt. (kg): 0.3 GTIN (EAN): 4058352379349

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 27.06.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

# siteco

### Order No.: 59HL94002 | GTIN (EAN): 4058352379349 Detailed technical description: HB11basemod,surf



#### Key data

- System family: Siteco Connect 11, SITECO Connect 22
- Product type: base module
- Product name: Highbay 11
- Order No.: 59HL94002

# Lighting technology | Lamps | Control gear

#### **Component 1**

#### **Operating device:**

- Control: DALI 2, dimmable

#### **Certificates, Standards**

- Protection rating: IP54
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): -20..+50°C
- Certification, designation: CE

#### Material, Colour

- housing: plastic, white, square
- Colour specification: white
- mounting bracket: steel, galvanised

#### Mounting

- Mounting method, mounting location: surface-mounted, to the luminaire
- Supplement: only suitable for use in indoor areas

#### Dimensions, Weight

- Length: 83mm
- Width: 83mm
- Height: 28mm
- Weight: 0.3kg

#### Outputs

- 1x DALI-2
- Feature: DALI, slave function, DALI current max. 6mA