

Order No.: 59HL94001 | GTIN (EAN): 4058352379325 Product description: HB11basemod, surf



Highbay 11Interface MD, master, local control, dimmable, installation type: surface-mounted, installation location: to the luminaire, of plastic, protection rating (complete): IP54, insulation class (complete): insulation class II (safety insulation), certification: CE, voltage: 230V, voltage type: AC, 1 x DALI, packaging unit: 1 piece

IP 54 🔲 🤆

Wt. (kg): 0.3 GTIN (EAN):

4058352379325

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 05.01.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -

siteco

Order No.: 59HL94001 | GTIN (EAN): 4058352379325 Detailed technical description: HB11basemod,surf



Key data

- Product type: base module
- Product name: Highbay 11
- Order No.: 59HL94001

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: DALI, dimmable

Certificates, Standards

- Protection rating: IP54
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): -20..+50°C
- Certification, designation: CE

Material, Colour

- housing: plastic, white, square
- Colour specification: white
- mounting bracket: steel, galvanised

Mounting

- Mounting method, mounting location:
- surface-mounted, to the luminaire
- Supplement: only for mounting indoors

Electrical connection

- Nominal voltage: 230V, 50Hz, AC

Dimensions, Weight

- Length: 83mm
- Width: 83mm
- Height: 28mm
- Weight: 0.3kg

Outputs

1x DALI

- Connection: screw terminal, 2-pole, max. 4mm²
- Feature: DALI, master function, broadcast addressing, max. 30 DALI ECGs