

Order No.: 5EA40EHC01 | GTIN (EAN): 4058352641323

Product description: SConWi,SmartPlugCelMotHigh





SITECO Connect WirelessSmart Plug Cellular Motion High, Smart Interface below, installation type: screw fastening, installation location: to the luminaire, of plastic, voltage: 24V, voltage type: DC, D4i, local mesh radio network, EGPRS, NB-IoT NB2, LTE Cat M1, 5G, 4G, 2G, 2.4GHz, remote setup and operation, local setting and operation with USB stick, local setting and operation with smartphone app, manual, by time, by timer, by weekday, by AstroDim calendar, by daylight, by movement, via API, with radio clock, optionally via radio push button, 1 PIR movement sensor, daylight sensor, temperature sensor, inclination sensor, GPS, GNSS, GLONASS, GALILEO, PIR movement sensor, brightness sensor, radio, 2.4GHz, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 (€

Wt. (kg): 0.1

GTIN (EAN): 4058352641323



Order No.: 5EA40EHC01 | GTIN (EAN): 4058352641323

# Detailed technical description: SConWi,SmartPlugCelMotHigh



# Key data

- Product type: sensor

 Product name: SITECO Connect Wireless

Order No.: 5EA40EHC01

# Lighting technology | Lamps | Control gear

# **Component 1**

## Operating device:

- Control: D4i, Smart Interface below

#### Certificates, Standards

- Protection rating: IP66
- Temperature range (operation): -40..+85°C
- Standard: according to Zhaga book 18
- Certification, designation: CE

# Material, Colour

- housing: plastic, transparent, colourbacked, dark grey
- Colour specification: dark grey

# Mounting

- Mounting method, mounting location: screw fastening, to the luminaire
- Mounting height: 6..12m

## **Electrical connection**

Nominal voltage: 24V, DC

# **Dimensions, Weight**

- Weight: 0.1kg

#### Inputs

# PIR movement sensor

- Detection range: D max. 18m



Order No.: 5EA40EHC

Dimensions: SConWi,Sm.

Mounting height	X axis	Y axis
7.0 m	11.9 m	12.4 m
8.0 m	13.6 m	14.2 m
9.0 m	15.3 m	15.9 m
10.0 m	17.0 m	17.7 m