


**Order No.:** 51FP209P460H | **GTIN (EAN):** 4058352389294


**Product description:** Mon11,wd,5490lm840,0/1,PC



Monsun 11, damp-proof luminaire, chain hanger, primary optical cover: enclosure, of PC, light emission: direct distribution, primary light characteristic: symmetric, installation type: suspended mounting, surface-mounted, horizontal mounting, vertical mounting, LED, rated luminous flux: 5.490lm, luminous efficacy: 161lm/W, light colour: 840, colour temperature: 4000K, control gear: ON/OFF, with terminal, 3-pole, max. 2.5mm<sup>2</sup>, mains connection: 220..240V, AC, 50/60Hz, rated input power: 34W, luminaire housing, of glass-fibre reinforced polyester, uncoated, bright grey, incl. chain hanger, length: 1.590mm, width: 90mm, height: 88mm, clip for enclosure, of stainless steel (V2A), ceiling mounting element, of stainless steel (V2A), chain hanger, of stainless steel (V2A), protection rating (complete): IP66, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, VDE, UKCA, protection symbol: D, impact resistance: IK08, permissible operating ambient temperature: -35..+40°C, standard: EN 50419, EN 60598-2-1, no direct snow, no direct sun, no direct rain, for indoor or canopied outdoor use, corresponds to IFS (International Featured Standards) requirements for safety and quality in the food industry, contact your sales advisor before using the luminaires in applications with unclear chemical exposure, large temperature fluctuations or condensation-forming humidity, LABS conformity tested according to VDMA 24364:2018-05, packaging unit: 1 piece



Lamps: LED  
 Wt. (kg): 2.5  
 GTIN (EAN): 4058352389294



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))  
 Tolerances related to thermal, electrical and photometric data according to IEC 62722  
 Issued 16.01.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 51FP209P460H | GTIN (EAN): 4058352389294

**Detailed technical description:** Mon11,wd,5490lm840,0/1,PC



#### Key data

- Product type: damp-proof luminaire
- Product name: Monsun 11
- Order No.: 51FP209P460H

#### Lighting technology | Lamps | Control gear

##### Component 1

###### Lighting technology:

- Cover: enclosure
- Beam angle: wide distribution
- Symmetry: symmetric
- Light emission: direct distribution

###### Lamps:

- Lamps: with LED
- Rated luminous flux: 5490lm
- Luminous efficacy: 161lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 80
- Light colour: 840
- SDCM (Standard Deviation of Colour Matching): MacAdam  $\leq$  3 SDCM (initial)
- Rated input power: 34W
- Supplement: internal wiring halogen-free, without flicker

###### Operating device:

- Control: ON/OFF

#### Certificates, Standards

- Protection rating: IP66
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK08
- Protection symbol: D
- Temperature range (operation): -35..+40°C
- Supplement: corresponds to IFS (International Featured Standards) requirements for safety and quality in the food industry, for indoor or canopied outdoor use, no direct snow, no direct sun, no direct rain, LABS conformity tested according to VDMA 24364:2018-05, contact your sales advisor before using the luminaires in applications with unclear chemical exposure, large temperature fluctuations or condensation-forming humidity
- Standard: EN 50419, EN 60598-2-1
- Certification, designation: CE, ENEC, VDE, UKCA

#### Material, Colour

- luminaire housing: glass-fibre reinforced polyester, uncoated, bright grey, incl. chain hanger
- Colour specification: bright grey
- clip for enclosure: stainless steel (V2A)
- Quantity: 10 piece
- ceiling mounting element: stainless steel (V2A), ceiling mounting included
- Quantity: 2 piece
- chain hanger: stainless steel (V2A)
- Quantity: 2 piece
- Cover: enclosure of PC

#### Mounting

- Mounting method, mounting location: suspended mounting, surface-mounted, horizontal mounting, vertical mounting, to the ceiling, to the wall, to the Licross mounting rail
- Arrangement: single/continuous arrangement
- Supplement: luminaire includes fixing accessories for ceiling surface mounting; for other types of installation: please order mounting accessories separately

**Order No.:** 51FP209P460H | **GTIN (EAN):** 4058352389294

**Detailed technical description:** Mon11,wd,5490lm840,0/1,PC



#### **Electrical connection**

- Connection: terminal, 3-pole, max. 2.5mm<sup>2</sup>
- Nominal voltage: 220..240V, 50/60Hz, AC

#### **Dimensions, Weight**

- Length: 1590mm
- Width: 90mm
- Height: 88mm
- Weight: 2.5kg


#### **Service life**

- Rated service life: 50000h (L90) at AT = 25°C, 70000h (L80) at AT = 35°C

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))  
Tolerances related to thermal, electrical and photometric data according to IEC 62722  
Issued 16.01.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -

**Order No.:** 51FP209P460H | **GTIN (EAN):** 4058352389294

**Dimensions:** Mon11,wd,5490lm840,0/1,PC



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))  
Tolerances related to thermal, electrical and photometric data according to IEC 62722  
Issued 16.01.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -


**Order No.:** 51FP209P460H | **GTIN (EAN):** 4058352389294

**Planning data:** Mon11,wd,5490lm840,0/1,PC

## 51FP209P460H: 1x LED

4058352389294

51FP209P460H



$\phi_{\downarrow}$  94%    $\phi_{\uparrow}$  6%

Luminance values (cd/m<sup>2</sup>)

	C 0/180	C 90/270
L <sub>80</sub>	6698	6474
L <sub>70</sub>	7814	8754
L <sub>65</sub>	8236	9383

UGR 25      23.8  
 X 4H Y 8H p 70/50/20 S 0.25H

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))  
 Tolerances related to thermal, electrical and photometric data according to IEC 62722  
 Issued 16.01.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -