

**Order No.:** 5EA40RC01 | **GTIN (EAN):** 4058352493618

**Product description:** SConWi,SmartPlugMotionRadar



SITECO Connect WirelessSmart Plug Motion Radar, sensor, communication: 2.4GHz, local mesh radio network, D4i type A, control: local setting and operation with USB stick, by movement, manual, by time, by timer, by weekday, optionally via radio push button, sensor technology: 2 radar movement sensors, Smart Interface below, Logarithmic DALI dimming curve preset. Can be switched to linear via software, installation type: screw fastening, installation location: to the luminaire, of plastic, voltage: 24V, voltage type: DC, radar movement sensor, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 IK 09 CE

Wt. (kg): 0.1  
GTIN (EAN): 4058352493618

**Order No.:** 5EA40RC01 | **GTIN (EAN):** 4058352493618

**Detailed technical description:** SConWi,SmartPlugMotionRadar



## Key data

- System family: SITECO Connect 31 Wireless
- Product type: sensor
- Product name: SITECO Connect Wireless
- Order No.: 5EA40RC01

## Lighting technology | Lamps | Control gear

### Component 1

#### Operating device:

- Control: D4i, Smart Interface below, Logarithmic DALI dimming curve preset. Can be switched to linear via software

#### Certificates, Standards

- Protection rating: IP66
- Impact resistance: IK09
- Temperature range (operation): -20...+60°C
- Standard: according to Zhaga book 18
- Certification, designation: CE

#### Material, Colour

- housing: plastic, transparent, colour-backed, transparent
- Colour specification: transparent

#### Mounting

- Mounting method, mounting location: screw fastening, to the luminaire
- Mounting height: 3..8m

#### Electrical connection

- Nominal voltage: 24V, DC

#### Dimensions, Weight

- Diameter: 80mm
- Height: 63mm
- Weight: 0.1kg

#### Inputs

#### radar movement sensor


- Detection range: max. 70x20m

Order No.: 5EA40RC01 | GTIN (EAN): 4058352493618


Dimensions: SConWi,SmartPlugMotionRadar

Detection zone "Smart Plug Motion Radar"  
5EA40RC01

Side view



Top view



| Mounting height 5m | X axis | Y axis |
|--------------------|--------|--------|
| Vehicles           | 70.0 m | 15.0 m |
| People             | 25.0 m | 10.0 m |

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -