

Order No.: 56TL1FCSA | GTIN (EAN): 4058352373880

Product description: LicIntsens




Licross® InterfaceInterface S, slave, local control - self-sufficient standalone sensors, central control - connection to lighting or building management, dimmable, installation location: to the Licross® trunking rail, of sheet steel, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, VDE, UKCA, 1 x DALI-2, packaging unit: 1 piece



Wt. (kg): 0.8

GTIN (EAN): 4058352373880





Order No.: 56TL1FCSA | GTIN (EAN): 4058352373880

Detailed technical description: LicIntsens



Key data

- System family: Siteco Connect 11, SITECO Connect 21
- Product type: sensor
- Product name: Licross® Interface
- Order No.: 56TL1FCSA

Lighting technology | Lamps | Control gear

Component 1

Lamps:

 Supplement: internal wiring halogenfree

Operating device:

- Control: DALI 2, dimmable

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): -20..+50°C
- Certification, designation: CE, ENEC, VDE, UKCA

Material, Colour

- trunking rail adapter set: sheet steel, coil coated, white
- Colour specification: white

Mounting

 Supplement: only suitable for use in indoor areas

Electrical connection

Connection: plug, 5-pole, with phase selection

Dimensions, Weight

Length: 500mmWidth: 96mmHeight: 97mmWeight: 0.8kg

Outputs

DALI-2

 Feature: DALI, slave function, DALI current max. 6mA



Order No.: 56TL1FCSA | **GTIN (EAN):** 4058352373880

Dimensions: LicIntsens

