

Order No.: 5DTAXTSCF62003 | **GTIN (EAN):** 4050737913544

Product description: AXT,3ph-tr,rec,wh,L2000,DA



AX T, 3-phase track, installation type: recessed, control gear: DALI, mains connection: 220..240V/380..400V, AC, of extruded aluminium section, coated, white, can be cut to preference, length: 2.000mm, width: 32mm, height: 33mm, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, packaging unit: 1 piece

 IP 20  

Wt. (kg): 2.0
GTIN (EAN): 4050737913544

Order No.: 5DTAXTSCF62003 | GTIN (EAN): 4050737913544

Detailed technical description: AXT,3ph-tr,rec,wh,L2000,DA



Key data

- Product type: 3-phase track
- Product name: AX T
- Order No.: 5DTAXTSCF62003

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Supplement: max. 16A

Operating device:

- Control: DALI

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE, ENEC

Mounting

- Mounting method, mounting location: recessed, in the ceiling

Electrical connection

- Nominal voltage: 220..240V/380..400V, AC

Dimensions, Weight

- Length: 2000mm
- Width: 32mm
- Height: 33mm
- Weight: 2.0kg