

Order No.: 5LS59000C | **GTIN (EAN):** 4050737600352

Product description: Mon11X,rail-ins,DALI



Monsun 11 Extreme, rail insert, luminaire mounting insert, with luminaire system connector: socket, 5-pole; for Modario trunking rail, 10-core, mains connection: 220..240V, AC/DC, 0/50..60Hz, end cap, of PC, white, length: 1.495mm, width: 48mm, luminaire mounting insert, of sheet steel, galvanised, coated, pure white, protection rating (complete): IP64, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, VDE, UKCA, protection symbol: D, packaging unit: 1 piece



Wt. (kg): 0.7
GTIN (EAN): 4050737600352

Order No.: 5LS59000C | **GTIN (EAN):** 4050737600352

Detailed technical description: Mon11X,rail-ins,DALI



Key data

- Product type: rail insert
- Product name: Monsun 11 Extreme
- Order No.: 5LS59000C

Lighting technology | Lamps | Control gear

Component 2

Lamps:

- Supplement: for ECG DALI, dimming operation

Certificates, Standards

- Protection rating: IP64
- Insulation class: insulation class I (protective earthing)
- Protection symbol: D
- Certification, designation: CE, ENEC, VDE, UKCA

Material, Colour

- end cap: PC, white
- luminaire mounting insert: sheet steel, galvanised, coated, pure white

Electrical connection

- Connection: luminaire system
connector: socket, 5-pole; for Modario trunking rail, 10-core
- Nominal voltage: 220..240V, 0/50..60Hz, AC/DC

Dimensions, Weight

- System units: 5x SE
- Length: 1495mm
- Width: 48mm
- Weight: 0.7kg