

Order No.: 5LS591030 | **GTIN (EAN):** 4050737712284

Product description: Mon11Xbatt.box,batt.box,emerg.lght.elem



Monsun 11 Extreme, battery box, battery box, installation type: surface-mounted, with system connector: plug/socket, 2-pole, control gear: emergency light element, battery: NiMH, 4Ah, mains connection: 6V, DC, fixing bracket, of stainless steel (V2A), grey, battery box, rectangular, of PC, grey, protection rating (complete): IP66, insulation class (complete): insulation class I (protective earthing), certification: CE, UKCA, permissible operating ambient temperature: +5..+40°C, standard: EN 60598-2-22, packaging unit: 1 piece

IP 66  CE

Wt. (kg): 0.9
GTIN (EAN): 4050737712284

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 30.10.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 5LS591030 | GTIN (EAN): 4050737712284

Detailed technical description: Mon11Xbatt.box,batt.box,emerg.light.elem



Key data

- Product type: battery box
- Product name: Monsun 11 Extreme
- Order No.: 5LS591030

Lighting technology | Lamps | Control gear

Component 2

Lamps:

- Supplement: for emergency light function, suitable for emergency light operating devices according to EN 60598-2-22, battery NiMH 4Ah 6V(DC)

Operating device:

- Control gear: emergency light element
- Battery: NiMH
- Nominal operating time: 3h

Certificates, Standards

- Protection rating: IP66
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): +5...+40°C
- Standard: EN 60598-2-22
- Certification, designation: CE, UKCA

Material, Colour

- fixing bracket: stainless steel (V2A), grey
- Colour specification: grey
- battery box: PC, grey, rectangular
- Colour specification: grey

Mounting

- Mounting method, mounting location: surface-mounted, to the luminaire
- Arrangement: single arrangement

Electrical connection

- Connection: system connector: plug/socket, 2-pole

Dimensions, Weight

- Weight: 0.9kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 30.10.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -