


Order No.: 5TR36TDS | **GTIN (EAN):** 4058352139257

Product description: Mod,track-ad-ins,DA,sr,4su




Modario®, track adapter insert, control gear: DALI, with plug, 5-pole, with phase selection, for trunking rail, 10-core, mains connection: 230/400V, track adapter insert, of sheet steel, coil coated, metallic grey (RAL 9006), 4x system unit, max. weight load 5kg, length: 1.196mm, width: 48mm, protection rating (complete): for IP20 protection rating, insulation class (complete): insulation class I (protective earthing), certification: CE, packaging unit: 1 piece



Wt. (kg): 1.7
GTIN (EAN): 4058352139257

Order No.: 5TR36TDS | **GTIN (EAN):** 4058352139257

Detailed technical description: Mod,track-ad-ins,DA,sr,4su



Key data

- Product type: track adapter insert
- Product name: Modario®
- Order No.: 5TR36TDS

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Supplement: max. current consumption 6A

Operating device:

- Control: DALI

Certificates, Standards

- Protection rating: for IP20 protection rating
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE

Material, Colour

- track adapter insert: sheet steel, coil coated, metallic grey (RAL 9006), 4x system unit, max. weight load 5kg
- Colour specification: metallic grey (RAL 9006)

Electrical connection

- Connection: plug, 5-pole, with phase selection, for trunking rail, 10-core
- Nominal voltage: 230/400V

Dimensions, Weight

- System units: 4x SE
- Length: 1196mm
- Width: 48mm
- Weight: 1.7kg