

Order No.: 5XA7670C2A00C | **GTIN (EAN):** 4058352233559

Product description: FL20mn,LED-unit,PL43,740,96W



Floodlight FL 20 mini, LED unit, primary light control with lens, of plastic, primary optical cover: cover panel, of toughened safety glass, transparent, light distribution: PL43, light emission: direct distribution, primary light characteristic: asymmetric, installation type: screw fastening, LED, High Power LED, light colour: 740, colour temperature: 4000K, with cable with plug, mains connection: 220..240V, AC, 50/60Hz, rated input power: 96W, LED unit, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), length: 291 mm, width: 309mm, height: 51mm, protection rating (complete): IP66, packaging unit: 1 piece

IP 66

Lamps:	LED
Wt. (kg):	2.5
GTIN (EAN):	4058352233559

Order No.: 5XA7670C2A00C | GTIN (EAN): 4058352233559

Detailed technical description: FL20mn,LED-unit,PL43,740,96W



Key data

- Product type: LED unit
- Product name: Floodlight FL 20 mini
- Order No.: 5XA7670C2A00C

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: lens of plastic
- Cover: cover panel, transparent
- Light distribution: PL43
- Symmetry: asymmetric distribution
- Light emission: direct distribution

Lamps:

- Lamps: High Power LED, LED
- Colour temperature: 4000K
- Colour rendering index: CRI > 70
- Light colour: 740
- Rated input power: 96W

Certificates, Standards

- Protection rating: IP66

Material, Colour

- LED unit: diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S)
- Colour specification: Siteco® metallic grey (DB 702S)
- Cover: cover panel of toughened safety glass

Mounting

- Mounting method, mounting location: screw fastening, in housing

Electrical connection

- Connection: cable with plug
- Nominal voltage: 220..240V, 50/60Hz, AC
- Surge voltage resistance: 10kV 1.2/50µs

Dimensions, Weight

- Length: 291mm
- Width: 309mm
- Height: 51mm
- Weight: 2.5kg