siteco

Order No.: 5XA7681E0000C | **GTIN (EAN):** 4058352236505

Product description: FL20md,hous,Basic,208W,IC1

Floodlight FL 20 midi, housing, primary light characteristic: asymmetric, control gear: Basic, control: overheat protection, electronic power reduction, with terminal, 5-pole, max. 2.5mm², mains connection: 220..240V, AC, rated input power: 208W, housing frame, housing, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm, length: 654mm, width: 450mm, height: 76mm, ON/OFF, protection rating (complete): IP66, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, VDE, packaging unit: 1 piece

IP 66

Wt. (kg):	6.8
GTIN (EAN):	4058352236505

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 27.09.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com

siteco

Order No.: 5XA7681E0000C | **GTIN (EAN):** 4058352236505

Detailed technical description: FL20md,hous,Basic,208W,IC1

Key data
- Product type: housing
- Product name: Floodlight FL 20 midi
- Order No.: 5XA7681E0000C

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:
- Symmetry: asymmetric distribution

Lamps:
- Rated input power: 208W

Operating device:
- Control gear: ECG Basic
- Control: Basic
- Equipment: overheat protection
- Switching method: electronic power reduction

Certificates, Standards
- Protection rating: IP66
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE, ENEC, VDE

Material, Colour
- housing frame: diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm
- housing: diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm
- Colour specification: Siteco® metallic grey (DB 702S)

Electrical connection
- Connection: terminal, 5-pole, max. 2.5mm²
- Nominal voltage: 220..240V, AC

Dimensions, Weight
- Length: 654mm
- Width: 450mm
- Height: 76mm
- Weight: 6.8kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 27.09.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com