

Order No.: 59US1FCSA | **GTIN (EAN):** 4058352361948

Product description: SConbasemod,surf



SITECO ConnectExternal Interface S, slave, local control, central control, dimmable, installation type: surface-mounted, installation location: to the ceiling, to the luminaire, of plastic, protection rating (complete): IP54, insulation class (complete): insulation class II (safety insulation), certification: CE, VDE, 1 x packaging unit: 1 piece

 IP 54  

Wt. (kg): 0.1
GTIN (EAN): 4058352361948

Order No.: 59US1FCSA | GTIN (EAN): 4058352361948

Detailed technical description: SConbasemod,surf



Key data

- System family: Siteco Connect 11, SITECO Connect I/O, SITECO Connect 31 Wireless
- Product type: base module
- Product name: SITECO Connect
- Order No.: 59US1FCSA

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: DALI 2, dimmable

Certificates, Standards

- Protection rating: IP54
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): -20..+50°C
- Certification, designation: CE, VDE

Material, Colour

- housing: plastic, white, square
- Colour specification: white

Mounting

- Mounting method, mounting location: surface-mounted, to the ceiling, to the luminaire

Dimensions, Weight

- Length: 83mm
- Width: 83mm
- Height: 28mm
- Weight: 0.1kg