

**Order No.:** 59US1FCSA | **GTIN (EAN):** 4058352361948

**Product description:** SConsens,surf



SITECO ConnectExternal Interface S, slave, local control - self-sufficient standalone sensors, central control - connection to lighting or building management, dimmable, installation type: surface-mounted, installation location: to the ceiling, of plastic, protection rating (complete): IP54, insulation class (complete): insulation class II (safety insulation), certification: CE, VDE, 1 x packaging unit: 1 piece



Wt. (kg): 0.1

GTIN (EAN): 4058352361948

**Order No.:** 59US1FCSA | **GTIN (EAN):** 4058352361948

**Detailed technical description:** SConsens,surf



#### **Key data**

- System family: SITECO Connect 11, SITECO Connect 21
- Product type: sensor
- Product name: SITECO Connect
- Order No.: 59US1FCSA

**Lighting technology | Lamps | Control gear**

#### **Component 1**

##### **Operating device:**

- Control: DALI 2, dimmable

#### **Certificates, Standards**

- Protection rating: IP54
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): - 20..+50°C
- Certification, designation: CE, VDE

#### **Material, Colour**

- housing: plastic, white, square
- Colour specification: white

#### **Mounting**

- Mounting method, mounting location: surface-mounted, to the ceiling
- Supplement: only suitable for use in indoor areas

#### **Dimensions, Weight**

- Length: 83mm
- Width: 83mm
- Height: 28mm
- Weight: 0.1kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))  
Tolerances related to thermal, electrical and photometric data according to IEC 62722  
Issued 30.10.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -