


**Order No.:** 5LZ905731A | **GTIN (EAN):** 4058352692875

**Product description:** DA2,psh.bttm.interf,lokCtrlcentCtrl




DALI2push button interface, slave, local control, central control, dimmable, installation type: recessed, installation location: in the switch box, of plastic, protection rating (complete): IP20, certification: CE, 4 x push button input, 1 x DALI-2, packaging unit: 1 piece

IP 20 

Wt. (kg): 0.1  
GTIN (EAN): 4058352692875

Order No.: 5LZ905731A | GTIN (EAN): 4058352692875

Detailed technical description: DA2,psh.bttf.interf,lokCtrlcentCtrl



#### Key data

- System family: Siteco Connect 11, SITECO Connect 22
- Product type: lighting management components
- Product name: DALI2
- Order No.: 5LZ905731A

#### Lighting technology | Lamps | Control gear

##### Component 1

#### Operating device:

- Control: DALI 2, dimmable

#### Certificates, Standards

- Protection rating: IP20
- Temperature range (operation): 0..+40°C
- Certification, designation: CE

#### Material, Colour

- housing: plastic, black
- Colour specification: black

#### Mounting

- Mounting method, mounting location: recessed, in the switch box
- Supplement: only suitable for indoor use

#### Dimensions, Weight

- Length: 210mm
- Width: 20mm
- Height: 10mm
- Weight: 0.1kg

#### Inputs

##### 4x push button input

- Connection: cable pair (2-pole), A=0.25mm<sup>2</sup>, colour coding of cables, with pre-assembled wire end sleeve
- Feature: zero-potential

#### Outputs

##### 1x DALI-2

- System current: max. 10mA