

Order No.: 59TL3MNE | GTIN (EAN): 4058352471746

Product description: Lic-cent.feed-I/O,L650,14x2.52,IP40,bk



Licross® central feed for 1x feed-in / 1x feed-out, matt jet black (RAL 9005); wiring trunking rail element of sheet steel, galvanised, coated, with cable entry for six cables, Ø 8.5..13mm; blank cover of PC/ABS, jet black (RAL 9005), 2x connector of steel, galvanised, connector pre-assembled on trunking rail; connection via terminal, 14-pole, 1.5..2.5mm², wired ready for connection, internal wiring halogen-free; dimension: (LxWxH) = 650 x 64 x 67mm; for IP20/IP40 protection rating; insulation class: insulation class I (protective earthing); certification: CE, UKCA; packaging unit: 1 piece

(<u>L</u>)

 \in

Wt. (kg): 2.0

GTIN (EAN): 4058352471746



Order No.: 59TL3MNE | GTIN (EAN): 4058352471746

Detailed technical description: Lic-cent.feed-I/O,L650,14x2.52,IP40,bk



Key data

Product type: additional feed
Product name: Licross®
Order No.: 59TL3MNE

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Supplement: for connection on rail side

Component 2

Component 3

Certificates, Standards

- Protection rating: for IP20/IP40 protection rating
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE, UKCA

Material, Colour

- trunking rail element: sheet steel, galvanised, coated, matt jet black (RAL 9005)
- Colour specification: matt jet black (RAL 9005)
- blank cover: PC/ABS, jet black (RAL 9005)
- Colour specification: jet black (RAL 9005)
- connector: steel, galvanised, connector pre-assembled on trunking rail
- Quantity: 2 piece

Electrical connection

- Connection: terminal, 14-pole, 1.5..2.5mm²
- Through-wiring: 14x 2.5mm²

Dimensions, Weight

Length: 650mmWidth: 64mmHeight: 67mmWeight: 2.0kg