

Order No.: 5EA40LH01 | GTIN (EAN): 4058352450239

Product description: SConWi,MotionHigh



SITECO Connect WirelessMotion High, Smart Interface below, setting of the ECG to logarithmic DALI dimming required, installation type: screw fastening, installation location: to the luminaire, of plastic, voltage: 24V, voltage type: DC, Bluetooth, D4i, local setting and operation with smartphone app, by daylight, by movement, 1 PIR movement sensor, daylight sensor, PIR movement sensor, protection rating (complete): IP66, certification: CE, UKCA, packaging unit: 1 piece

IP 66 IK 09 CE

Wt. (kg): 0.1
GTIN (EAN): 4058352450239

Order No.: 5EA40LH01 | GTIN (EAN): 4058352450239

Detailed technical description: SConWi,MotionHigh



Key data

- Product type: sensor
- Product name: SITECO Connect Wireless
- Order No.: 5EA40LH01

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: D4i, Smart Interface below, setting of the ECG to logarithmic DALI dimming required

Certificates, Standards

- Protection rating: IP66
- Impact resistance: IK09
- Temperature range (operation): -40..+70°C
- Standard: according to Zhaga book 18
- Certification, designation: CE, UKCA

Material, Colour

- housing: plastic, grey
- Colour specification: grey

Mounting

- Mounting method, mounting location: screw fastening, to the luminaire
- Mounting height: 4..12m

Electrical connection

- Nominal voltage: 24V, DC

Dimensions, Weight

- Weight: 0.1kg

Inputs

PIR movement sensor

- Detection range: D max. 30m
- Feature: incl. shield for reducing detection area

Order No.: 5EA40LH01

Dimensions: SConWi, Motion

Y axis



Mounting height	X axis	Y axis
4.6 m	12.0 m	12.0 m
8.0 m	24.0 m	24.0 m
12.0 m	30.0 m	30.0 m

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 22.12.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -