

Order No.: 5EA40EH01 | GTIN (EAN): 4058352450178 Product description: SConWi,SmartPlugMotionHigh





SITECO Connect WirelessSmart Plug Motion High, Smart Interface below, installation type: screw fastening, installation location: to the luminaire, of plastic, voltage: 24V, voltage type: DC, 2.4GHz, local mesh radio network, D4i, local setting and operation with USB stick, by daylight, by movement, manual, by time, by timer, by weekday, via API, optionally via radio push button, 1 PIR movement sensor, daylight sensor, temperature sensor, inclination sensor, PIR movement sensor, brightness sensor, radio, 2.4GHz, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 (€

Wt. (kg): 0.1

GTIN (EAN): 4058352450178



Order No.: 5EA40EH01 | GTIN (EAN): 4058352450178

Detailed technical description: SConWi,SmartPlugMotionHigh



Key data

Product type: sensor

Product name: SITECO Connect

Wireless

Order No.: 5EA40EH01

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: D4i, Smart Interface below

Certificates, Standards

- Protection rating: IP66
- Temperature range (operation): -40..+85°C
- Standard: according to Zhaga book 18
- Certification, designation: CE

Material, Colour

- housing: plastic, transparent, colourbacked, dark grey
- Colour specification: dark grey

Mounting

- Mounting method, mounting location: screw fastening, to the luminaire
- Mounting height: 6..12m

Electrical connection

Nominal voltage: 24V, DC

Dimensions, Weight

- Weight: 0.1kg

Inputs

PIR movement sensor

- Detection range: D max. 18m



Order No.: 5EA40EH0 Dimensions: SConWi,Sm.

| Mounting height | X axis | Y axis |
|-----------------|--------|--------|
| 7.0 m | 11.9 m | 12.4 m |
| 8.0 m | 13.6 m | 14.2 m |
| 9.0 m | 15.3 m | 15.9 m |
| 10.0 m | 17.0 m | 17.7 m |