

Order No.: 5EA40EL01 | GTIN (EAN): 4058352450208 Product description: SConWi,SmartPlugMotionLow





SITECO Connect WirelessSmart Plug Motion Low, Smart Interface below, installation type: screw fastening, installation location: to the luminaire, of plastic, voltage: 24V, voltage type: DC, 2.4GHz, local mesh radio network, D4i, local setting and operation with USB stick, by daylight, by movement, manual, by time, by timer, by weekday, via API, optionally via radio push button, 1 PIR movement sensor, daylight sensor, temperature sensor, inclination sensor, PIR movement sensor, brightness sensor, radio, 2.4GHz, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 (€

Wt. (kg): 0.1

GTIN (EAN): 4058352450208



Order No.: 5EA40EL01 | GTIN (EAN): 4058352450208

Detailed technical description: SConWi,SmartPlugMotionLow



Key data

Product type: sensor

Product name: SITECO Connect Wireless

Order No.: 5EA40EL01

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: D4i, Smart Interface below

Certificates, Standards

- Protection rating: IP66
- Temperature range (operation): -40..+85°C
- Standard: according to Zhaga book 18
- Certification, designation: CE

Material, Colour

- housing: plastic, transparent, colourbacked, dark grey
- Colour specification: dark grey

Mounting

- Mounting method, mounting location: screw fastening, to the luminaire
- Mounting height: 0..6m

Electrical connection

Nominal voltage: 24V, DC

Dimensions, Weight

- Weight: 0.1kg

Inputs

PIR movement sensor

- Detection range: D max. 11m





Order No.: 5EA40EL01

Dimensions: SConWi,Sm.

Mounting height	X axis	Y axis
5.0 m	8.5 m	8.8 m
6.0 m	10.2 m	10.6 m